AD-E300 451

**DNA 4590F**

AD A0 65388

# WIND-TUNNEL SHOCK-TUBE SIMULATION AND EVALUATION OF BLAST EFFECTS ON AN ENGINE INLET

Kaman AviDyne
83 Second Avenue
Burlington, Massachusetts 01803

15 March 1978

Final Report for Period October 1975—December 1977

CONTRACT No. DNA 001-76-C-0107

APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION UNLIMITED.

Prepared for

Director

DEFENSE NUCLEAR AGENCY

Washington, D. C. 20305

D D C
RECEIVED
MAR 7 1979
B

79 01 22 090

Destroy this report when it is no longer
needed. Do not return to sender.

PLEASE NOTIFY THE DEFENSE NUCLEAR AGENCY,
ATTN: TISI, WASHINGTON, D.C. 20305, IF
YOUR ADDRESS IS INCORRECT, IF YOU WISH TO
BE DELETED FROM THE DISTRIBUTION LIST, OR
IF THE ADDRESSEE IS NO LONGER EMPLOYED BY
YOUR ORGANIZATION.

## REPORT DOCUMENTATION PAGE

READ INSTRUCTIONS
BEFORE COMPLETING FORM

| 1. REPORT NUMBER <br> DNA 4590F | 2. GOVT ACCESSION NO. <br> AD-E300 45 | 3. RECIPIENT'S CATALOG NUMBER |
|---|---|---|

**4. TITLE (and Subtitle)**
WIND-TUNNEL SHOCK-TUBE SIMULATION AND EVALUATION OF BLAST EFFECTS ON AN ENGINE INLET.

**5. TYPE OF REPORT & PERIOD COVERED**
Final Report for Period
Oct 75—Dec 77,

**6. PERFORMING ORG. REPORT NUMBER**
KA-TR-147

**7. AUTHOR(s)**
J. Ray Ruetenik
Robert F. Smiley

**8. CONTRACT OR GRANT NUMBER(s)**
DNA 001-76-C-0107

**9. PERFORMING ORGANIZATION NAME AND ADDRESS**
Kaman AviDyne
83 Second Avenue
Burlington, Massachusetts 01803

**10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS**
NWED Subtask N99QAXAE510-14

**11. CONTROLLING OFFICE NAME AND ADDRESS**
Director
Defense Nuclear Agency
Washington, D.C. 20305

**12. REPORT DATE**
15 March 1978

**13. NUMBER OF PAGES**
236

**14. MONITORING AGENCY NAME & ADDRESS(if different from Controlling Office)**

240 p.

**15. SECURITY CLASS (of this report)**
UNCLASSIFIED

**15a. DECLASSIFICATION/DOWNGRADING SCHEDULE**

**16. DISTRIBUTION STATEMENT (of this Report)**

Approved for public release; distribution unlimited.

**17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)**

**19. KEY WORDS (Continue on reverse side if necessary and identify by block number)**

| | | | |
|---|---|---|---|
| Aircraft | Computer Studies | Inlet | Shock Tube |
| Blast | Engine | Pressure | Subsonic |
| B-1 | Experimental Test | Shock | Wind Tunnel |

This report describes a program for simulating

**20. ABSTRACT (Continue on reverse side if necessary and identify by block number)**

A development and test program is described for simulation of blast wave
intercepts with a scaled aircraft engine in subsonic flight, using the shock
tube technique for firing the blast-type waves. The program initially con-
sisted of preliminary theoretical calculations and tests with two-inch-
diameter shock tubes fired into the AEDC 1T transonic tunnel, followed by the
design, construction and testing of three large 22.6 inch-diameter shock
tubes. These shock tubes were installed in the AEDC 16T (16 foot square)

DD FORM 1473 1 JAN 73 EDITION OF 1 NOV 65 IS OBSOLETE

*Φ deg and 5 deg.*

## 20. ABSTRACT (Continued)

transonic wind tunnel and were used to project blast waves at a 0.1-scale B-1 aircraft model. Forty-five firings were made, covering tunnel speeds of Mach 0, 0.55, 0.70, 0.85 and 0.90, blast overpressures (scaled to 1 atm. ambient pressure) from 2 to 6 psi, 0° and 5° yaw, and inlet flow rates representative of cruise and maximum power conditions. The model inlets were instrumented with 40 combination steady-state and dynamic total-pressure probes at each engine face section and other dynamic transducers to measure incident blast wave properties and inlet internal ramp and cowl pressures. The test data were digitized and used to determine time histories of inlet distortion during the blast encounter.

Calculations of blast pressures in the inlets made with the KA BID code satisfactorily reproduced the principal features of the observed inlet duct and engine face pressures.

Blast-induced distortions during the time of definite blast-type flow in the inlet were generally smaller than but did sometimes exceed normal inlet allocation levels for the B-1 aircraft. Distortions at later times greatly exceeded this allocation.

Four potentially adverse effects to engine operation from blast interaction were identified: blast-induced distortion, fan choking, afterburner blow-out and shock-boundary layer induced distortion.

PREFACE

This work was performed by the AviDyne Division of the Kaman Sciences Corporation for the Defense Nuclear Agency under Contract DNA-001-76-C-0107. MAJ David W. Garrison of the DNA Shock Physics Directorate served as technical monitor to July 31, 1977, and CAPT Michael Rafferty from August 1, 1977, through the remainder of the program.

Dr. J. Ray Ruetenik of Kaman AviDyne was the project leader under Dr. Norman P. Hobbs, Technical Director of KA. Mr. Robert F. Smiley performed engineering functions. Professor Jack L. Kerrebrock, Professor and Director of the Gas Turbine and Space Propulsion Laboratories, MIT, served as technical consultant on propulsion.

Appreciation is expressed to MAJ Garrison and CAPT Rafferty for their continuing interest and significant support of this program. Appreciation is also expressed to CAPT William Tuck, AEDC, for test coordination, and the ARO personnel for their dedicated work, in particular Mr. H. Eldon McDill and Mr. Richard J. Christenson, Test directors of the 1T and 16T tests, respectively, and Mr. Karl F. Thormaehlen, mechanical engineer. Appreciation is also extended to Rockwell International personnel, particularly Mr. Ray L. Noonan, Mr. W. Robert Haagenson and Mr. Clarence E. Mitchell, for their contributions to the test program.

## Conversion factors for U.S. customary to metric (SI) units of measurement.

| To Convert From | To | Multiply By |
|---|---|---|
| angstrom | meters (m) | 1.000 000 X E -10 |
| atmosphere (normal) | kilo pascal (kPa) | 1.013 25 X E +2 |
| bar | kilo pascal (kPa) | 1.000 000 X E +2 |
| barn | meter$^2$ (m$^2$) | 1.000 000 X E -28 |
| British thermal unit (thermochemical) | joule (J) | 1.054 350 X E +3 |
| calorie (thermochemical) | joule (J) | 4.184 000 |
| cal (thermochemical)/cm$^2$ | mega joule/m$^2$ (MJ/m$^2$) | 4.184 000 X E -2 |
| curie | *giga becquerel (GBq) | 3.700 000 X E +1 |
| degree (angle) | radian (rad) | 1.745 329 X E -2 |
| degree Fahrenheit | degree kelvin (K) | $t_K = (t°f + 459.67)/1.8$ |
| electron volt | joule (J) | 1.602 19 X E -19 |
| erg | joule (J) | 1.000 000 X E -7 |
| erg/second | watt (W) | 1.000 000 X E -7 |
| foot | meter (m) | 3.048 000 X E -1 |
| foot-pound-force | joule (J) | 1.355 818 |
| gallon (U.S. liquid) | meter$^3$ (m$^3$) | 3.785 412 X E -3 |
| inch | meter (m) | 2.540 000 X E -2 |
| jerk | joule (J) | 1.000 000 X E +9 |
| joule/kilogram (J/kg) (radiation dose absorbed) | Gray (Gy) | 1.000 000 |
| kilotons | terajoules | 4.183 |
| kip (1000 lbf) | newton (N) | 4.448 222 X E +3 |
| kip/inch$^2$ (ksi) | kilo pascal (kPa) | 6.894 757 X E +3 |
| ktap | newton-second/m$^2$ (N-s/m$^2$) | 1.000 000 X E +2 |
| micron | meter (m) | 1 000 000 X E -6 |
| mil | meter (m) | 2.540 000 X E -5 |
| mile (international) | meter (m) | 1.609 344 X E +3 |
| ounce | kilogram (kg) | 2.834 952 X E -2 |
| pound-force (lbs avoirdupois) | newton (N) | 4.448 222 |
| pound-force inch | newton-meter (N·m) | 1.129 848 X E -1 |
| pound-force/inch | newton/meter (N/m) | 1.751 268 X E +2 |
| pound-force/foot$^2$ | kilo pascal (kPa) | 4.788 026 X E -2 |
| pound-force/inch$^2$ (psi) | kilo pascal (kPa) | 6.894 757 |
| pound-mass (lbm avoirdupois) | kilogram (kg) | 4.535 924 X E -1 |
| pound-mass-foot$^2$ (moment of inertia) | kilogram-meter$^2$ (kg·m$^2$) | 4.214 011 X E -2 |
| pound-mass/foot$^3$ | kilogram/meter$^3$ (kg/m$^3$) | 1.601 846 X E +1 |
| rad (radiation dose absorbed) | **Gray (Gy) | 1.000 000 X E -2 |
| roentgen | coulomb/kilogram (C/kg) | 2.579 760 X E -4 |
| shake | second (s) | 1.000 000 X E -8 |
| slug | kilogram (kg) | 1.459 390 X E +1 |
| torr (mm Hg, 0° C) | kilo pascal (kPa) | 1.333 22 X E -1 |

*The becquerel (Bq) is the SI unit of radioactivity; 1 Bq = 1 event/s.
**The Gray (Gy) is the SI unit of absorbed radiation.

A more complete listing of conversions may be found in "Metric Practice Guide E 380-74," American Society for Testing and Materials.

## TABLE OF CONTENTS

TABLE OF CONTENTS (CONCL'D)

## LIST OF ILLUSTRATIONS

5

LIST OF ILLUSTRATIONS (Cont'd)

LIST OF ILLUSTRATIONS (CONT'D)

7

## LIST OF ILLUSTRATIONS (CONCL'D)

## LIST OF TABLES

# SECTION I

## INTRODUCTION

This study is concerned with the simulation of the situation where an aircraft inlet is subjected to a blast wave of sufficient strength and long enough duration to produce significant distortion of the flow field at the engine face. For critically designed engine-inlet systems, such blasts, produced by nuclear explosions, might cause severe engine stall or flameout problems.

The objective of the test program reported here was to develop a test technique for measuring blast interaction with an aircraft inlet and to conduct a series of tests for the development of prediction methods.

Wind tunnels provide a well-developed means for the simulation of flight flow conditions for an engine inlet. A technique for the simulation of blast waves in a supersonic wind tunnel by employing a shock tube mounted in the wind tunnel wall has been demonstrated by Pierce (Ref. 1.1).

A development and test program, conducted at the Arnold Engineering Development Center (Ref. 1.2), is reported here for the simulation of blast wave intercepts with a scaled aircraft inlet in subsonic flight using the shock-tube technique for firing the blast-type waves. Pilot tests of the technique were performed in a 1-ft wind tunnel during August 1975, followed by "bench" tests of a prototype shock tube during August 1976. A wind tunnel test program then was conducted in the AEDC 16T wind tunnel with a 0.1-scale B-1 inlet during September 24-28, 1976.

This report is concerned primarily with documentation of the development of the facility to test the response of engine-inlet systems to blast waves in high speed wind tunnels, with the presentation of test results from the facility for a 0.1-scale aircraft inlet, and with the discussion and application of associated analytical techniques to predict inlet behavior in a blast environment.

Section 2 of the report describes preliminary analytical studies and small model wind tunnel tests performed to assess the feasibility of performing well controlled inlet blast tests in a high speed wind tunnel with blast waves produced by shock tubes fired into the tunnel. Section

11

3 describes the subsequent development of a large shock tube facility for use in the AEDC 16T (16 foot square) transonic wind tunnel (Ref. 1.2). Section 4 describes and presents sample results of a blast test program performed in this facility, using three 23 in.-diameter shock tubes and a 0.1-scale B-1 inlet model. Section 5 presents a general analysis of the test results, pointing out some basic characteristics of the inlet blast interaction process and presenting an analysis of the inlet distortion measurements obtained during the tests.

Section 6 presents a comparison of experimental blast pressure time histories with theoretical calculations made with the BID computer code. Section 7 supplements the test results by presenting some blast calculations made with the BID code to illustrate some blast-inlet interaction effects over a greater range of blast intercept angles than were covered by the tests.

Section 8 discusses the interaction of a blast-induced inlet shock with an engine fan and Section 9 discusses blast-induced boundary layer interactions in an inlet.

The overall study results are discussed in Section 10 and conclusions are given in Section 11.

Appendix A discusses some theoretical studies of the firing of a shock tube into a stationary fluid. Appendix B presents the steady-state pre-blast measurements made during the 16T tests.

## SECTION II
## PRELIMINARY INVESTIGATION FOR DEVELOPMENT OF TEST TECHNIQUE

As the first stage of the development of a wind-tunnel shock-tube
blast test facility, a program of preliminary theoretical calculations
and model tests was undertaken to establish the feasibility of the test
concept and to provide design information for construction of a full-
scale installation.

### 2.1 THEORETICAL STUDIES-REFLECT/S2D

The first development step consisted of theoretical calculations
for the problem of a circular shock tube fired into stationary air.
These calculations, made with the Kaman AviDyne REFLECT-2 and S2D computer
codes (see Appendix A) indicated that useful shock wave patterns simulating
nuclear blast wave patterns in the 2 to 5 psi overpressure range could
be obtained at distances 3 to 10 diameters downstream of the end of a
shock tube.  In particular, these calculation results, summarized in
Appendix A, indicated that, at a distance of about 4.5 diameters down-
stream of the end of a shock tube, a blast duration of nearly constant
overpressure could be obtained for about 2.5 milliseconds per foot of
tube diameter.

### 2.2 SHOCK TUBE FIRINGS IN AEDC 1T WIND TUNNEL

Using the results of the above theoretical calculations as a
guideline, a small 2 in.-dia shock tube was constructed and was fired
into the AEDC 1T (one-foot-square) transonic wind tunnel for a wide
range of flow and shock tube conditions, during which pressure measurements
were made for a large number of locations inside the wind tunnel.

The geometric setup used in the AEDC 1T tunnel is indicated in
Figure 2.1.  Three shock tube configurations were tested, about 14
inches long, with ratios of the driven-tube lengths to driver-tube
lengths of about 0.5, 2 and 8.  The end of each shock tube protuded into
the tunnel by about one inch (perpendicular to the floor) where it was
terminated by a 8 in-dia. circular flange (Fig. 2.1).  Firings were made
with the angle of the shock tube axis to the tunnel axis, $\Phi$, (see
Figure 2.1), being $90^{\circ}$, $60^{\circ}$ and $45^{\circ}$.  Tunnel ambient pressures were in

Figure 2.1. Test setup for blast tests in the AEDC 1T transonic wind tunnel (tunnel side walls removed).

the range 11 to 16 psia and shock tube driver pressures ranged from about 60 to 380 psia.

Transient blast pressure measurements were made inside the wind tunnel by means of pressure transducers imbedded in the surface of a thin plate placed in the plane of symmetry, as shown in Figure 2.1. Measurements were made of local blast pressure time histories for radial distances from the shock tube exit of 2.5, 3.5 and 4.5 tube diameters (r/d) and for polar angle locations ($\theta$ in Fig. 2.1) of $-15^o$, $0^o$, $15^o$, $30^o$, $45^o$, $60^o$ and $75^o$. Also, for several locations, measurements of transient total pressure and flow velocities were made with two total-pressure and two claw probes mounted about a half inch from the face of the thin plate, as shown in the figure. Kulite XCQL-093-025 pressure transducers were used in the plate and probes.

Sample shadowgrams showing the blast field produced by firing the 2-in shock tube into the wind tunnel are presented in Figures 2.2 and 2.3. Figure 2.2 shows three shadowgrams of one firing into still air and Figure 2.3 shows two shadowgrams for a firing into a Mach 0.8 tunnel flow. The shadowgrams are taken looking into the side of the tunnel, with the tunnel flow proceeding from left to right, and with the shock tube being fired into the tunnel vertically up ($\Phi=90^o$) through the bottom wall of the tunnel.

In Figure 2.2, the lowest shadowgram was taken first (before blast exit from the tubes) and the upper one last. The blast front can be clearly seen in these shadowgrams and becomes essentially a circular arc after the front of the blast wave has moved several tube diameters away from the tube exit. In the upper shadowgram of Figure 2.2, between the top of the blast front and the shock-tube exit is seen a nearly horizontal dark line which roughly delineates the contact surface between the "hot" tunnel air (above) and the "cold" expanded air (below) from the driver section of the shock tube. This cold gas can also be more clearly seen as the dark jet core in Figure 2.3. From the viewpoint of simulating a nuclear blast or other long-duration blast wave, it should be noted that only that portion of the blast wave lying between the blast front and the hot-cold gas contact surface is of interest.

Figure 2.2.   Shadowgrams of blast field produced by firing a shock tube
into air at rest, $\phi = 90^{\circ}$.

Figure 2.3.   Shadowgrams of blast field produced by firing a shock tube
into a wind tunnel at Mach 0.80, $\Phi = 90^{\circ}$.

The effect of the tunnel flow on the shape of the blast shock front was found to be relatively small in the sense that the blast front shape remained essentially circular for all Mach numbers tested (up to 0.9), but, of course, the pattern is convected downstream more with increasing tunnel speed. The central cold-gas core also tends to be convected downstream (Fig. 2.3), but less so than the blast front.

Pressure time histories obtained from all transducers were digitized by ARO and were subsequently provided in the form of plots, tabulations and magnetic tapes (Ref. 2.1).

Sample pressure measurements in the blast field are shown in Figure 2.4 for the shock tube normal to the tunnel axis, $\Phi=90^{o}$, measured at a radial distance of 4.5 tube diameters from the tube exit, at a tunnel Mach number of 0.8 and a ratio of tube driver pressure to driven pressure of about 10. It should be noted that for a polar angle ($\theta$ in Figure 2.1) of $15^{o}$ a blast wave is produced with a nearly constant pressure level for about 0.2 milliseconds. In the polar angle range $-15^{o}$ to $30^{o}$ useful nearly-constant blast durations of at least 0.1 millisecond are seen to have been produced; but for larger angles ($\theta \geq 45^{o}$) the pressure has an initial spike-behavior which makes it of little value for simulating blast shocks of long duration.

Similar results to those shown in Figure 2.4 were obtained for most conditions tested, covering shock-tube angles ($\Phi$) of 45, 60 and 90 degrees to the tunnel axis, tunnel Mach numbers of 0, 0.6, 0.75 and 0.9 and driver/driven-tube pressure ratios between about 4 and 30. Useful nearly-constant pressure blast durations up to a maximum of about 0.3 millisecond were obtained for some conditions.

In order to provide a more quantitative index of the obtained duration of nearly constant pressure, estimates were made for the $90^{o}$ tube angle ($\Phi = 90^{o}$) from curves like Figure 2.4 of the time, $t_{30}$, required for the blast overpressure to decay (or increase) 30 percent from the initial shock value. For blast overpressures between 2 and 5 psi at a radial distance of 4.5 diameters (r/d = 4.5), the 30-percent-

18

Figure 2.4. Transient blast pressures for a firing of a shock tube into a Mach 0.75 wind tunnel flow, $\Phi = 90^{\circ}$.

decay time was found to generally increase about linearly with increasing overpressure.  In the 4 - 5 psi overpressure range the decay time was about 0.16 msec or 1 msec/ft. dia. for a polar angle ($\theta$) of $0^o$ and about 0.09 msec or 0.5 msec/ft for $30^o$, and did not appear to vary much with Mach number.  For a polar angle of $15^o$ the decay time decreased considerably with increasing Mach number; at the 5 psi level, it appeared to vary from about 0.3 msec or 2 msec/ft at Mach 0.6 to about 0.18 msec or 1.1 msec/ft at Mach 0.9.

The angle of the tubes to the tunnel axis ($\phi$) had a marked effect on the blast waves that were produced.  As the angle was reduced, causing the blast to be fired more in the downstream direction, the resulting shock overpressure was lower and the overpressure at a fixed point decayed more rapidly.  Satisfactory results were obtained for the tube at 90 degrees to the tunnel axis, so this angle was selected for later development of a large shock tube facility.

Blast pressure waveforms were found to be relatively insensitive to the shock-tube driven-tube/driver length ratio in the useful early-time (hot-gas) part of the flow period.  Hardly any difference was observed between the waveforms for the length ratios of 0.5 and 2.0, but some waveforms for the length ratio of 8 had somewhat shorter nearly-constant durations than those for the other length ratios.

To summarize the test results, it appeared that useful long duration blast waves could be obtained by firing shock tubes into a wind tunnel operating at speeds up to at least Mach 0.9.  Nearly constant pressure blast durations lasting up to a maximum of about 2 milliseconds per foot of tube diameter were obtained for some firing conditions and the longest duration of nearly constant pressure blast waves was obtained at polar angles ($\theta$) from the shock tube of about $15^o$.

## SECTION III
## DEVELOPMENT OF 16T BLAST TEST FACILITY

Having established the feasibility of shock tube-wind tunnel blast tests by small model tests in the 1T tunnel, a program was undertaken to develop and apply a similar large shock tube facility for engine inlet testing in the AEDC 16T (sixteen foot square) transonic wind tunnel (Ref. 2.1). Development of this facility consisted of selection and modification of a inlet model, shock tube design, construction and testing, selection of dynamic instrumentation for measuring the blast field, and tunnel modifications.

The test installation was designed to take as much advantage as possible of existing hardware and fixtures.

### 3.1 GENERAL DESIGN CRITERIA

The inlet model selected for blast testing in the AEDC 16T tunnel is designated as the 0.1-scale B-1 Inlet Development Model II. This model was selected as having a representative transonic inlet of modern design which was already well instrumented with dynamic pressure engine face transducers of high enough frequencies to respond to blast induced transients. The model required only small modifications to strengthen it for blast testing and it was compatible with existing mounting fixtures for the 16T tunnel.

The important features of the model with respect to shock tube design are the size of the inlet opening, which is about 5.5" long by 4.4" wide by 3.3" high for each inlet, and the length of the inlet, about 25". Other model characteristics are discussed in Section 4.2.

The shock tubes had to be designed to produce a sufficiently small variation of incident shock pressure across the above inlet opening. Also the duration of the blast wave produced had to be at least long enough so that the blast wave does not decay significantly before its front has had time enough to pass down the inlet into the engine and to be reflected back past the engine face.

21

It appeared that the most cost-effective facility design satisfying the above requirements was to position the test model near the center of the tunnel, permitting use of existing fixtures, and to mount shock tubes in both tunnel walls, two in one wall and one in the other, as indicated in Figures 3.1 and 3.2. This design concept, using three shock tubes, permitted the firing of three blast waves at the model before the tunnel had to be shut down to change shock tube diaphragms, thus saving considerable time and expense. Dimensions and orientations of the three shock tubes were chosen to conform as close as practical to the optimum conditions obtained from the 1T model tests, namely, ratio of tube-to-inlet distance to tube diameter of about 4.5, polar angles from shock tube to inlet ($\theta$) between $-15^o$ and $+30^o$, with about $15^o$ being optimum, and shock tube axis perpendicular to tunnel wall ($\Phi=90^o$). A common inside diameter of 22.6 inches appeared to be the best choice, which gave distance/diameter ratios of 4.3, 3.8 and 4.3 for shock tubes 1, 2, and 3, respectively. The resulting geometrical arrangement of tunnel, shock-tubes and model is shown schematically in Figure 3.1 and photographs of the setup are presented in Figure 3.2.

With respect to the question as to how uniform the blast pressure would be across the inlet opening, the results of the 1T tests indicated that for the above-selected model and shock tube geometry, the intensity of the blast wave would generally vary across one inlet not more than $\pm$ 2 percent from the mean value and at worst not exceeding $\pm$ 4 percent.

## 3.2  SHOCK TUBE DESIGN AND TESTING

Using the guidelines discussed in Section 3.1, ARO designed and constructed three similar 22.6 in-dia[*] shock-tube blast generators for

---

[*]A necked down shock tube driven section having a 13.1-inch exit diameter was also designed as an insert for any of the three shock tubes. This smaller diameter insert was constructed and several static firings were made with it to explore the possibility of obtaining a better blast waveform at low blast pressures than could be obtained with the large diameter tubes. This insert was also intended to provide more flexibility in the range of blast overpressures which could be obtained with a particular pair of diaphrams. However, the few firings made with this insert produced no obviously improved waveforms and the time required to install and remove the insert from a shock tube when installed in the 16T wind tunnel proved to be too long to be tolerated for the limited test time available. Consequently, no wind tunnel firings were made with the small diameter driven section insert.

22

Figure 3.1. Top view of test installation in AEDC wind tunnel.

(a) View looking downstream.

Figure 3.2. Blast test setup in the AEDC 16T transonic wind tunnel.

24

(b) View showing model forebody and west wall.

Figure 3.2. Continued.

(c) View showing model, supports and east wall.

Figure 3.2. Concluded.

firing shock waves into the AEDC 16T tunnel. Some details of one of these tubes can be seen in Figure 3.3. The shock tube is about 17 feet long. The driven-tube length is about twice the driver tube length. The tube has a double diaphragm construction, and uses pre-scored pre-stressed 24 in-dia diaphragms. Diaphragms are constructed either of aluminum, nickel steel or 316 stainless steel, depending on the firing pressure level.

All three shock tubes had essentially the same design dimensions except that the ratio of the length of the driven section to that of the driver section had to be varied somewhat to permit close mounting of two of the tubes side by side in the 16T tunnel without interference. Judging from the results of the 1T tests (Sec. 2.2), these differences in lengths would not be expected to produce any significant differences between the blast waves generated by the three tubes.

Considerable effort was devoted to the design and operational use of the diaphragms. A series of 17 static firings was run to establish the range of loading pressures and other requirements for achievement of satisfactory diaphragm bursts in respect to the blast wave produced and avoidance of ejecta. A typical diaphragm break pattern is shown in Figure 3.4. The diaphragms generally broke cleanly on the pre-scored lines, forming four petals, and never produced any observable flying metallic debris.

Shock-tube operations were automated as much as possible in order to obtain a maximum number of firings in the few test days available for wind tunnel testing. Semi-automated diaphragm removal and replacement required less than 15 minutes per diaphragm pair and nearly fully automated pressurization and firing of a shock tube generally took less than 5 minutes.

The above-mentioned 17 static firings, made in the AEDC 16S wind tunnel facility at an ambient pressure of 0.5 atmosphere at driver pressures from 62 to 233 psia, were also utilized to obtain measurements of blast overpressures and impact pressures produced by the shock tube flow, both for protective design of wind tunnel equipment to be in the path of the jet from the shock tube and for providing a guide for diaphram

27

Figure 3.3. 23-inch-diameter shock tube setup for testing.

AEDC/ARO,Inc.

Figure 3.4.   Typical diaphragm rupture pattern.

selection to achieve desired levels of blast overpressure at the test
model during wind tunnel firings.

## 3.3  BLAST INPUT INSTRUMENTATION

In order to provide measurements of blast wave intensity and direction
as the blast wave strikes the inlet, three similar claw probes were
designed to be mounted on or near the test model.  Figure 3.5 shows a
photograph of one of these probes mounted above the tested inlet.  Each
probe consists basically of two $45^{\circ}$-swept claw arms ($90^{\circ}$ apart) with
Kulite series XCQL-093-025 type dynamic pressure transducers at the
tips, to measure total pressure and flow direction, and of a flat plate
surface toward the rear of the probe with one static pressure orifice
and one imbedded Kulite LQ series wafer pressure transducer to measure
the pre-blast and transient "static" blast pressures, respectively.  The
three claw probes were calibrated in the AEDC 16T tunnel for sideslip
angles from about -50 to + 50 degrees at Mach numbers of 0.6, 0.7, 0.85
and 0.95. The calibration data indicated that the probes could provide
reasonable estimates of flow characteristics for sideslip angles between
about -30 and +30 degrees.

## 3.4  TUNNEL WALL MODIFICATIONS

Preliminary KA estimates of the forces which would be imposed on
the 16T wind tunnel wall opposite a firing shock tube indicated that the
local wall pressures could greatly exceed the tunnel wall design criterion
of 3 psi differential pressure.  To obtain design information on such
wall loads, during the shock tube calibration test (Sec. 3.2), ARO fired
one of the 22.6 in-dia shock tube at a large plate instrumented with an
array of pressure transducers.  Using these test results as a guideline,
the tunnel walls were strengthened in critical areas.  In the subsequent
test program in the wind tunnel, no damage was experienced to the tunnel
walls during any shock tube firing.

30

Figure 3.5. Oblique view of a claw probe mounted above the inlet model.

31

## SECTION IV
## 16T WIND TUNNEL BLAST TEST PROGRAM

Following development of the 16T wind tunnel blast test facility, a series of 45 wind tunnel shock tube firings were performed with the 0.1-scale B-1 inlet model. This section presents a discussion of the details of the test setup, instrumentation, and firing conditions and presents and discusses some aspects of sample data obtained from the tests.

### 4.1 GENERAL TEST SETUP

As was mentioned in Section 3, the test setup consisted of a 0.1-scale B-1 model installed in an inverted position near the center of the AEDC 16T transonic tunnel, with three shock tubes projecting through the tunnel side walls (Fig. 3.1). Figure 3.2 presents photographs of the model and shock tube setup inside the tunnel. Various details of model construction are shown in Figures 3.5, 4.1 and 4.2. During all tests the model was maintained at an angle of attack of +3 degrees.

Blast waves can be fired at the model inlet from any of the three 22.6 in-dia shock tubes seen projecting into the tunnel about 6 inches from the side walls in Figure 3.2. The shock-tube axes are perpendicular to the side walls ($\Phi=90^{o}$) and the axis of each tube is located at a fixed location between 1 and 4 feet upstream of the inlet opening, so that, for all three shock tubes, the inlet is located within the polar angle range ($\theta$) 12 to 29 degrees from the shock-tube exit (Figure 3.1), the angles being $28.3^{o}$, $11.2^{o}$ and $13.6^{o}$ for tubes 1, 2 and 3, respectively. These locations were chosen to give blast waves of as long duration as practical, whose fronts would generally strike the inlet roughly side-on or slightly from the rearward.

### 4.2 MODEL AND INSTRUMENTATION DETAILS

The most important features of the inlet model used for the blast test are illustrated in Figures 4.1 through 4.4 (see also Ref. 4.1). The model is a 0.1-scale representation of the forward part of the B-1 aircraft fuselage with a left-hand stub wing set at the $67.5^{o}$- sweep position and a left-hand dual inlet. The normally variable geometry

32

Figure 4.1. Details of inlet model and engine simulation. (Rockwell drawing)

Figure 4.2. Closeup view of engine inlet and claw probes in the AEDC 16T wind tunnel.

34

Figure 4.3.   Engine face transducer locations.   (Rockwell drawing)

N.S.
(FULL SCALE)
0

1020
(1902)
1702
1703
1030
(1903)
1704
1035(1904)
1701
1700
1435(1935)
1543
1450(1950)
1470(1970)
1573
1480(19
2450
2543
2435
2470
2573
2480
2703
2704
2702
2020
(2902)
2030
2035

20   40   60   80   100   120   140   160   180   20

COWL LIP

X=1, OUTB'D
X=2, INB'D

X902
X020
X935
X435
X970
X470
X480
X980
X950
X450
X903
X030
X904
X035

RA   RB   RC   RD or THROAT

O — RAMP ORIFICES (SOLID DENOTES KULITE)
□ — COWL ORIFICES ( "      "      " )
△ — UPR. SIDEPLATE ORIFICES
◇ — RAMP PLENUM ORIFICES
◉ — RAMP HINGE

Figure 4.4.

Figure 4.4. Inlet instrumentation. (Rockwell drawing)

inlet ramp system for the model was fixed for these tests in the normal subsonic cruise position. The engine face is located at Nacelle Station 269.5. The aircraft engine is simulated by an engine hub structure and by remotely actuated hydraulically operated flow control vanes which produce prescribed choked flow rates in the simulated engine at a position about 4.5 inches downstream of the engine face.

Forty combination steady-state and dynamic total-pressure probes are located in each inlet at the engine face section, located as indicated in Figures 4.3 and 4.4 and in Table 4.1. The dynamic probes used Kulite type CQL-080-25 transducers, which were found, from pre-test shock tube calibrations, to generally have response times to transient pulses of about 25 microseconds or less. These Kulite transducers had a 25-psi range, 0.080-in diameter and about 125 kHz natural frequency.

Other model instrumentation consisted of 54 static-pressure orifices and 10 dynamic Kulite transducers whose locations are described in Reference 4.1 (some indicated in Fig. 4.4). The 10 Kulite transducers, each accompanied by a static-pressure orifice, were mounted inside and flush with the inlet wall in the locations indicated in Figure 4.4 (also Fig. 5.4) and Table 4.1. These transducers were used to monitor inlet ramp and cowl pressures. All but one of these transducers were mounted in the outboard inlet.

Also mounted on the model were three claw probes, described in Section 3.3, to measure the characteristics of the blast wave at the model. Figures 3.5 and 4.2 indicate the locations of these three probes. Probe 2 was located just above the forward tip of the inlet; Probes 1 and 3 were located just above the wing surface, about 9.3 inches outboard and inboard of the inlet centerline, respectively, with their tips located at the same longitudinal station as the inlet cowl tips.

## 4.3  16T WIND TUNNEL TESTS

The 16T wind-tunnel blast test program was designed to obtain data on the blast response of the test model for a range of overpressures from 2 to 5 psi (scaled to 1 atmosphere ambient pressure) for tunnel

TABLE 4.1

LOCATIONS OF DYNAMIC PRESSURE TRANSDUCERS[+]

Engine face pressures (see Figure 4.3)

| TYPE | RADIUS (Inches) | ORIFICE NUMBER | | | | | | | |
|------|------|------|------|------|------|------|------|------|------|
| | | $\emptyset$=22.5 | 67.5° | 112.5° | 157.5° | 202.5° | 247.5° | 292.5° | 337.5° |
| Total | 1.025 | 801 | 806 | 811 | 816 | 821 | 826 | 831 | 836 |
| ↓ | 1.393 | 802 | 807 | 812 | 817 | 822 | 827 | 832 | 837 |
| | 1.683 | 803 | 808 | 813 | 818 | 823 | 828 | 833 | 838 |
| | 1.930 | 804 | 809 | 814 | 819 | 824 | 829 | 834 | 839 |
| ▼ | 2.149 | 805 | 810 | 815 | 820 | 825 | 830 | 835 | 840 |

Add 1000 to tube number for outboard inlet; add 2000 to tube number for inboard inlet.

Cowl unsteady-state pressures (see Figure 4.4 or 5.4)

| Transducer Number | | Type | Location | |
|------|------|------|------|------|
| Outboard | Inboard | | N.S.[*] | Remarks |
| 1902 | 2902 | Static | 8.90 | Buzz indicator |
| 1903 | – | " | 11.60 | Cowl static |
| 1904 | – | " | 16.50 | Cowl static |
| 1905 | – | " | 25.45 | Cowl static |

Ramp unsteady-state pressures outboard inlet (see Figure 4.4 or 5.4)

| 1935 | | Static | 6.90 | Third ramp |
|------|------|------|------|------|
| 1950 | | " | 7.91 | Aft ramp |
| 1970 | | " | 11.70 | Aft ramp |
| 1980 | | " | 17.42 | Aft ramp |
| 1990 | | " | 25.45 | Aft ramp |

[*]Nacelle station in inches (model scale).

[+]This page modified from Reference 4.1.

Mach numbers from 0.55 to 0.90 and for inlet flow rates representative of cruise and maximum power conditions. Table 4.2 outlines the test matrix which was followed to cover these conditions.

Tunnel testing was performed over a three night period, on 24 September and 27-28 September 1976. Testing consisted of calibrations, steady-state runs and a series of blast firings as described below. All tests were performed at below one atmosphere ambient pressures (usually 0.5 atmosphere) to minimize blast loads on the model and equipment, subject to the limit of a minimum Reynolds number per foot of 2.5 X $10^6$.

### 4.3.1 Unyawed Steady-State Tests

Prior to the blast tests, a series of unyawed steady-state runs were made covering all Mach number and inlet mass flow rate ranges of interest. These runs were made partly as a calibration of the inlet model vanes to control mass flow rate and partly to verify that the inlet steady-state distortion properties were the same as were found in previous tests of the model.

Steady state runs were also made immediately before each shock tube firing to provide reference (pre-blast) pressures at all dynamic pressure transducer locations. (The dynamic pressure transducers measure only changes of pressure; absolute pressures are obtained by adding pre-blast (steady-state) pressures to the dynamic pressures). Results of these pre-blast steady-state tests are presented in Appendix B.

### 4.3.2 Yawed Steady-State Tests

A few steady-state runs were made with the model at various yawed positions in the range -10 to +10 degrees, according to the schedule given in Table 4.3. These runs were made partly to calibrate the inlet flow controls under yawed conditions and partly to aid in assessing the quasi-steady late-time response of the inlet to the side-slip effects of blast waves of very long duration.

### 4.3.3 Shock Tube Firings

Forty-five shock tube firings were performed in the AEDC 16T tunnel at tunnel Mach numbers of 0, 0.55, 0.70, 0.85 and 0.90. Tests were

39

## TABLE 4.2

### NOMINAL TEST CONDITIONS

| Mach No. | Flight conditions | Mass flow (lb/sec[+]) | Overpressure[*] (psi) | Yaw (deg) |
|----------|-------------------|-----------------------|-----------------------|-----------|
| 0 | Parked | 0 | 4 | 0 |
| 0.55 | Cruise | 235 | 4 | 0 |
| 0.55 | Max. power | 350 | 4 | 0 |
| 0.70 | Cruise | 300 | 2,3,4 | 0 |
| 0.70 | Max. power | 350 | 2,3,4,5 | 0,5 |
| 0.85 | Cruise | 300 | 2,3,4,5 | 0 |
| 0.85 | Max. power | 350 | 4,5 | 0 |
| 0.90 | Max. power | 350 | 4 | 0 |

[+]Full scale values (divide by 100 to obtain model values)

[*]Scaled to ambient pressure of one atmosphere

## TABLE 4.3

### STEADY-STATE YAW CONDITIONS

| Mach no. | Flow rate (lb/sec) | Yaw angle range (deg) |
|----------|--------------------|-----------------------|
| 0.55     | 352                | -10 to +10            |
| 0.70     | 303                | -10 to +10            |
| 0.70     | 352                | -10 to +10            |
| 0.85     | 350                | -10 to +7.5           |

generally performed with the tunnel static pressure set at about 1/2 atmosphere, except for the Mach 0.55 runs, for which about 2/3 atmosphere was used. The inlet mass flow rate was generally set to simulate both cruise and maximum power flight conditions for each Mach number condition according to the schedule in Table 4.2. This schedule required testing at mass flow rates of about 235, 300, and 350 lb/sec (full scale)[*].

Tunnel steady-state pre-blast conditions are tabulated in Table 4.4 and Appendix B. Tunnel total temperature was $569^{\circ}$ ($\pm 1^{\circ}$) for all firings with the tunnel turned on and was $534^{\circ}$ R for the one static firing. Firings were made over a range of overpressures from about 2 to 6 psi, scaled to a tunnel ambient pressure of one atmosphere.[**]

Also presented in Table 4.4 are estimated values of the blast overpressure ($\Delta p$) and the blast intercept angle ($\phi$) as the blast wave strikes the inlet. The source and accuracy of these values is discussed subsequently in Section 4.6.

## 4.4 DATA REDUCTION

The test data obtained from each shock tube firing were digitized by ARO at time intervals of 10.45 microseconds for a total of 2048 samples per firing. The resulting digital data were provided to KA in the form of magnetic tapes and time history plots of most of the basic data and derived quantities (Ref. 4.2). Tabular time history printouts of a few variables were also provided by ARO.

## 4.5 SAMPLE TEST RESULTS

Pressure time histories for typical pressure transducers are presented in Figure 4.5 for a typical shock tube firing (Run 8/Part 573) to illustrate the major features of the test data. In general, in this figure, the ordinate label designates the variable measured and the vertical scale is always either pressure/$p_{t_o}$ or pressure/$p_o$ (the latter

---

[*] All mass flow rates in this report are scaled to full scale conditions. Model values are 1/100 of these values.

[**] It should be noted that all blast pressure values designated as $\Delta p$ in this report are all scaled to a tunnel ambient pressure of one atmosphere. Pressures not specifically designated as $\Delta p$, such as shock tube driver pressures in Table 4.4 and all pressure values in Appendix B are actual test pressures.

# TABLE 4.4

## 16T WIND TUNNEL TEST CONDITIONS

| Run | Part Point No. | Mach No. | Flow Rate (lb/sec) OB Inlet | IB Inlet | Tube No. | Tube Pressure (psia) | Nominal Shock Overpressure (psi) | Intercept Angle (deg) | Yaw Ang. (deg) |
|-----|------|------|------|------|------|------|------|------|------|
| 1 | 501.01 | 0 | 0 | 0 | 2 | 69 | 2.7 | 79 | 0 |
| 2 | 615.03 | .552 | 235 | 235 | 3 | 186 | 4.7 | 91 | |
| 3 | 591.03 | .550 | 351 | 348 | 1 | 157 | 3.7 | 76 | |
| 4 | 589.03 | .551 | 351 | 348 | 2 | 115 | 3.8 | 97 | |
| 5 | 590.02 | .549 | 351 | 349 | 3 | 124 | 4.0 | 94 | |
| 6 | 602.02 | .700 | 302 | 300 | 1 | 72 | 2.6 | 86 | |
| 7 | 600.04 | .701 | 302 | 302 | 2 | 58 | 2.6 | 106 | |
| 8 | 573.04 | .700 | 304 | 302 | ↓ | 112 | 5.0 | 98 | |
| 9 | 601.03 | .701 | 302 | 300 | 3 | 69 | 3.0 | 104 | |
| 10 | 574.03 | .701 | 303 | 300 | ↓ | 132 | 4.4 | 97 | |
| 11 | 621.03 | .700 | 351 | 351 | 1 | 73 | 3.0 | 84 | |
| 12 | 519.02 | .699 | 348 | 344 | | 103 | 3.8 | 88 | |
| 13 | 527.02 | .700 | 349 | 344 | ↓ | 135 | 4.8 | 78 | |
| 14 | 626.02 | .701 | 352 | 352 | | 142 | 4.8 | 79 | |
| 15 | 512.03 | .700 | 351 | 344 | 2 | 59 | 2.8 | 103 | |
| 16 | 517.02 | .700 | 349 | 344 | | 85 | 3.8 | 103 | |
| 17 | 525.02 | .701 | 348 | 344 | ↓ | 113 | 5.0 | 100 | |
| 18 | 624.02 | .700 | 350 | 350 | | 139 | 5.2 | 99 | |
| 19 | 513.03 | .700 | 351 | 344 | 3 | 70 | 3.0 | 102 | |
| 20 | 518.02 | .700 | 348 | 343 | | 102 | 4.2 | 99 | |
| 21 | 526.02 | .700 | 349 | 344 | ↓ | 133 | 4.8 | 98 | |
| 22 | 625.02 | .701 | 350 | 350 | | 155 | 5.6 | 92 | |
| 23 | 570.03 | .699 | 351 | 350 | 1 | 144 | 3.6 | 87 | +5.0 |
| 24 | 568.04 | .700 | 350 | 349 | 2 | 132 | 5.8 | 103 | +5.0 |
| 25 | 569.03 | .703 | 350 | 349 | 3 | 143 | 4.2 | 105 | -5.0 |
| 26 | 559.02 | .850 | 300 | 298 | 1 | 61 | 2.2 | 89 | 0 |
| 27 | 598.03 | .848 | 299 | 299 | | 90 | 3.0 | 85 | |
| 28 | 584.03 | .847 | 294 | 293 | ↓ | 122 | 5.0 | 82 | |
| 29 | 608.04 | .850 | 299 | 299 | | 142 | 4.4 | 82 | |
| 30 | 557.04 | .850 | 300 | 298 | 2 | 55 | ~ | - | |
| 31 | 596.05 | .848 | 300 | 300 | | 73 | 3.8 | 108 | |
| 32 | 582.03 | .847 | 300 | 297 | | 94 | 4.4 | 105 | |
| 33 | 606.03 | .849 | 300 | 299 | ↓ | 120 | ~ | - | |
| 34 | 558.03 | .850 | 303 | 301 | 3 | 60 | >2 | - | |
| 35 | 597.03 | .848 | 300 | 300 | | 85 | 4.0 | 104 | |
| 36 | 583.03 | .847 | 298 | 296 | | 114 | 4.4 | 102 | |
| 37 | 607.03 | .850 | 299 | 298 | ↓ | 140 | 4.8 | 108 | |
| 38 | 546.02 | .847 | 348 | 347 | 1 | 121 | 3.6 | 84 | |
| 39 | 544.04 | .847 | 348 | 347 | 2 | 94 | 4.0 | 107 | |
| 40 | 619.02 | .850 | 352 | 351 | ↓ | 120 | 5.8 | 110 | |
| 41 | 545.03 | .847 | 348 | 347 | 3 | 113 | 4.4 | 105 | |
| 42 | 620.02 | .850 | 351 | 350 | ↓ | 139 | 5.6 | 100 | |
| 43 | 553.03 | .900 | 327 | 329 | 1 | 117 | 3.0 | 86 | |
| 44 | 550.02 | .899 | 349 | 354 | 2 | 86 | 4.0 | 107 | |
| 45 | 551.01 | .900 | 349 | 354 | 3 | 104 | 4.2 | 105 | |

FIGURE 4.5.

SAMPLE TEST RESULTS

FOR RUN 8 (PART 573), MACH 0.70,

FLOW RATE $\approx$ 303 LB/SEC, TUBE 2, $\Delta p$ = 5.0 PSI

Figure 4.5a. Blast and shock tube pressures.

Figure 4.5b.  Ramp pressures.

46

Figure 4.5c.  Cowl pressures.

47

Figure 4.5d. Blastward inlet engine face total pressures.

48

Figure 4.5e.    Leeward inlet engine face total pressures.

49

Figure 4.5f. External blast pressures and average engine face total pressures.

50

Figure 4.5g.　Left claw arm pressures.

51

Figure 4.5h.  Claw 3 parameters.

52

being designated by an asterisk after the label), where $p_t$ is the steady-state (pre-blast) tunnel total pressure and $p_o$ is the steady-state tunnel ambient static pressure.

The lowest part of Figure 4.5a shows the blast pressure inside the firing shock tube 14 inches from the muzzle end (STE). The pressure variation consists of a initial shock, followed by a slight rise and a nearly constant level for about 8 milliseconds, after which a slow decay follows.

The upper parts of Figure 4.5a give the (static) local blast pressures (PS) measured on the three claw probes, which provide an indication of the strength of the blast wave as it strikes the inlets. Looking first at PS2, which is near to the forward tip of the inlet, it may be noted that the pressure rises immediately on blast arrival to a large shock value, appears to increase slightly more over a period of about one millisecond, decays slowly until a time typically of about 3.3 milliseconds after initial blast arrival and then decays more rapidly. Similar variations are seen for the other two probes (PS1 and PS3), except that the signal for PS1, on the blastward side of the inlet, is complicated by the appearance of the reflection of the shock wave from the blastward blunt side of the inlet at about one millisecond after blast arrival.

It should be noted that for nuclear blast wave simulation purposes only the part of the signal from shock arrival to the rapid pressure change, starting at about 3.3 msec after blast arrival for PS2 in Figure 4.5a, is directly of interest. This rapid change can appear either as a rapid pressure drop usually at about 3.3 msec., as for PS2, or it may take the form of a rapid increase in pressure at about the same time followed by an abrupt pressure drop at a slightly later time, as for PS1 (Fig. 4.5a). At later times (after about the 3.3 msec) the flow pattern is more like a quasi-steady flow where the shock tube exit flow can be considered similar to a nozzle or jet flow. More specifically, from our two-dimensional REFLECT2 theoretical calculations (Appendix A), it appears that the rapid change in the blast pressure (at about 3.3 msec) corresponds generally to the arrival of the contact surface between the

53

"hot" tunnel gas and the "cold" gas jet from the shock tube. In most figures hereafter, the time of blast arrival at the transducer and a time 3.3 msec[*] later are indicated as a pair of vertical arrows in order to permit the reader to focus his attention more easily on the range of primary significance for nuclear blast simulations (between the arrows). While the test results for larger times may also be of some significance for blast simulations, this remains to be demonstrated.

Time histories of ramp and cowl pressures are presented in Figures 4.5b and 4.5c. (See Fig. 4.4 and Table 4.1 for transducer locations). It may be noted that there is considerable variation of waveform for the different locations for reasons to be discussed later. (It should be noted that transducer 1990 generally appears to be truncated, 1904 is generally unreliable and the calibration constant used for 2902 appears generally unreliable).

Typical time histories of blast-induced total pressure at the blastward engine face location are shown in Figure 4.5d. Roughly, the same variations are seen to be experienced for all locations and the general trends are similar to those of the input blast pressure (e.g., PS2 in Figure 4.5a).

Typical time histories of blast total pressure at the leeward engine face location are shown in Figure 4.5e. The leeward pressures are somewhat similar to those for the blastward side (Fig. 4.5d) but are clearly different from those for the blastward side in two significant respects. First the initial pressure rise is more rapid for the leeward side (essentially a single shock) whereas for the blastward side the rise time is relatively large (say about 0.3 msec), and generally appears to involve a sequence of several small shocks. Secondly, the blast pressure appears to decay more rapidly for the leeward side at late times.

---

[*] For a few firings the onset of this cold gas effect appeared to occur somewhat later, but for most cases where a definite onset could be estimated, it appeared to occur at between about 3.2 and 3.5 milliseconds after blast intercept.

Figure 4.5f presents times histories of the already presented three blast pressure measurements PS1, PS2 and PS3 as a fraction of pre-blast free stream total pressure ($p_{t_2}$) and also presents the average engine face total pressures R20 and R21, for the outboard (blastward) and inboard (leeward) inlets, respectively. As would be expected, these last two variables correspond closely to the corresponding variations for the individual transducers in Figures 4.5d and 4.5e, respectively.

Typical claw probe results are shown in Figure 4.5g and 4.5h. Directly measured parameters are the "static" pressure PSi and the left and right claw arm pressures, PCLi and PCRi, where i designates the probe number. Derived quantities are the resultant flow (sideslip) angle, ANG, the local Mach number, Mi, and the total pressure, PTi.

## 4.6 OBSERVATION ON BLAST INPUT CONDITIONS

Before proceeding to an analysis of the significance of the test results in Section 5 it is important to first indicate briefly the source and reliability of the blast input overpressure ($\Delta p$) and intercept angle ($\phi$) data presented in Table 4.4 and to indicate what differences in blast input and inlet response behavior may be attributed to the different locations of the three firing shock tubes.

### 4.6.1 Blast Input to the Inlets

The strength and orientation of the initial blast wave incident on the inlets and its subsequent time history variations must be known in order to evaluate the significance of any test firing. However, insomuch as the blast waves for these tests were not simple constant strength plane waves it is not a simple task to deduce the blast strength from the test data. More specifically, the orientation of the blast wave at the inlet depends on the tunnel flow conditions (Mach number), on the location of the shock tube, and on the shock tube firing conditions (tube driver pressure/tunnel pressure) and may be time dependent. The intensity of the blast depends on the radial distance and polar angle of the inlet from the shock tube axis and on the tunnel flow conditions and the shock tube firing conditions. Furthermore the strength of the blast wave striking the inlet and the blast measurement probes can be significantly modified by interferences between the blast wave, the

55

model wing and fuselage and the inlet, particularly at late times after arrival of the blast at the inlet.

### 4.6.1.1 Blast Strength

A first approximation for the blast input to the inlet is given by the static pressure transducers mounted on the claw probes as indicated in Figure 4.2. Typical time histories of the blast signal seen by these static transducers are shown in Figure 4.6 for firings from the three shock tubes.

Referring first to the firing from tube No. 1 (Fig. 4.6a), probe 1 (PS1) is struck first by the blast wave, probe 2 second, and probe 3 last. Probe 1 defines the blast wave as it is seen from a position slightly downstream of the inlet cowl lip and about 6 inches outboard of the cowl lip. This record should provide a reasonable estimate of the incident blast strength at the probe location for a time duration of about one millisecond, at the end of which time the blast wave has reflected from the blunt side of the inlet model and returned to the probe, thereby providing the second shock pressure increase observed on that probe at that time. In view of this reflection effect it is difficult to determine the late time history of the incident blast wave for tube 1 firings from probe 1 measurements. (The same argument applies to probe 3 measurements for firings from tube 3, as can be seen from Figure 4.6c).

The blast strength time history obtained from probe 2, located above and near the forward end of the inlet appears to generally give the best representation of the blast wave input that can be obtained without a detailed analysis of the claw probe data. There are no obvious strong interference reflections in the probe 2 data (at least up to about 3.3 milliseconds after blast arrival), although there certainly must be some interferences due to diffraction of the blast wave about the inlet structure.

The blast strength record obtained from probe 3 for firings from tube 1 or 2 (or from probe 1 for tube 3 firings) is considered only qualitatively representative of the true blast input to the inlet because the blast wave experiences substantial diffraction about the inlet structure before reaching this probe.

56

(a)   Shock tube 1 firing, Run 29 (Part 608)

Figure 4.6.   Typical blast pressure measurements for firings from three
shock tubes, Mach 0.85, flow rate ≈ 300 lb/sec.

(b)   Shock tube 2 firing, Run 31 (Part 596)

Figure 4.6.   Continued.

(c)   Shock tube 3 firing, Run 35 (Part 597)

Figure 4.6.   Concluded.

In view of the above observations and in view of frequent malfunctions of many of the claw probe elements, it was concluded that the best representations of the blast strength that is available from the test data at present are the probe 2 static data and these data were generally used to define the (nominal) blast strength data presented in the tables and figures of this report. A more accurate evaluation of the true incident blast strength and its time history derived from the claw probe data would, of course, be desirable, but insufficient time was available to develop this subject.

### 4.6.1.2 Blast Orientation

The blast incidence angle, $\phi$, at which the blast wave strikes the inlet is of considerable importance in determining blast effects on the inlet. The blast intercept angle is defined as the angle between a line normal to the blast front and the axis of the inlet, with $0^o$, $90^o$ and $180^o$ representing head-on, side-on and tail-on blast intercepts, respectively.

Initial estimates of blast intercept angles for the 16T tests were made from the shadowgram studies made in the 1T tunnel (Sec. 2.2). Attempts were made to take similar shadowgrams during the 16T tests, but these were generally unsuccessful. Instead, estimates of the blast intercept angles for the 16T test conditions were generally obtained by observing the differences in arrival times of the blast wave at claw probe 2 and at the transducers 1935, 1902 and 2902[*] located near the inlet mouth, under the assumption that the blast wave could be considered to be locally a plane shock wave, travelling with respect to the local pre-blast fluid at a shock speed corresponding to the shock overpressure in Table 4.4. The resulting intercept angle estimates are presented in Table 4.4. Generally these angles are in reasonable agreement with estimates from the 1T test shadowgrams, for cases of comparable test conditions.

---

[*] See Figure 4.4.

4.6.2  Shock Tube Location Effects on Blast Input and Inlet Response

The blast waves produced at the inlet by firings from different shock
tubes can produce somewhat different effects on the inlet response due to
factors other than obvious differences in intercept angles and overpressures.
It is the purpose of this section to clarify this question somewhat by
examination of some of the test data before proceeding to a more extensive
analysis of the data in Section 5.

Consider the effects of firing at the inlet from opposite sides of
the tunnel.  The blast waves fired at the model from shock tubes 1 and 2
encounter the inlet essentially without any initial interferences from
the model wing and fuselage body (see Fig. 3.1), whereas the blast wave
from shock tube 3, which must cross the wing before reaching the inlet,
may be substantially modified before striking the inlet.  Consequently,
some differences might be expected for the inlet response conditions to
firings from the different sides of the tunnel.  In order to indicate the
extent of these differences, Figure 4.7 presents a comparison of inlet
engine face total pressure time histories for firings from shock tubes
2 and 3 for roughly comparible overpressure and blast intercept conditions.
The left-hand side of this figure presents inlet pressure for a firing
from tube 2 and the right hand side presents the corresponding inlet
pressure for a firing from tube 3.  For example, transducer 1806 (in
the outboard inlet) for a tube 2 firing would be expected to have the
same type of response as the symmetrically located transducer 2831 (in
the inboard inlet) would have for a firing from tube 3.

It is evident from Figure 4.7a that the inlet response pressures
are about the same for firings from the two tubes, certainly for the
estimated duration of the blast event, say to about 3.3 msec after blast
arrival.  For much later times, there are appreciable differences, but
this is not of great importance for the present study.

For the leeward inlet, Figure 4.7b indicates the same general shape
of pressure histories for the two firings but does indicate an appreciably
more rapid decay of pressure for the firing from tube 3.  This more rapid

61

Tube 2 - Run 40 (Part 619)          Tube 3 - Run 42 (Part 620)

(a) Blastward inlet

Figure 4.7.   Comparison of engine face pressures for firings from
shock tubes 2 and 3.

62

Tube 2 - Run 40 (Part 619)                Tube 3 - Run 42 (Part 620)

(b) Leeward inlet

Figure 4.7.  Concluded.

63

decay can be attributed partly to wing-fuselage-inlet interference, which would be expected to have more effect on the leeward inlet than on the blastward inlet, and partly to the $10^{\circ}$ difference in intercept angles for the two firings.

Some differences are also observable between the blast inputs and inlet responses for firings from the two tubes located on the same side of the tunnel. For example, Figure 4.8 compares inlet ramp pressure time histories for firings at similar overpressure levels from the side-by-side shock tubes 1 and 2 (see Fig. 4.4 for transducer locations). It may be noted that the two sets of time histories are quite similar during the blast event (between the two arrows), especially for the first two milliseconds after blast arrival. Then the pressures tend to <u>decrease</u> for the rest of the blast event for the tube 2 firing and to <u>increase</u> for the tube 1 firing, and after the end of the blast event the two sets of time histories are considerably different. The greater pressures and fluctuations observed toward the end of and after the blast event for the tube 1 firing may be attributed partly to its much lower blast incidence angle, $84^{\circ}$ here compared to $110^{\circ}$ (see Sec. 7), and partly to the greater closeness of the jet from tube 1 to the inlet mouth.

64

Figure 4.8. Comparison of blastward inlet ramp pressure time histories for Mach 0.85 firings from two shock tubes.

65

# SECTION V

## ANALYSIS OF 16T TEST RESULTS

This section presents a general discussion and analysis of some of the principal effects relevant to and observed from the 16T blast test results. First a brief discussion is given of the basic characteristics of a blast wave interacting with an inlet-engine system (Sec. 5.1), followed by a more specific discussion of the transient shock wave pattern in an inlet after blast encounter (Sec. 5.2). Next are discussed distortion effects in the inlet (Sec. 5.3). Finally some observations are made on the ability of the inlet to endure long-duration blast effects (Sec. 5.4).

### 5.1 GENERAL PHENOMENA

The physical characteristics of a blast wave and its initial inter-actions with an inlet-engine system are discussed below. The initial discussion deals primarily with the case where the blast wave is considered as a simple plane shock wave of constant or very slowly decaying strength, resembling the blast wave from a nuclear weapon. Subsequently, attention is given to the differences in phenomena which are associated with the more complex blast wave produced by the shock tubes as used in the present studies.

As a blast wave travels toward an aircraft moving in space it produces changes in the ambient atmosphere behind its front which are imposed on the aircraft as it is enveloped by the blast field. The blast wave is defined essentially by two characteristics, the overpressure, $\Delta p$, and the intercept angle, $\phi$, between a normal to the blast front and the direction of aircraft motion. With reference to the aircraft, the flow field behind the blast front will have a greater ambient pressure, $p_o + \Delta p$, a greater total pressure, $p_t + \Delta p_t$, and a blast-induced increased side-slip angle, $\psi = \psi_o + \Delta \psi$. Figures 5.1 and 5.2 illustrate the magnitude of these blast-induced side-slip angle and total pressure changes for several Mach numbers. For example, it is seen from

66

(a)  MACH 0.55

Figure 5.1.  Variation of blast-induced side-slip angle with intercept angle and overpressure.

67

(b) MACH 0.70

Figure 5.1. Continued

68

(c) MACH 0.85

Figure 5.1. Continued

(d) MACH 0.90

Figure 5.1. Concluded.

70

(a)  MACH 0.55

Figure 5.2.  Variation of blast-induced total pressure with
intercept angle and overpressure.

71

(b) MACH 0.70

Figure 5.2. Continued

72

(c)  MACH 0.85

Figure 5.2  Continued

(d)  MACH 0.90

Figure 5.2.  Concluded

74

Figure 5.1 that the greatest blast-induced yaw angles are produced by intercept angles somewhat over $90^{\circ}$ (i.e., slightly from the rear). Blast-induced total pressure changes in Figure 5.2 are seen to be largest for zero intercept angle and to decrease subsequentially to relatively small values for tail-on ($\phi=180^{\circ}$) intercepts.

As a blast wave envelopes an aircraft these blast properties may be substantially modified by diffraction and reflections from various parts of the structure before and after the wave encounters the engine inlet.

As the wave proceeds into an engine inlet it may experience a sequence of reflections from the walls of the inlet (as discussed in Sec. 5.2) and from engine components, and may penetrate in part completely through the engine system.

Eventually, if the blast wave is of sufficient duration, these blast reflection effects will be resolved and the inlet-engine system will come to a quasi-steady equilibrium condition consistent with the blast-induced overpressure, total pressure and side-slip angle, characterized by an engine mass flow rate which can be different from that for the pre-blast condition.

In discussing the effects of a blast wave on inlet-engine performances it is convenient to think of the phenomena in terms of the following somewhat overlapping three stages of the blast encounter.

The first or initial stage consist of the time during which the blast wave moves down the inlet into the engine, reflects in part from the engine structure or fan of a turbofan engine and subsequently moves upstream and out the mouth of the inlet. In the case of the present 0.1-scale model the time required for these events up to the time when the reflected shock wave has moved upstream of the simulated engine face section is on the order of 2 milliseconds. (Time zero is defined here as the time when the blast wave first strikes the cowl lip of the blastward inlet.)

The second stage of the blast flow encounter is associated with the inception and convection of boundary-layer disturbances down the inlet. In particular, boundary-layer separation and vortex formations may be

75

produced at the cowl lip by large blast-induced side-slip angles and will be convected downstream at speeds comparable to or lower than the particle velocity in the inlet, which is generally much smaller than the rate at which a blast wave moves down the inlet. In the case of the tested inlet, it would take on the order of 3 milliseconds (after cowl lip blast encounter) for such particle velocity effects to reach the engine face. Other boundary layer effects which might be expected in this same time period would be boundary layer instabilities excited by the reverse flow reflected upstream from the engine throat. For the present inlet, such effects would not be expected to begin at the engine face before times of about 2 milliseconds after blast intercept.

The third stage of the blast flow consists of the late time stage when all significant internal shock wave systems have been dissipated or reflected from the inlet-engine system and boundary layer effects have reached a quasi-steady equilibrium condition. This stage was not reached in the present tests because of the limited duration of the blast waves used.

5.1.1 Differences Between Shock Tube and Nuclear Blast Flows

The initial flow from the shock tubes used in the present tests generally resembles the essential features of a nuclear blast wave at least for part of the blast-type flow period described (in Section 4.5) of about 3.3 milliseconds. However there are some noteworthy features, which should be borne in mind, where the shock tube flow differs from that for a nuclear blast. First the strength of the shock tube blast wave remains relatively constant for only one or two milliseconds, after which its strength generally tends to decrease toward zero at 4 to 6 seconds after initial shock arrival. Also, in the late decay stage, "cold" air blown out of the shock tube produces a high velocity jet with a complex spatial variation of fluid properties which bears little resemblance to a nuclear blast field. As a general rule of thumb for the present tests, it appears that this "cold" jet does not strongly influence the test results for times after blast arrival less than about 3.3 milliseconds (see Sec. 4.5).

76

A sketch illustrating the above-discussed sequence of events in the blastward inlet is presented as Figure 5.3 in the form of a time distance plot for an inlet mass flow rate of 350 lb/sec. The time origin is the time when the blast wave first arrives at the cowl lip. The initial blast wave moves down the inlet to the simulated engine throat vane system and is reflected back upsteam as indicated by the "shock" curve. The "particle velocity" curve indicates the convective speed of material in the inlet; "vortex" motions are indicated here as travelling at speeds between 1/2 and 1 times the particle velocity and are indicated to reach the engine face at times on the order of 3-6 milliseconds, depending on the vortex speed. The cold gas motion is indicated by the two upper curves, starting at time 3.3 msec. This cold gas effect might be expected to travel down the inlet at some speed between the particle velocity and the sound(+ particle) velocity, depending on how close the inlet mouth is to the jet from the shock tube. It is important to note here that large shock-type cold gas effects (see lower cold gas curve) can arrive at the engine face before vortex effects arrive, hence making it difficult to unambiguously evaluate vortex effects at the engine face by simple inspection of test records.

## 5.2 SHOCK PATTERN IN THE INLETS

As a guide to the discussion in later sections of blast-induced distortion and its effects on engine performance, this section briefly discusses some details of the character of the blast-induced shock flow pattern in the inlet.

Figure 5.4 presents a sketch of the tested inlet configuration and shows the shock wave pattern inside the inlet for a time when the blast shock has penetrated down the blastward (outboard) inlet to slightly beyond the engine face location. In this figure, the blast is assumed to have struck the inlet about perpendicular to the inlet axis ($\phi=90^{o}$) from the outboard side of the inlet. After encountering the lip of the outboard cowl, the blast shock wave begins to diffract about the cowl lip and to penetrate into the inlet at a downstream speed about equal

Figure 5.3. Inlet time-distance relationships.

78

Figure 5.4. Typical shock wave pattern in the inlets.

to the sum of the (pre-blast) flow velocity in the inlet plus the speed of sound in the inlet. At the same time the part of the shock wave upstream of the cowl lip proceeds to the outboard ramp surface, experiences essentially normal reflection there, with about doubling of its intensity, and then tends to bounce back and forth between the ramp and cowl surfaces while being at the same time convected downstream into the inlet. The resulting overall blast front pattern at any time can be constructed graphically by assuming the shocks to travel at essentially the speed of sound relative to the local ambient inlet velocity and the accuracy of the construction can be checked or improved by adjusting these constructions slightly to conform to the experimentally observed times of blast arrivals at the various transducer stations along the ramp and cowl indicated in Figure 5.4. (Generally the first two or three shock arrival times can be clearly distinguished in the transducer time histories.) It should be noted that the shock pattern in Figure 5.4 is rather simplified in that it assumes regular reflection of the waves at the cowl and ramp surfaces and it does not consider the interference effects of the engine hub structure (Figure 4.1). Actually Mach stems will tend to form for some reflected waves and additional reflections will occur from the hub; however, Figure 5.4 does illustrate the overall pattern well enough for the present discussions.

The shock pattern on the leeward side of the inlet is much simpler. Here, the shock wave simply diffracts about the tip of the ramp and tends to enter the leeward inlet essentially as a one-dimensional disturbance having a single shock with its front essentially normal to the inlet side walls.

The shock patterns shown in Figure 5.4 were based partly on test data for Run 39 (Part 544) conditions, Mach 0.85 at 350 lb/sec, but would be expected to apply rather well to any of the other test Mach numbers as well.

Now, to indicate the significance of the type of shock pattern seen in Figure 5.4, consider first the blastward inlet. It is seen that the shock waves are generally not at all parallel to the inlet walls, except

for the initial blast front. Hence, there is generally an appreciable time-varying spatial variation of blast pressure across any section of the inlet, which lasts from the time of first blast arrival until that time when all of the incident blast front and its reflections will have been either convected downstream through the engine or reflected from the engine throat back upstream and out the mouth of the inlet. This spatial pressure variation across any section of the inlet will, of course, produce flow distortion in the section, the intensity of which will be related to the intensity of the shock or shocks passing through or near to that section at the time in question.

Another consequence of the complex shock pattern in the blastward inlet is its effect on the rate at which the shock pressure builds up. Essentially, for the blastward inlet, the pressure buildup consists of a sequence of separated shocks adding to each other, so that the resultant effect is a relatively slow staircase type buildup of pressure, taking on the order of 0.3 millisecond for typical cases. On the leeward inlet, however, where there is essentially a single shock front, the pressure buildup is essentially instantaneous.

5.3 ANALYSIS OF INLET DISTORTION

A primary objective of the test program was to obtain time histories of the inlet distortion parameters resulting during blast wave inlet interactions. In this study, time histories of the following inlet distortion parameters were calculated from the test data for both inlets for all runs and were plotted as illustrated in Figure 5.5 for Run 8 (Part 573): $IDC_i$, $IDR_i$, IDC12, IDC45, IDR, IDC, IDL, IDA and IDT, where i designates the ith instrumented engine face ring (i = 1 to 5). These particular distortion parameters, defined in Table 5.1, were selected because they are standard for the analysis of the B-1 inlet and engine system. The discussion of distortion in this report is, however, restricted to the parameters IDC, IDR and IDL, and primarily to IDL. IDC is the total circumferential distortion index, IDR is the total radial distortion index and IDL is the fan stall margin ratio. IDL is an overall measure of the inlet distortion, which depends on IDC,

81

Figure 5.5. Distortion time histories for Run 8 (Part 573), Mach 0.70, $\Delta p$ = 5.0 psi, $\phi$ = 98$^{o}$, flow rate $\approx$ 303 lb/sec, tube 2.

Figure 5.5. Continued.

OUTBOARD INLET

Figure 5.5. Continued.

84

Figure 5.5.  Continued.

INBOARD INLET

Figure 5.5. Continued.

86

Figure 5.5.  Continued.

87

INBOARD INLET



Figure 5.5. Concluded.

## TABLE 5.1

### EQUATIONS FOR CALCULATING DISTORTION
### PARAMETERS IDC, IDR, IDL, IDA AND IDT

**Circumferential Distortion on Individual Rings**

$$IDC_i = (p_{t2_{avci}} - p_{t2_{min_i}})/\overline{p}_{t2}$$

where

$$i = 1 \text{ to } 5 \text{ rings}$$

**Hub Distortion**

$$IDC_{12} = (IDC_1 + IDC_2)/2$$

**Tip Distortion**

$$IDC_{45} = (IDC_4 + IDC_5)/2$$

**Total Circumferential Distortion**

$$IDC = \text{Largest of } IDC_{12} \text{ or } IDC_{45}$$

**Radial Distortion on Individual Rings**

$$IDR_i = \text{Largest of } (1.0 - \frac{p_{t2_{ave_i}}}{\overline{p}_{t2}} ,0)$$

**Total Radial Distortion**

$$IDR = \text{Largest of } IDR_1, \ IDR_2, \ IDR_4, \text{ or } IDR_5$$

**Fan Stall Margin Ratio**

$$IDL = b(KCIRC)IDC + (KRAD)IDR$$

where

$$b = \frac{IDR/IDC}{A+B(IDR/IDC)} + C$$

89

TABLE 5.1. CONCLUDED

| MACH NUMBER | TUNNEL TOTAL TEMPERATURE ($^{o}$R) | KCIR | KRAD | SUPER POSITION FACTOR b | | |
|---|---|---|---|---|---|---|
| | | | | A | B | C |
| $0 \leq .15$ | All | 7.93 | 12.41 | -0.536 | -0.591 | 1. |
| $.15 \leq .35$ | All | 7.69 | 11.76 | -0.520 | -0.643 | 1. |
| $.35 \leq .65$ | All | 7.69 | 12.28 | -0.520 | -0.644 | 1. |
| $.65 \leq .75$ | All | 7.69 | 12.42 | -0.520 | -0.644 | 1. |
| $.75 \leq 1.5$ | Less Than/Equal To 560. | 7.69 | 12.83 | -0.520 | -0.644 | 1. |
| $.75 \leq 1.5$ | Greater Than 560. | 7.93 | 12.99 | -0.553 | -0.532 | 1. |
| $1.5 \leq 2.3$ | All | 7.69 | 11.75 | -0.560 | -0.920 | 1. |

Average Distortion:

$$IDA = (\bar{p}_{t2} - p_{t_{min}})\bar{p}_{t2}$$

Total Distortion:

$$IDT = (p_{t_{max}} - p_{t_{min}})/\bar{p}_{t2}$$

IDR and the speed altitude regime.  An indication of the normally allowable range of these distortion parameters for subsonic flight of the B-1 aircraft is given in Figure 5.6 (from Ref. 5.1).  Generally, the inlet and engine can be considered to perform satisfactorily at values of IDL up to unity, which corresponds to values of IDC and IDR to the left of and below the solid line curve in Figure 5.6.  For larger values of IDC, IDR or IDL the engine can stall, but will not necessarily do so.

5.3.1  Data Presentation

Typical time histories of distortion parameters for various over-pressure levels are presented in Figures 5.7 through 5.17.  Figure 5.7 presents IDL for the lower tested mass flow rate ($\approx$ 300 lb/sec) at Mach 0.70 for both inlets and Figures 5.8 and 5.9 present similar data for the higher tested mass flow rate ($\approx$350 lb/sec) for the blastward and leeward inlets, respectively.  Figure 5.10 presents IDC, IDR and IDL for the lower mass flow rate ($\approx$300 lb/sec) at Mach 0.85 for the blastward inlet and Figure 5.11 presents IDL for the leeward inlet; Figure 5.12 presents IDC, IDR and IDL for the higher mass flow rate ($\approx$350 lb/sec). Mach number effects on IDC, IDR and IDL are indicated in Figures 5.13 and 5.14 for blastward and leeward inlets for firings from Tube 2 and, for IDL only, in Figures 5.15 and 5.16 for firings from Tube 1.  IDL measurements made during the three yawed firings are presented in Figure 5.17.

5.3.2  Effects at Low Mass Flow Rates

Considering now the distortion effects at the lower tested mass flow rate of about 300 lb/sec (full scale), it can be seen from Figure 5.7 for Mach 0.70 and from Figure 5.10c and 5.11 for Mach 0.85 that the stall margin, IDL, is usually well below the normally safe limit of unity, usually being near to or below 0.5, for the time range where the test data are definitely representative of a blast wave (between the two arrows in the figures).  Corresponding values of IDC and IDR, shown in Figure 5.10 for Mach 0.85 are similarly rather low, being generally below 0.10 for IDC and below 0.05 for IDR.

Figure 5.6. Range of distortion indices for B-1 inlet at subsonic cruise.

Figure 5.7.    Distortion time histories for two overpressures at Mach 0.70,
flow rate ≈ 300 lb/sec, tube 2.

OUTBOARD INLET



Figure 5.8. Distortion time histories for four overpressures at Mach 0.70 for the blastward inlet, flow rate ≈ 350 lb/sec, tube 2.

Figure 5.8.  Continued.

95

OUTBOARD INLET



Figure 5.8. Concluded.

96

INBOARD INLET



Figure 5.9.   Distortion time histories for three overpressures at Mach 0.70 for the leeward inlet, flow rate ≈ 350 lb/sec, tube 2.

97

Figure 5.9. Continued.

INBOARD INLET

Figure 5.9.   Concluded.

99

OUTBOARD INLET



Figure 5.10.   Distortion time histories for four overpressures at Mach 0.85
for the blastward inlet, flow rate ≈ 300 lb/sec, tube 1.

100

OUTBOARD INLET



Figure 5.10. Continued.

OUTBOARD INLET

Figure 5.10. Concluded.

102

Figure 5.11. Distortion time histories for four overpressures at Mach 0.85 for the leeward inlet, flow rate ≈300 lb/sec, tube 1.

Figure 5.12. Distortion time histories for two overpressures at Mach 0.85, flow rate ≈ 350 lb/sec, tube 2.

104

Figure 5.12. Continued.

105

Figure 5.12. Concluded.

Figure 5.13. Distortion time histories for four Mach numbers for the blastward inlet, flow rate ≈ 350 lb/sec, tube 2.

Figure 5.13. Continued.

108

OUTBOARD INLET



Figure 5.13. Concluded.

109

Figure 5.14. Distortion time histories for four Mach numbers for the leeward inlet, flow rate ≈ 350 lb/sec, tube 2.

110

INBOARD INLET

Figure 5.14. Continued.

111

INBOARD INLET



Figure 5.14. Concluded.

112

## OUTBOARD INLET



Figure 5.15. Distortion time histories for four Mach numbers for the blastward inlet, flow rate ≈ 350 lb/sec, tube 1.

113

INBOARD INLET

Figure 5.16.   Distortion time histories for four Mach numbers for the leeward inlet, flow rate ≈ 350 lb/sec, tube 1.

114

(a) Blastward Inlet

Figure 5.17. Distortion time histories for three yawed runs at Mach 0.70, yaw = 5°, flow rate≈350 lb/sec.

(b) Leeward Inlet

Figure 5.17. Concluded.

116

In a few cases, values of IDL, IDC and IDR in excess of normally allowable limits were observed. For example, for Run 28 (Part 584) in Figure 5.10, large distortion values were experienced in the blastward inlet shortly after blast intercept, but the duration of this large distortion appears to have been less than 0.1 msec (1 msec full-scale). It is uncertain whether the duration of this distortion pulse was long enough to imply a significant adverse effect on engine performance. As a matter of possible interest, Figure 5.18 presents engine-face total-pressure contours for this run, indicating the total-pressure variation across the engine face at a time close to the time of peak distortion (indicated by the arrow in the inset IDL plot). The corresponding instantaneous values of IDL, IDC and IDR are 1.05, 0.103 and 0.061, respectively. The numerical values in this figure represent the difference between the face-average total-pressure and the local total-pressure, expressed as a fraction of face-average total-pressure. Test data points (or interpolations thereof for a few bad data points) are represented as large numbers and contour levels by small handwritten numbers. It may be noted that the lowest total-pressure drop is about 17 percent below the face-average total-pressure.

### 5.3.3 Effects at High Mass Flow Rates

The distortion effects at the higher tested mass flow rate of 350 lb/sec are generally at least somewhat larger than for the lower mass flow rate. However, for the lower overpressures, up to about 4 psi, the stall margin, IDL, is generally observed to be well below the limit of unity in the blast range (between the two arrows), being generally near to or below 0.9 (see Figures 5.8 and 5.9 for Mach 0.70, Figure 5.12 for Mach 0.85 and Figures 5.13 and 5.14 for a range of Mach numbers). For higher overpressures than 4 psi, IDL sometimes appears to exceed unity in the blast range (e.g., for the blastward inlet at $\Delta p = 5.2$ psi at Mach 0.70 in Figure 5.8 and for the leeward inlet for $\Delta p = 5.8$ psi at Mach 0.85 in Figure 5.12), but only for a small fraction of a millisecond at most. Outside the blast range (to the right of the second arrows in the figures) IDL values appreciably larger than unity are observed

117

Figure 5.18. Outboard inlet total pressure contours for a large blast-induced distortion condition.

118

for some firings (e.g., for the blastward inlet at $\Delta p$ = 5.2 psi at Mach 0.7 in Figure 5.8 and for blastward and leeward inlets at $\Delta p$ = 3.8 psi at Mach 0.55 in Figure 5.13), but further study would be required to verify whether these late time data are relevant to the blast-inlet problem. Possible sources of late-time distortion are discussed in Section 9.

## 5.3.4 Mach Number Effects

No definite significant effects of Mach number on the distortion indices IDL, IDC and IDR were observed in the blast range (e.g., see Figures 5.13 and 5.14). This lack of observed effect is attributed primarily to the choking action of the vane system downstream of the simulated engine face, which tends to maintain the internal inlet flow at any location in the inlet at a constant Mach number condition, regardless of the state of the external flow conditions. Further more definite evidence indicating this apparent lack of Mach number effects on inlet pressures is given in Figure 5.19, which compares inlet ramp pressures for transducer 1980 (located about half-way down the inlet, see Figure 5.4) for four Mach number conditions. It may be noted that most fine details of the pressure histories in Figure 5.19 are almost identical for the different Mach numbers, especially for Mach 0.55 and 0.85.

## 5.3.5 Effects of Yaw Angle

No definite effects of yaw angle on distortion are readily evident from the results of the three yawed test firings (Figure 5.17). Appreciable increases in IDL occurred for both inlets in each firing, but the increases did not generally appear much greater than for similar unyawed firings (see Figs. 5.8 and 5.9). However, it should be noted that a significantly high level of distortion appears to have developed in the leeward inlet toward the end of the nominal blast event (at second arrow) of Run 25 (Fig. 5.17b).

## 5.3.6 Long Duration Distortion Effects

If the rate of decay of a blast wave is extremely small, as for a large nuclear burst, then the struck inlet-engine system will tend at late times to come to a quasi-steady equilibrium condition where the

119

Figure 5.19. Comparison of ramp pressure time histories for four Mach numbers, tube 2, flow rate ≈ 350 lb/sec.

120

effect of the blast wave will be essentially the same as would be produced by steady yawed flight at the side-slip angle and total pressure caused by the blast (as given by Figures 5.1 and 5.2. In regard to this point, it may be noted that our test results for steady yawed conditions generally indicate 10% or less increase, or decrease, in the distortion parameter IDL as the sideslip angle varies from the zero angle condition to angles anywhere in the range from $-10^{\circ}$ to $+10^{\circ}$. Hence, it might be expected that late-time blast distortions would be small for blast overpressures producing blast-induced sideslip angles up to at least $10^{\circ}$, as given by Figure 5.1 in Section 5. For example, for Mach 0.85 flight, Figure 5.1 indicates that blast overpressures up to about 3.3 psi would not produce sideslip angles over $10^{\circ}$ and, hence, would not be expected to produce large late-time distortion effects.

The value of the above observations is, of course, of limited value since we cannot at this time specify what we mean by "late time" in a very definite manner. However, judging from BID code calculations for times up to about 6 milliseconds, presented later in Section 7 (Figure 7.2), it appears that quasi-steady equilibrium would not be reached for the test model until times considerably greater than 6 milliseconds (or 60 milliseconds for a full scale B-1 inlet).

5.3.7 Concluding Remarks on Distortion Effects

In concluding this discussion of distortion effects, it should be noted that while generally very few large distortion values were obtained during the early-time definitely blast-type flow periods of the present tests, the distortion criteria used above (IDC, IDR and IDL) are not necessarily completely reliable indices of whether an engine would stall under transient blast conditions. Other distortion criteria should also be considered (e.g., Ref. 5.2 and 5.3) and attention shoudl also be directed to the actual contours of pressure distortion which are obtained under blast intercept conditions, such as is illustrated in Figure 5.18 for one run at a time shortly after blast intercept (see arrow in inset IDL plot) when appreciable distortion was experienced in the outboard inlet. Also attention should be directed to the durations of any large observed distortion levels, comparing them with duration results

121

from other tests (e.g., Ref. 5.4).  Furthermore, attention should be directed also to effects of blast-induced longitudinal pressure variations (Sec. 9) and blast-fan interactions (Sec. 8) to assess more completely the possible stall inducing potential of blast waves.

These same types of questions should also be considered with respect to the large distortion values sometimes observed at times after the fairly definite blast type flow duration time of 3.3 milliseconds.

Most of the above topics are not explored in the present report because the reduced test data were not made available in a suitable form in time to permit such studies to be performed.

# SECTION VI
## COMPARISON OF THEORY AND EXPERIMENT

Concurrent with the performance of this experimental investigation, Kaman AviDyne developed a theoretical two-dimensional computer code, designated BID (blast-induced-distortion), for predicting the transient flow field produced in a inlet by a blast wave striking the inlet at an arbitrary angle of incidence (Reference 6.1). Calculations of inlet pressure time histories were made with this code for four conditions similar to those of the 16T experimental tests and the results of these calculations are compared with the test results in this section.

The specific conditions for which BID calculations were made are: constant shock overpressure of 5 psi at one atmosphere ambient pressure, inlet mass flow rate (full-scale) 350 lb/sec, tunnel Mach number of 0.70 for a blast intercept angle of $\phi=90^{\circ}$ and tunnel Mach number of 0.85 for intercept angles of $\phi=90^{\circ}$, $105^{\circ}$ and $135^{\circ}$. Calculated BID pressure time histories for various locations in the inlets are presented in Figures 6.1 to 6.5 together with experimental data for those test runs corresponding most closely to the conditions of the theoretical calculations.

The reader is reminded here that in looking at the experimental data in Figures 6.1 to 6.3, attention should be directed on times between the two arrows above each curve; the data at later times are not considered necessarily representative of a blast type flow (See Sec. 4). Also it should be recognized that the theoretical calculations shown in Figures 6.1 to 6.4 are for a constant-strength (step) blast wave (5 psi overpressure), whereas the test data correspond to a time-varying blast wave characterized by an initial shock value (shown below each figure), and possible subsequent increases in pressure, followed by a tendency to decrease to zero in 4-6 milliseconds after initial shock arrival.

The reader is also advised to make comparisons of theory and experiment primarily on the basis of wave shape rather than on amplitude comparisons, since the calibration factors used for some of the shown

123

ramp and cowl data are either nominal or questionable values and a few appear to be significantly in error[*].

Considering first the Mach 0.7 condition, it can be seen from the presentation of ramp and cowl time histories in Figure 6.1 that there is a great difference in the pressure waveforms for different locations in the inlet (see Figure 5.4 to identify the locations indicated in the figure), and that in almost every case the theoretical results follow well most of the details observed in the experimental data. For example, for location 1970, the BID calculation clearly delineates the first three shock arrivals and, at late time, delineates a large pressure increase resulting from reflection of the blast from the simulated engine throat of the inlet model.

A similar comparison is made for ramp pressures for Mach 0.85 in Figures 6.2 and 6.3 and for cowl pressures in Figure 6.4. Again the theoretical and experimental wave shapes are generally in good agreement. A few noticible differences do appear to exist, such as the more rapid late time decays (say near the second arrow) of the experimental pressures for locations 1950 and 1970 in Figure 6.3 and for the cowl locations in Figure 6.4. These differences may be attributed in part to differences between the constant strength blast assumed for the calculations and the actual variable strength blast of the test.

A final comparison is made in Figure 6.5 between calculated and experimental total pressures at the simulated engine face location for a location near the ramp in the blastward (outboard) inlet. The two transducers shown are located vertically above one another in the inlet (see Figure 4.3) so that the theoretical (two-dimensional) BID prediction is the same for both transducers. Differences between the two experimental results are hence indicative of the importance of three-dimensional effects not covered by the theory in its present form.

---

[*] These calibration factor problems arose as a result of pre-test mechanical and electrical malfunctions of the transducers which could not be resolved in the very limited time available for the 16T tunnel tests. Preliminary examinations of the test data indicated that more reliable estimates for some of these factors can be obtained by considering some redundant features of the data, but this has not yet been done.

Figure 6.1. Comparison of theoretical and experimental time histories of ramp and cowl pressures at Mach 0.70, flow rate ≈ 350 lb/sec.

125

Figure 6.2. Comparison of theoretical and experimental time histories of ramp pressures in the blastward inlet at Mach 0.85, tube 1 data, flow rate ≈ 350 lb/sec.

Figure 6.3. Comparison of theoretical and experimental time histories of ramp pressures in the blastward inlet at Mach 0.85, tube 2 data, flow rate $\approx$ 350 lb/sec.

Figure 6.4. Comparison of theoretical and experimental time histories of cowl pressures at Mach 0.85, flow rate ≈ 350 lb/sec.

Figure 6.5. Comparison of theoretical and experimental total pressure time histories at the engine face for the blastward inlet.

In order to permit a reasonable quantitative comparison of theory and experiment in Figure 6.5, it was necessary to take into account the fact that the pre-blast (steady-state) pressures were slightly different and the input blast overpressures and orientations were significantly different for the two cases. This difference was taken into account by multiplying the theoretical BID code curve by the ratio of the experimental and theoretical values of the shock jump in input total pressure and by vertically shifting the theoretical curve so that the pre-blast steady-state values were the same for theory and experiment.

The theoretical and experimental total pressures in Figure 6.5 are seen to be in reasonably good agreement in the following respects. Both indicate a reasonably similar (slow) rate of rise of the pressure to a peak value in about 0.3-0.4 millisecond and both have about the same mean peak level of pressure for about 2 milliseconds. Also the third peak in the theoretical curve (at about 1 msec after blast arrival), which represents the return of the blast wave reflected from the simulated engine throat, is in agreement with the corresponding experimental time. There are, of course, some noticable differences, in that the experimental peak values are appreciably greater than the theoretical values and, at later times, may be smaller. These differences may be attributed in part to the finite resolution of the numerical code, some attenuation of the shock for the code due to an effective "artificial viscosity", with a fixed-mesh cell system, to three-dimensional effects (as evidenced by differences between the two experimental traces) not covered by the theory, and to the use in the theoretical calculation of the approximation that the blast wave is of constant strength.

In summary, the above limited comparisons indicate that the major features of the transient pressures observed in the inlet tests are well represented by the BID code results. However, a more extensive comparative study of the 16T results would be desirable to more definitively establish the limitations of the code predictions. Such a correlation would require incorporation into the BID code of the actual time history of the blast wave incident on the inlet (instead of the constant over-

130

pressure value used here).  This, in turn, requires evaluation of the input blast time history from the test data, which is a non-trivial task because of possible significant fuselage inlet and claw probe interference effects.

## SECTION VII
## SHOCK ORIENTATION EFFECTS

This section considers briefly some gross effects of the blast intercept angle, $\phi$, on engine face total pressures for the test model as calculated from the BID code for Mach 0.85 flight conditions.

It was noted in Section 5 that for a blast wave of constant over-pressure, the increase in blast total pressure in free space (before intercepting the inlet) is largest for zero intercept angle and decreases with increasing intercept angle, according to the curves of Figure 5.2. As might be expected, the same type of variation is obtained for the total pressure at the engine face, as is shown in Figure 7.1. This figure presents total-pressure time histories near the center of the blastward and leeward inlets as calculated with the BID code for a constant-strength 5-psi overpressure blast wave striking the inlets at intercept angles of $90^{\circ}$, $105^{\circ}$ and $135^{\circ}$.

It may be noted in Figure 7.1 that, in addition to a decrease of face total pressure with increasing intercept angle, there is a noticeable reduction in the complexity of the pressure signature for the blastward inlet as the intercept angle increases from $90^{\circ}$ to $135^{\circ}$. For the nearly side-on intercept angles of $90^{\circ}$ and $105^{\circ}$ there are two distinct peaks, the first representing the initial blast wave striking the face and the second representing the reflected shock from the choked section of the simulated engine. For the larger $135^{\circ}$ intercept angle, where the blast wave overtakes the inlet from the rear, the distinction between the incident and reflected blast wave is hardly detectable.

It can also be observed in Figure 7.1 that the rate of increase of face pressure to its maximum value decreases considerably as the intercept angle increases from $90^{\circ}$ to $135^{\circ}$, both for the blastward and leeward inlets.

In order to better relate the face pressures to the incident blast conditions, the total-pressure curves from Figure 7.1 are also presented in Figure 7.2 in the form of the ratio of the change in total pressure (due to the blast) to the change in total pressure across the blast front before it encounters the inlet (from Figure 5.2). It is evident from

132

Figure 7.1. Comparison of engine face total pressure time histories for three blast intercept angles.

(a) Blastward inlet.

(b) Leeward inlet.

Figure 7.1. Concluded.

134

(a)  Blastward inlet.

Figure 7.2.  Comparison of engine face total pressure ratio time histories for three blast intercept angles.

135

(b) Leeward inlet.

Figure 7.2. Concluded.

136

Figure 7.2 that, for the blastward inlet, the average total-pressure change at the simulated engine face has about the same ratio to the incident total-pressure change for all three intercept angles, the ratio being about 1.17 for the time range shown. For the leeward inlet, this ratio is smaller and varies somewhat with the intercept angle.

The significance of the above observations with respect to engine performance has not yet been explored in detail. However, both the decreasing intensity and the decreasing rate of change of total pressure observed for increasing intercept angle in Figure 7.1 may imply a decrease in inlet distortion with increasing intercept angle, at least in the $90^{\circ}$ to $135^{\circ}$ range.

## SECTION VIII
## INTERACTION OF BLAST SHOCK WITH THE
## ENGINE FAN

The principal question regarding blast wave interaction with the engine inlet, of course, is what effect this interaction would have upon the operation of the engine downstream.

The effect would depend upon the nature of the transient events that take place when the blast shock and blast-induced flow reach the engine. At present there is no means for analyzing this sequence of events nor are there test data available for its assessment. As an admittedly limited first step in understanding the problem, the interaction at the fan stage of a turbofan engine will be examined here on a quasi-steady basis.

### 8.1  QUASI-STEADY BLAST SHOCK INTERACTION WITH A FAN

The quasi-steady interaction of a blast shock leaving the inlet and entering a fan will be analyzed by making the assumption that the interaction reaches an equilibrium rapidly enough that a new steady-state fan point is reached essentially immediately after shock arrival. Of course, the transient interactions of the blast shock with the rotor and stator blades are expected to be important, but, until the means are available for analysis of these interactions, the analysis of a quasi-steady interaction will have to suffice for providing an assessment of some of the features of shock interaction with a fan.

The time sequence of events associated with the interaction of a shock wave with a fan is shown in Figure 8.1. Here the flow going into and out of the fan is treated on a one-dimensional basis. Region 2 contains the preblast flow entering the fan and region 3 contains the preblast flow leaving it. The fan is located at the origin of the coordinates.

The blast shock at the fan is assumed for this analysis to be a step-blast, i.e. to have uniform properties in region 2' behind the

138

Figure 8.1. Shock interaction with fan.

139

shock. The shock wave is partially reflected upstream producing the flow in regions 2" ahead of the fan. It also is transmitted through the fan producing the flow in regions 3' and 3" downstream of the fan. The air in region 3' has first passed through the fan and is then shock compressed by the transmitted shock. The air in region 3" has been twice shock compressed before passing through the fan, first by the incident shock (separating zones 2 and 2') and then by the reflected shock (separating zones 2' and 2"). The air in regions 3' and 3" is separated by a contact surface; the pressures and particle velocities are equal in the two regions but the densities differ.

It should be noted that the shock interaction with a fan might possibly produce expansion waves in place of the transmitted or reflected shock waves. For the particular fan interactions analyzed here, which are believed to be typical for modern axial-flow turbo-fan engines, only shock waves would be possible, so only shock waves are assumed here for the transmitted and reflected waves. The addition of expansion waves to the analysis would be straightforward.

Prior to the arrival of the incident shock, the fan compresses region-2 flow upstream into region-3 flow downstream. After arrival of the incident shock at the fan, the fan compresses region-2" flow upstream into region-3" flow downstream. The fan therefore goes from a pre-interaction operating point between regions 2 and 3 to a post-interaction operating point between regions 2" and 3".

The flow properties in the initial regions 2 and 3 are determined by a match between the fan characteristics and the inlet and downstream engine characteristics. For typical current aircraft the flows entering and leaving the fan are subsonic, so the inlet, fan and downstream engine characteristics are interacting. The flow properties in region 2' are determined by knowing the strength of the incident shock. The properties in regions 2", 3' and 3" are determined by a match between the strengths of the transmitted and reflected shock waves and the characteristics of the fan. Results for a typical fan will be shown.

140

This quasi-steady interaction of the shock with a fan has been programmed into a FORTRAN IV code called QBIF (Quasi-steady Blast Interaction with a Fan). The fan characteristics are a code input.

The important questions stemming from the QBIF calculation are (a) what operating point the fan would arrive at, (b) what effect the reflected shock would have upon upstream flow within the inlet and (c) what effect the transmitted shock wave might have on the flow downstream at the compressor inlet or through the bypass duct to the afterburner and the turbine outlet.

## 8.2 BLAST SHOCK AT ENGINE FACE

In view of the large number of tests and variables in the 0.1-scale B-1 inlet tests at AEDC, calculations with the QBIF code have been concentrated in this study on the test conditions of a selected run in the test series at AEDC, Run 40 (Part 619). The pre-blast flow and blast conditions for this run are tabulated in Table 8.1.

The wind-tunnel Mach number for Run 40 (Part 619) was 0.85 and the mass flow at the engine faces was 351.9 and 351.0 lb/sec full-scale for the outboard and inboard inlets, respectively. The blast shock strength scaled to standard sea level conditions was 5.8 psi. The jump in average total pressure at the two engine faces when the blast shock arrived was 0.435 and 0.150 of the pre-blast free-stream total pressure, respectively, for the two inlets. The corresponding ratios of the static pressure behind the shock to the value ahead is 1.280 and 1.101 at the engine face for the respective inlets.

## 8.3 ENGINE FAN CHARACTERISTICS

For two-stage fan characteristics representative of current technology, the data of Reference 8.1 have been employed. A sketch of this fan and a tabulation of its passage dimensions are reproduced from Reference 8.1 in Figure 8.2. The fan was designed for a tip speed of 1450 ft/sec, an overall pressure ratio of 2.8 and a corrected mass flow of 184.2 lbm/sec. The efficiency at this design operating point was found to be 85.7 percent from tests (Reference 8.1). The overall performance maps for the fan are presented in Figure 8.3. An enlarged

141

## TABLE 8.1

### INLET DATA OF RUN 40 (PART 619) PERTINENT TO
### BLAST SHOCK-FAN INTERACTION

### TUNNEL DATA

<u>PREBLAST</u>                                                    <u>BLAST</u>

$M_o = 0.850$                                         $\Delta p = 5.8 \text{ psi}^*$

$P_{t_o} = 11.801 \text{ psia}$

$p_o = 7.358 \text{ psia}$

$T_{t_o} = 569^o\text{F}$

### ENGINE-FACE DATA

|  | OB INLET | IB INLET |
|---|---|---|
| <u>PREBLAST</u> | | |
| $M_2$ | 0.519 | 0.511 |
| $P_{t_{av}}/P_{t_o}$ | 0.979 | 0.980 |
| W2R-FS(lb/sec) | 351.9 | 351.0 |
| <u>BLAST</u> | | |
| $(P_{t_{av_s}} - P_{t_{av}})/P_{t_o}$ | 0.435 | 0.150 |
| $p_s/p$ | 1.280 | 1.101 |

$^*$Scaled to one atmosphere ambient pressure.

(b)  Schematic of two-stage fan test arrangement.

| Station | Inside diameter | | Outside diameter | | Inside diameter | | Outside diameter | |
|---|---|---|---|---|---|---|---|---|
| | in. | m | in. | m | Axial distance, z | | | |
| | | | | | in. | m | in. | m |
| 1 | 10.00 | 0.254 | 32.48 | 0.825 | -5.20 | -0.132 | -5.20 | -0.132 |
| 2 | 10.26 | .261 | 32.33 | .821 | -3.70 | -.094 | -3.70 | -.094 |
| 3 | 10.94 | .278 | 31.96 | .811 | -2.245 | -.057 | -2.245 | -.057 |
| 4 | 12.40 | .315 | 31.00 | .787 | .0 | .0 | .42 | .011 |
| 5 | 14.84 | .377 | 29.93 | .760 | 3.30 | .084 | 2.75 | .070 |
| 6 | 15.22 | .387 | 29.67 | .754 | 3.80 | .097 | 3.45 | .088 |
| 7 | 16.85 | .428 | 28.96 | .736 | 6.15 | .156 | 6.33 | .161 |
| 8 | 17.39 | .442 | 28.58 | .726 | 7.23 | .184 | 7.57 | .192 |
| 9 | 18.35 | .467 | 28.12 | .714 | 9.20 | .234 | 8.82 | .224 |
| 10 | 18.58 | .472 | 27.90 | .709 | 9.80 | .249 | 9.59 | .244 |
| 11 | 18.90 | .480 | 27.60 | .701 | 11.85 | .301 | 11.93 | .303 |
| 12 | 18.90 | .480 | 27.60 | .701 | 13.50 | .343 | 13.50 | .343 |
| 13 | 18.90 | .480 | 27.68 | .703 | 15.00 | .381 | 15.00 | .381 |
| 14 | 18.90 | .480 | 27.94 | .709 | 16.50 | .419 | 16.50 | .419 |
| 15 | 18.90 | .480 | 28.54 | .724 | 18.55 | .471 | 18.55 | .471 |



(a)  Flow path.

Figure 8.2.  Configuration of NASA two-stage axial-flow fan.

143

Figure 8.3. Performance maps for NASA two-stage axial-flow fan.

map is presented in Figure 8.4 for the fan total-pressure ratio. Four operational lines have been added to this map for fan exit Mach numbers of 0.45, 0.51, 0.64 and 1.00.

Six preblast operating points were calculated for the two engine-face Mach numbers of Table 8.1 and for three values of the stall margin — 8, 15 and 24 percent. The definition of stall margin, SM, used here is

$$SM = \frac{\left(\dfrac{p_{t_3}}{p_{t_2}}\right)_{stall} - \left(\dfrac{p_{t_3}}{p_{t_2}}\right)}{\left(\dfrac{p_{t_3}}{p_{t_2}}\right)_{stall}} \times 100, \text{ percent}$$

where $p_{t_3}/p_{t_2}$ is the fan total-pressure ratio at the operating point and $(p_{t_3}/p_{t_2})_{stall}$ is the value at stall or surge for the same equivalent mass flow.

8.4  Blast Effect on Fan Operation

Calculations with the QBIF code were carried out for the fan of Reference 8.1 for three initial conditions of the two inlets. The fan operating points that would result are presented in Figure 8.4 for the three initial stall margins for the two inlets. The shock pressure ratio at the engine face, $p_2'/p_2$, is the parameter for the curves. The results show that increasing this shock strength reduces both the equivalent mass flow and the total pressure ratio.

The incident shock pressure ratio at the engine face for the inboard inlet in Part 619 was 1.101. The operating points resulting from this interaction with the fan for the three initial stall margins are joined in Figure 8.4 by the curve for $p_2'/p_2 = 1.10$. The points for double and half that shock overpressure, i.e. $p_2'/p_2$ equal 1.20 and 1.05, are joined similarly. These resulting operating points are all well within the area of the performance map where acceptable operation would be expected. Therefore the blast should produce no problem for the inboard fan according to the QBIF code calculations.

145

Figure 8.4. Two-stage-fan overall performance map.

The pressure ratio of the shock at the engine face in the outboard inlet in Run 40 was 1.28. The resulting three operating points for the three stall margins wind up much closer to the $M_3=1.0$ operating line. The flow in stator no. 2 of the fan would be expected to choke at about midway between the $M_3=0.64$ line and the $M_3=1.00$ line. Therefore the blast would be expected to choke the fan in the outboard inlet for this shock strength and an initial stall margin of 24 percent.

The resulting operating points are also shown for about a 42 and 100 percent increase in shock overpressure, i.e. $p_2'/p_2 = 1.40$ and 1.56, and one-half the overpressure, $p_2'/p_2 = 1.14$. The higher overpressures would be expected to choke the fan for the initial 24 percent stall margin.

Choking of a fan for the short durations that would be experienced during penetration of a blast wave is not expected to be harmful to its operation on this quasi-steady basis. The problem for the fan would arise if it be driven to the surge-stall boundary. The effect of this initial shock from the blast wave for the cases run, however, is to increase the downstream Mach number, thereby driving the fan away from the surge-stall boundary. What the effect would be for other initial fan points remains to be explored.

8.5 FAN REFLECTED SHOCK

The properties of the shock reflected upstream from the fan, following the interaction of the incident shock with the fan, are presented in Figure 8.5 from the calculations with the QBIF code.

In Figure 8.5(a) the pressure of the reflected shock in excess of the initial pressure is presented as a ratio to the overpressure of the incident shock, $\dfrac{p_2''-p_2}{p_2'-p_2}$. This excess pressure ratio is plotted as a function of the pressure ratio of the incident shock, $p_2'/p_2$. A value of the ordinate of unity corresponds to no reflected shock and a value of two indicates an overpressure of the reflected shock equal to the overpressure of the incident shock.

147

(a) Excess pressure ratio.

Figure 8.5. Variation of fan reflected shock properties with incident shock pressure ratio.

148

INCIDENT SHOCK PRESSURE RATIO, $p_2'/p_2$

(b) Particle Mach number.

Figure 8.5. Continued.

RUN 40 (PART 619)
$M_o = 0.85$
W2RFS = 350 LB/SEC
TUBE 2
$\Delta p = 5.8$ PSI

149

INCIDENT SHOCK PRESSURE RATIO, $p_2'/p_2$

(c) Excess total-pressure ratio.

Figure 8.5. Concluded.

EXCESS TOTAL PRESSURE RATIO, $\dfrac{p_{t_2}'' - p_{t_2}}{p_{t_2}' - p_{t_2}}$

RUN 40 (PART 619)
$M_O = 0.85$
W2RFS = 350 LB/SEC
TUBE 2
$\Delta p = 5.8$ PSI

FAN
STALL MARGIN
24%
15
8

CHOKED
ORIFICE

OB INLET

IB INLET

IB
INLET

OB
INLET

TIME

150

A common method for simulating an engine in inlet testing is to choke the flow leaving the inlet at about the downstream location for the engine. This is done by using a fixed choked orifice or nozzle or adjustable vanes. The latter were employed with the 0.1-scale B-1 inlet and were located near the fan station.

The properties of shocks reflected upstream from a choked orifice (or nozzle or vanes) and fan are compared in Figure 8.5(a). The values of the incident shock pressure ratio at the engine face for Run 40 are indicated on the abscissa. The increment in excess pressure ratio of the reflected shock for the fan is markedly greater than for the choked orifice. Under the shock conditions of the outboard inlet in Run 40 it is 33 to 45 percent greater. This means that the strength of the shock reflected upstream from the fan would be that much greater with a turbofan engine than was experienced in the tests in the 0.1-scale B-1 inlet.

The partial Mach number, $M_2''$, of the flow behind (downstream) the reflected shock and entering the fan or a choked orifice is shown in Figure 8.5(b). The inflow Mach number for a choked fan would be constant. The decrease for the fan is due primarily to the increase in temperature and speed of sound by the double shocking of the air, and only partially to the reduction, generally, in particle velocity.

Analyses of aircraft turbine engines are generally concerned with the total pressure. The excess total-pressure ratio,

$\dfrac{P_{t_2}'' - P_{t_2}}{P_{t_2}' - P_t}$ , is presented in Figure 8.5 (c). It is not as large for

either the choked orifice or fan as was the excess static pressure. In other words, this means that the total pressure does not get incremented as much by the reflected shock relative to the increment by the incident shock as does the static pressure. However, the total pressure increment due to the reflected shock is markedly greater for the fan than for a choked orifice. For the outboard inlet and the shock conditions of Run 40 (Part 619), the increment would be 34 to 50 percent greater for the fan than for the choked orifice.

The variation of the properties of the shock transmitted downstream by the fan as a function of the incident shock strength are presented in Figure 8.6. The pressure ratio for the transmitted shock wave is shown in Figure 8.6(a). The ratio is always less than for the incident shock, but it is relatively large. The effect upon the downstream engine operation might be significant.

The particle Mach number $M_3''$ downstream of the fan for the transmitted shock is plotted in Figure 8.6(b). It increases with the strength of the incident shock in all cases. It is reasonable to expect that the second stator of the fan would choke at a downstream Mach number somewhere near 0.8, so the downstream Mach number would not increase beyond that point. In the absence of data on the choke Mach number, the curves have been continued as if there were no choking.

This condition for a choked second stator would be nearly reached for the fan operating at a stall margin of 24 percent and incident shock pressure ratios approaching 1.6. For lower initial stall margins the pressure ratio of the incident shock would need to be considerably greater for choking. In summary, the result of this analysis with the QBIF code is to indicate that this fan operating at the initial conditions of the Run 40 test would not experience any operational problems on a quasi-steady basis for (step) shocks at the engine face of the magnitude expected of Run 40 for the incidence angle, $\phi$, of 100 degrees and shock overpressure of 5.8 psi scaled to 1 atm. The upstream reflected shock would be notedly stronger, however, than for the choked control vanes used (as the simulated engine) in the tests.

The effect of the reflected shock on the flow within the inlet will be examined in Section 9. The strength of the transmitted wave is large, Its effect on engine operation downstream is not known.

Figure 8.6. Variation of fan transmitted shock properties with incident shock pressure ratio.

(a) Shock pressure ratio

(b) Particle Mach number.

Figure 8.6. Concluded

154

SECTION IX

REFLECTED SHOCK-BOUNDARY LAYER INTERACTION WITHIN INLET

Another important feature of the inlet-blast interaction problem is
the interaction inside the inlet between the blast shock waves and the
inlet boundary layer. The sketch in Figure 9.1 depicts the features of
shock-boundary layer interaction that might occur on the walls of the
inlets of the B-1 type due to the reflected shock from the fan. The
flow in the boundary layers would be forced to negotiate the adverse
pressure gradients associated with these shock waves moving upstream
from the engine forces. If sufficiently strong, the adverse pressure
gradients could cause the boundary layers to separate on the inlet
walls, depending upon the boundary layer characteristics. This pos-
sibility will be assessed in this section.

The interaction is complicated by the variation of the "free-
stream" properties within the inlet both in the flow direction and time-
wise. The total pressure and total temperature in particular both vary
longitudinally and with time as the reflected shock moves upstream.
More data are required for this analysis than were measured in the tests
with the 0.1-scale B-1 inlet, so calculations made of the flow with the
BID code have been employed.

9.1 SHOCK-BOUNDARY LAYER CALCULATION

The development of the boundary layers was computed using the
results of BID code calculations to provide the distributions of the
free-stream properties of static pressure, total pressure and total
temperature near each wall. The BID code models the fan as a choked
orifice, in line with the 0.1-scale inlet model. The distributions for
each wall of the inlets were selected corresponding to the time when the
static pressure gradients appeared to be relatively steep within the
blastward inlet. No systematic attempt was made to select the most
adverse distributions for the boundary layers. These properties defined
the conditions at the outer edge of each boundary layer.

155

BLAST WAVE

SHOCK

SHOCK                    DISTORTION

INLET                              FAN

Figure 9.1.   Boundary layer separation and distortion from fan reflected shock wave.
reflected shock wave.

156

The growth and behavior of the boundary layers along the walls for these free-stream conditions were computed using the BLAYER code of NASA, presented in Reference 9.1. Since the Reynolds number of the boundary layers would be generally large relative to the transition value, the boundary layers were assumed to be turbulent from the leading edge of each surface.

The BLAYER code assumes a constant total pressure and total temperature outside of the boundary layer. Because they both generally vary significantly for the calculations made, the calculations were carried out piecewise taking the total pressure and total temperature as constant over each segment. This procedure was found to be significant to the values computed, but it is not believed to alter the general conclusions reached from the calculations.

The distributions of the free-stream properties that were selected were assumed to be frozen. That is they were taken as non-varying in time, whereas they do change as the reflected shock moves upstream. The significance of this assumption is not readily assessable. The BLAYER code applies only for the frozen pressure distribution, so the question must be resolved at a later time.

The BLAYER calculations were performed for the full-scale B-1 inlets, as scaled up from the 0.1-scale model. The blast wave in the BID calculation is assumed to arrive from the side of the aircraft, that is $\phi = 90^o$ ($0^o$ is a head-on intercept), with a shock overpressure of 5.0 psi. The flight Mach number was taken to be 0.85 and the mass flow rate in the inlets to be 350 lb/sec.

9.2 SHOCK-BOUNDARY LAYER RESULTS

The pressure distributions for the boundary layer calculations with the BLAYER code are presented in Figure 9.2 along with the boundary-layer incompressible form factor $H_i$ that resulted from these calculations.

The boundary-layer factor $H_i$ is a parameter essentially representing the velocity distribution across the boundary layer (normal to the wall).

157

(a) Blastward inlet.

Figure 9.2. Effect of fan reflected shock on boundary layers of inlets.

(b) Leeward inlet.

Figure 9.2. Concluded

159

When the velocity distribution is more uniform, the parameter approaches unity. A value of 1.2 to 1.4 is typical for a turbulent boundary layer on a flat plate in the absence of a pressure gradient. In an adverse pressure gradient (increasing pressure in the direction of flow) the velocities decrease toward the wall so $H_i$ increases. When the velocity gradient normal to the wall goes to zero, the flow can separate from the wall. Experience shows that separation may occur for $H_i$ values as low as 2.0 and definitely by 2.8.

The $H_i$ distributions along the walls for the blastward inlet are presented in Figure 9.2(a). The results indicate that the boundary layers would separate on both the cowl and the ramp surfaces. The cowl boundary layer would separate upstream of the ramp, so it is quite probable that the stream would actually be deflected to the ramp side and that the ramp boundary layer would not separate. In any event, separation would take place on one side of the blastward inlet which would produce significant distortion at the engine face when the separated flow arrives there.

The $H_i$ distribution for the leeward inlet is shown in Figure 9.2(b). The distribution for the ramp is not presented because the longitudinal variation in total pressure outside of the boundary layer is so large as to make conclusions from the results undependable. The $H_i$ distribution for the cowl boundary layer reaches a maximum of only 1.8, which is below the threshold of separation.

In the BID code the fan is modeled as a choked orifice as mentioned (for matching to the 0.1-scale B-1 inlet model data), so pressure gradients for the leeward cowl may be 15 to 40 percent greater with a fan. This might be enough to separate the cowl boundary layer but the question is unresolved.

There is an effective antificial viscosity in the BID code because the cells are fixed in space (also called "shock capturing"). This has the effect of reducing pressure gradients, resulting in lower calculated values of $H_i$.

160

The question then arises as to why larger values of the distortion parameters were not measured during the test periods with the 0.1-scale B-1 inlet. Some rough estimates of the time-distance relationships of events within an inlet are useful in examining this question. Several are depicted in Figure 9.3 for Mach 0.85 flight conditions. The initial shock would reach the engine face in about 0.9 milliseconds and the vanes is about 1.1 milliseconds. The reflected shock from the vanes moves upstream more slowly, as shown. Somewhere within the inlet the boundary layer would separate. To estimate when the separated flow might reach the engine face, some other velocities must be considered.

The particle velocity within the duct is about one-third of the initial (incident) shock velocity. Vorticity shed from the leading edge of the cowl or splitter lips would first travel at about one half of the particle speed and slowly speed up as it moves out into the free stream. Assuming a step speed-up half way down the duct, the vortex would reach the engine face at 4.2 milliseconds.

The blast-type flow period produced by the shock tube exit flow at the inlet is terminated by the arrival of the shock-tube cold gas or the backward-facing shock or compression wave, observed as a sudden increase in the rate of pressure change at the inlet. In the case shown in Figure 9.3 this event would occur at the inlet entrance at about 3.3 milliseconds, and could arrive at the engine face by about 4.2 milliseconds.

The speed of the front of the separated boundary layer is not known, but it is reasonable to expect it to be significantly less than for the free-stream particles. For estimation purposes, if the reflected shock would separate the boundary layer midway down the inlet and the front of the separated flow travels at one-half of the particle velocity, the separation zone would reach the engine face at somewhat more than a millisecond after the termination of the test period.

Figure 5.8 shows that the distortion parameter IDC increased considerably for the blastward inlet for $\Delta p$ = 5.0 and 5.2 psi beginning at about one millisecond after termination of the 3.3-millisecond nominal test period, indicated in the figure by the arrows. IDR increased at

161

Figure 9.3. Inlet time-distance relationships for a flight Mach number of 0.85 and a mass flow rate of 350 lb/sec.

162

about the same time but not in as great a proportion, in comparison with the values during the test period. IDL increased apparently well beyond the full-scale value of 1.50.

For the leeward inlet, Figure 5.9, the distortion indicated is not as large. IDC and IDL appear to have increased beginning at about the end of the nominal test period, particularly for the 5.2 psi shock. IDR, on the other hand, decreased. IDL experiences only brief bursts above a value of about 1.1.

Because these large increases in distortion occurred after the expected arrival of the backward facing shock or compression wave, a question does arise as to what degree the high level of distortion may have been due to the character of the blast wave during the later period. This question should be examined to the extent possible for the present data.

SECTION X

DISCUSSION

This section presents a summary and discussion of some of the important aspects of the development and testing program, most of which are described in detail in previous sections, and indicates some recommendations for future developments. Topics discussed are the blast generator development, the 16T wind tunnel blast tests, the BID code for predicting inlet blast flows and blast-fan interactions.

10.1 BLAST GENERATORS

The blast generation development program began with theoretical REFLECT2/S2D code calculations for the firing of a shock tube into still air, followed by firings of two-in.-dia shock tubes into the AEDC 1T (one-foot-square) wind tunnel at Mach numbers from 0.6 to 0.9 (Sec. 2). Results of these tests, for the case of the shock tube firing perpendicular to the tunnel axis, gave useful blast type flows in this Mach number range for the overpressure range 2 - 5 psi (referred to sea-level ambient pressure) for distances from the tube exit of about 4.5 diameters, for polar angles from the tube axis from $-15^{\circ}$ to $+30^{\circ}$ downstream of the tube. Durations of nearly constant blast pressure (to 30% decay) were obtained for these conditions in the range of about 0.5 to 2 milliseconds per foot of tube diameter, with best results being obtained at a polar angle of $15^{\circ}$. At downstream polar angles from the tubes of $45^{\circ}$ or more, the blast wave durations were generally much shorter and were not of interest. Also, it was found from the 1T tests that if the shock tube driver pressure was too low compared to the ambient pressure a non-constant pressure type of blast wave profile was produced, characterized by an extremely rapid decay.

Results of the above calculations and small shock tubes were found to be essential in selecting the shock-tube dimensions, locations and driver pressures for the subsequent development of large shock tubes for the AEDC 16T (16 foot square) wind tunnel tests.

The three large shock tube installation designed and constructed for the 16T wind tunnel tests had the following characteristics. Distances from the shock tube exits to the inlet were 3.8 to 4.3 tube

164

diameters, at polar angles from 11.2$^o$ to 28.3$^o$. Shock tube driver pressures of 55 to 186 psia were used, usually at a tunnel ambient pressure of one-half atmosphere.

Definition of the properties of the blast waves produced at the inlet location in the 16T tests was made using both measured data from the tests as well as the test results from the 1T tests. The strength of the blast shock was well defined at probe locations by the 16T measurements, but interference from the inlet model degraded the definition of the flow following the shock somewhat. Firings in the 16T tunnel without a model would be useful for defining these blast properties, but they were precluded by limitations on tunnel time; as an alternative, an analysis of model interference on the blast measurements is recommended. The incidence angle of the blast shock was defined from comparative arrival times at several pressure transducers; shadowgraphs would be a useful alternative for this measurement in future tests for greater accuracy.

Shock-tube dimensions of a 22.6 in-ID and a 17-ft length were selected to provide the best combination of blast wave characteristics within space constraints of the wind tunnel for the three shock tubes. Commercial pre-scored, pre-stressed diaphrapms (rupture discs) in a double-diaphragm arrangement provided fast, clean-opening diaphragm bursts free of any petal debris. By using three shock tubes the number of firings during the test period was essentially doubled over using a single tube.

10.2   THE 16T WIND TUNNEL TESTS AND ANALYSIS

The 0.1-scale B-1 inlet model used in the 16T tests had been mated previously to the tunnel sting support, so only some strengthening of the model and the 16T tunnel walls for loading by the shock-tube driver gas was required for testing.

Blast tests were performed at Mach 0.55, 0.70, 0.85 and 0.90 with inlet mass flow rates ranging from 235 to 350 lb/sec (full scale), shock overpressures from about 2 to 6 psi (referred to sea level) and model yaw angles of 0 and 5 degrees (nose away from shock tube).

165

Typically, blast type flows lasting about 3.3 milliseconds were achieved at the inlet, with corresponding nearly constant pressure durations (to 30% decay) of between 1 and 4 msec. This met test requirements amply. However, for future tests vortex and boundary-layer separation phenomena effects that are now believed to be important at later times make it desirable to double the test durations.

The test durations might be increased about 50 percent by moving the model about four feet off the centerline of tunnel, increasing the distance from the shock tubes and thereby the blast duration, but the shock-tube dimensions would need to be reexamined. Any additional increase in duration would require using a smaller-scale model (gaining thereby in scaled duration).

The blast interaction with the inlet as observed in the tests can be divided into three characteristic phases in terms of events at the engine face. During the first phase the blast shock travels down both inelts and reflects from the choked vanes (or fan for the full-scale engine), then returning to the engine face. In the second phase any vortex shed from the leading edge of the splitter, for example, would reach the engine face, and shock wave-boundary layer interaction within the inlet would take place and also reach the engine face. After these two stages, events are believed to happen relatively slowly, that is on a quasi-steady basis, so steady-state test results and analyses would be applicable ─── this is called the third stage. Attention here is focused primarily on the first two stages.

In the blastward inlet during the first period the multiple reflec-tions of the shock result in a "staircase" of shocks arriving at the engine face over about a 0.3-msec period followed by some decay preceding the arrival of the reflected shock in about another millisecond. In the leeward inlet the shock diffracts around the splitter and enters the inlet more normal to the model centerline. It reaches the engine face as essentially a single shock, much weaker than for the blastward inlet.

166

When the shock in the blastward inlet reaches the engine face,
distortion IDL values near unity are observed which might be of some
concern during maneuvering or other stressful flight conditions.  The
distortion patterns examined have had high total pressures on the cowl
side of the face.  The distortions in the leeward inlet during this
period were generally lower.

Calculations were made of the blast shock interaction with a fan
typical of current technology for turbofan engines.  Shock strengths
measured at the engine face in the 16T tests were used.  The interaction
was assumed for simplification purposes to be quasi-steady with a step
shock (no ramp or decay).  For the blastward inlet the results indicate
the fan would choke at the second stator for the lateral ($\phi \approx 90^{o}$) blast
intercept.  This presumably presents no operational problem, but the
results are not believed to be general.  The interaction should be studied
for the range of conditions expected.  Of clear concern to engine operation
are effects produced downstream by the transmitted shock wave upon the
afterburner and turbine rear stages and upstream by the reflected shock
upon flow within the inlet.

Concerning the latter, boundary-layer calculations indicate that the
reflected shock would definitely separate the upstream boundary layers
within the blastward inlet for a 5-psi blast shock.  This is expected to
result in serious distortion at the engine face.

In the tests IDL values over 1.25 were observed at the engine face
at about 4 milliseconds after shock arrival there.  This is about one
millisecond after the end of the validated duration of blast type flow,
therefore it is possible the distortion at that late time was due to
variations in the blast wave.  In view of the significance of this effect
to engine operation, it is recommended that the blast data be analyzed
further to verify that the late-time distortions are relevant to the
blast-inlet problem.

Interaction of the reflected shock with the boundary layers in the
leeward inlet could only be analyzed to a limited extent, because of
restrictions in the methods of analysis available.  Separation on the
cowl side might occur if calculations were refined, but not as carried
out.  Estimation of separation on the ramp side requires an assessment

167

of separation effects in BID calculations for the leading edge of the ramp and the improvement in the boundary-layer method, needed also for the blastward inlet.

Vortex formation at the splitter is another possible source of distortion for the leeward inlet. Distortion values in the leeward inlet did reach large values in the tests for times after the 3.3-msec blast flow period but whether the shedding of vortices is also a blast inlet problem depends on resolution of the late-time blast-wave data.

During the about 3.3-msec period of blast type flow the maximum IDL values were affected by the inlet mass flow rate. But there were no definite significant effects of either Mach number or inlet yaw angle on IDL.

The whole question of blast distortion relative to its effect upon engine operation is an open question at this point. The particular distortion indices used in work with the B-1 inlet (IDC, IDR, IDL and IDT) have been employed here, basically as parameters that have met with success for distortions of the type obtained in typical flight situations (maneuvering flight, throttle transients, etc.). There are many other distortion parameters in use. Also, there are factors involved in a blast interaction that are not reflected in these parameters, such as the rapidity of the changes due to the shocks, and features of the spatial distortions that are significantly different, etc. The effects of these differences on engine operation must be answered before the question can be resolved.

The BID code provides good predictions of the observed pressure histories in the inlet duct and at the engine face, particularly in reproducing the principal events, such as shock reflections. The pressures predicted at the engine face tend to be slightly low but the trends are generally good, so that a simple factor (accounting for numerical viscosity effects) would be expected to bring them into good agreement. The BID code at present does not include blast decay; this addition to the code would provide an improvement at late times. A second improvement that is recommended is to extend the code to three

168

dimensions; this would allow for modelling the hub and would account for differences in the vertical direction.  Work is recommended to further correlate distortion predictions of the BID code with the test data.

BID code calculations have been made for intercept angles from 90 to 135 degrees from head on.  The 90-deg intercept results in much larger total-pressure increment at the engine face with greater pressure-time variations than for the more rearward intercepts.  Further studies extending the blast intercept angles are recommended.

Regarding the effects of the observed inlet pressures on an engine fan stage, the calculation of the quasi-steady interaction of the blast shock with a fan and with a choked flow for a 90-deg intercept indicates the reflected shock would be considerably stronger for a fan then for a choked-flow condition, as used in these tests, by as much as 43 percent for a typical case.  Control of flow by means of a choked nozzle or vanes is a standard technique used in inlet testing.  Consideration should be given to this problem of weaker reflected shocks in planning and analyzing results of similar blast-inlet testing.

## SECTION XI
### CONCLUSIONS

From the analyses and wind-tunnel tests carried out to simulate nuclear blast interaction on a B-1 type engine inlet, the following conclusions are reached.

1. Blast simulations capability has been developed and demonstrated in the AEDC 16T wind tunnel for blast strengths of 2 to 6 psi, scaled to sea-level conditions, and nearly constant blast pressures (with less than $\pm$ 30-percent decay) lasting from 1 to 4 milliseconds.

2. A data bank of blast interaction data has been developed with the 0.1-scale B-1 inlet for lateral intercepts, varying wind-tunnel Mach number from 0.55 to 0.90, inlet mass flow rate from 235 to 350 lb/sec. (full scale), shock overpressures from 2 to 6 psi (sea level) and model yaw angles from 0 to 5 degrees.

3. The BID code predicts satisfactorily the principal features of the pressure time history within the inlet duct and at the engine face. Additional work is recommended for prediction of distortion at the engine face. Recommended additions to the code include accounting for blast decay and extending the code to three dimensions.

4. Four potentially adverse effects to engine operation from blast interaction were identified: blast-induced distortion, fan choking, afterburner blow out and shock-boundary layer induced distortion.

5. Blast-induced distortions during the time of definite blast-type flow in the inlet were usually smaller than but did sometimes reach normal inlet allocation levels for the B-1 airplane. Distortions at later times greatly exceeded the allocation. Boundary-layer separation in the inlet by simulated fan (vane) reflection of the blast shock is suspect for the latter distortion levels.

170

6. Distortion studies made here are severely limited by the unavailability of a parameter for judging the effect of transient distortions on gas-turbine engine operation. Blast tests with an inlet-engine combination are strongly recommended for meeting this need.

# REFERENCES

1.1 Pierce, D., <u>Simulation of Blast Waves in a Supersonic Wind Tunnel</u>, British Royal Aircraft Establishment, Tech. Note No. Aero. 2665, January 1960.

1.2 <u>Test Facilities Handbook (Tenth Edition), Arnold Engineering Development Center</u>, Arnold Air Force Station, Tennessee, May 1974.

2.1 AEDC Reports, Data tabulations, Plots and Tapes on the Inlet Blast Effects Test, AEDC Project P41A-07A, Test TM 332, 1975.

4.1 Mitchell, C.E., and Powers, J.L. Jr., <u>Pretest Information for the 0.10 Scale B-1 Inlet Development Model II Nuclear Blast Effects Test in the AEDC 16-Foot Transonic Propulsion Wind Tunnel</u>, Rockwell International Report NA-76-593, August 1976.

4.2 AEDC Reports, Data Tabulations, Plots and Tapes on the DNA B-1 Blast Effects Test, AEDC Project P41T-D2A, Test TF-419, 1976-1977.

5.1 Haagenson, W.R., and Randall, L.M. <u>Inlet Development for the B-1 Strategic Bomber</u>, Rockwell International, AIAA Paper No. 74-1064, 1974.

5.2 Hercock, R.G., and Williams, D.D., Aerodynamic Response, in <u>Distortion Induced Engine Instability</u>, AGARD-LS-72, 1974.

5.3 Koch, K.E., and Rees, R.L., <u>Analysis of Pressure Distortion Testing</u>, NASA CR-2766, 1976.

5.4 Brimelow, B., <u>Techniques for Establishing Propulsion System Stability</u>, Technical Memorandum APTA-TM-69-12, April 1969.

6.1 Thompson, J.H., Tomayko M.A. and Ruetenik, J.R. <u>BID Code for Computing Aircraft Engine-Inlet Response to Blast Disturbances</u>, Kaman AviDyne TR-130. (In preparation).

8.1 Ruggeri, R.S., and Benser, W.A., Performance of a Highly Loaded Two-Stage Axial-Flow Fan, NASA Technical Memorandum X-3076, August 1974.

9.1 McNally, W.D., FORTRAN Program for Calculating Compressible Laminar and Turbulent Boundary Layers in Arbitrary Pressure Gradients, NASA Technical Note D-5681, May 1970.

172

REFERENCES (CONT'D)

A.1 Ruetenik, J.R., <u>Analysis of Godunov Method with Fixed Mesh for Hydrodynamic Calculations</u>, Sponsored by Kaman AviDyne Internal Research and Development Program, Proprietary, 1973.

A.2 Lee, W.N., Smiley, R., Ruetenik, J.R. and Hobbs, N.P., <u>Evaluation of Back-Blast Pressures Produced by a Wing-Mounted 105-MM Recoilless Rifle</u>, Kaman AviDyne Report TR-97, Watervliet Arsenal Technical Report WVT-CR-74023, 1974.

A.3 Thompson, J.H., <u>REFLECT2 Computer Code for Ground-Reflected Blast Waves and Shock Tube Jet Simulation</u>, Kaman AviDyne TM-98, 1976.

A.4 Thompson, J.H. <u>REFLECT Computer Code for Ground-Reflected Blast Waves</u>, Vol. II, Computer Program Description, Kaman AviDyne Report TR-96, Defense Nuclear Agency Report 3470F-2, 1975.

## APPENDIX A

## THEORETICAL STUDIES OF THE FLOW FIELD PRODUCED BY
## FIRING A SHOCK TUBE INTO A STATIONARY FLUID

### A.1  INTRODUCTION

In order to obtain background and planning information for the wind
tunnel tests of this report, KA performed a series of theoretical studies
for the axi-symmetrical problem where a prescribed flow exits from a
shock tube into initially stationary air ($\gamma = 1.4$) at an ambient pressure
of one atmosphere (14.7 psia).  The external transient pressure disturbance
or blast field produced in the fluid was calculated by two KA computer
codes for a wide range of shock tube firing conditions, as described below.

### A.2  S2D CODE STUDIES

Initial calculations were made with the KA S2D Eulerian computer
code (References A.1 and A.2), with several different representations of
the geometry of the exit end of the tube.  In one representation, shown
in Figure A.1a, the shock tube was assumed to be fired into a half-space
bounded by a rigid wall.  In a second representation, the shock tube
was assumed to protrude into the flow from a boundary by various distances,
X, as shown in Figure A.1b, with a non-reflecting boundary condition
being assumed to apply at this "boundary" distance behind the end of the
shock tube.  More specifically, the flow field for $x < -X$ in Figure A.1b
was assumed to have properties independent of x, with X being varied from
about 0.3 to 1.5 tube diameters.

These particular S2D solutions were used to determine the sensitivity
of the external flow field to the boundary conditions as described above.
In general, it was found that, for the range of exit pressures considered,
from 37 to 103 psia, the pressures at all distances two or more tube
diameters downstream of the tube exit were essentially independent of
the assumed boundary conditions.

Since our interest was primarily in large downstream distances, the
above observations indicated that we could more profitably study this
shock-tube fluid flow problem by making use of the REFLECT2 computer code
described below, which permits better resolution of pressure transients,

175

(a) Wall boundary.



(b) No wall boundary.

Figure A.1. Problem of a shock tube firing into a stationary fluid.

but is presently less capable than the S2D code for handling complex boundary conditions.

## A.3 REFLECT2 CODE STUDIES

Calculations were made with the KA REFLECT2 Lagrangian computer code (References A.3 and A.4) for the shock tube exit flow conditions of Figure A.1a for a range of exit pressures ($p_2$) from 24 to 103 psia.

Geometrical properties of the shock tube were taken as : inside diameter of 2 inches, driver length (LR) of 4.5 inches and driven length (LN) of 9 inches.

The shock tube exit flow conditions of pressure, density and velocity were taken to be the same as for a perfect one-dimensional shock tube flow with a specific heat ratio of $\gamma = 1.4$. In some solutions the exit flow conditions were assumed to be constant corresponding to the initial blast field behind the shock front. In other solutions, account was taken of the change in density produced when the contact surface originally at the tube diaphram position reached the exit end of the shock tube. Consideration of this contact surface change appeared to have little effect on the initial blast phenomena discussed below and is not discussed herein.

Figure A.2 presents sample time histories of pressure time histories at several positions along the axis of symmetry (r = radial distance from tube exit, d = diameter) for several firing pressures ($p_{41} = p_4/p_o$, $p_{21} = p_2/p_o$, $p_4 =$ driver pressure, $p_2 =$ shock (exit) pressure, $p_o =$ ambient pressure).

The following important features may be seen in Figure A.2. For the lowest shown driver pressure ratio, $p_{41} = 2.8$, the blast overpressure decays very rapidly after shock arrival reaching zero in less than 0.2 msec for the two inch-diameter shock tube. This waveform has a too rapid decay to be of interest for the present program. For the intermediate pressure ratio, $p_{41} = 10.4$, a much longer positive overpressure duation is obtained, about 0.4 msec and the overpressure is much more nearly constant during the positive phase than for $p_{41} = 2.8$. Finally, for the largest pressure ratio, $p_{41} = 15.3$, the positive phase duration is again about 0.4 msec, and the overpressure remains nearly constant for over 0.3 msec.

177

Figure A.2. Theoretical blast pressures outside of a shock tube.

178

Figure A.3 presents the calculated initial peak or transient blast overpressure, $\Delta p$, in the fluid along the axis of the shock tube, as a function of driver pressure ratio $p_{41}$, and exit pressure ratio, $p_{21}$ and radial distance in tube diameters from the tube exit, r/d.

The initial blast pressure is observed to increase nonlinearly with increasing pressure ratio and to vary roughly inversely with distance from the tube exit in the range of interest ($0.1 < \Delta p/p_o < 0.4$).

These theoretical results can be represented fairly well by the empirical equation:

$$\Delta p/p_o = 1.5 \; (6.39(r/d)p_{21}^{-1.75} + 0.4)^{-1.5} \qquad (A.1)$$

for the range $0.1 < \Delta p/p_o < 1.0$ where $1 < r/d < 10$ and $2 < p_{21} < 7$.

### A.4  CONCLUSIONS

The above results of these studies indicated that for reasonable shock tube driving pressure (under 600 psia) external shock overpressures in the desired range of 2 - 5 psi could be obtained at distances from the tube exit in the range of 3 - 10 diameters.  Also the calculated durations of the shock overpressure appeared to be long enough to be useful for simulating a nuclear blast on a small inlet model.  For example, at a driver pressure of 225 psia, at 4.5 diameters from the shock tube along the tube axis, the shock overpressure along the axis of the tube was calculated to be about 3.0 psi and the duration of nearly constant overpressure to be about 2.5 milliseconds per foot of tube diameter.

Figure A.3. Variation of overpressure with distance from shock tube.

## APPENDIX B

### STEADY-STATE PRE-BLAST TEST CONDITIONS IN THE AEDC 16T TUNNEL

This appendix presents AEDC tabulations of the steady-state wind tunnel and inlet operating conditions and inlet pressures and distortions existing immediately before the firing of each shock tube. The data are presented in the chronological order of the firings, by Part number, and are preceded by a table of nomenclature.

In these tables the following parameters are in error: IDCO, IDCI, IDLO and IDLI for data set 2 and PDO, PDI, PDPO and PDPI for both data sets 1 and 2. Corrected values of these parameters are available, but are not included here since they are not essential for the present study.

## Steady-State Printout Nomenclature

## DNA B-1 Blast Effects Test

## P41T-D2A (TF-419)

| Parameter | Description |
|---|---|
| AB1$\phi$-I | Outboard and inboard total bleed zone I areas, in.$^2$ |
| AB2$\phi$-I | Outboard and inboard total bleed zone II areas, in.$^2$ |
| ALPHA | Model angle of attack defined positive nose up, deg |
| BETA(SIC) | The angle of yaw defined positive pilot's right, deg |
| B5-1 | Fuselage configuration |
| C | Structural mode control fin's angle relative to the model axis |
| C3 | Structural mode control fin configuration |
| CP1SS | Claw probe one static pressure ratioed to free-stream total pressure |
| CP2SS | Claw probe two static pressure ratioed to free-stream total pressure |
| CP3SS | Claw probe three static pressure ratioed to free-stream total pressure |
| Date | The date the data were taken |
| Day | The day the data were taken, deg |
| ERCODE | Tunnel error code |
| E10 | Boundary layer control system configuration |
| G34-2 | Wing gutter configuration |
| H1I | Inboard lip height, in. |
| HL$\phi$ | Outboard lip height, in. |
| H16-1 | Wind hood configuration |
| HR | The hour the data were taken, hr |

| Parameter | Description |
|-----------|-------------|
| IDA | Average engine-face distortion index |
| IDC | Engine-face total circumferential distortion index |
| IDL | Fan stall margin ratio |
| IDR | Engine-face total radial distortion index |
| IDT | Engine-face overall total pressure distortion |
| I40 | Inlet configuration |
| IDC12 | Engine-face total circumferential distortion index at the hub |
| IDC45 | Engine-face total circumferential distortion index at the tip |
| J27 | Porous bleed hole configuration |
| L7 | Cowl configuration |
| M | Free-stream Mach number |
| MA | First ramp Mach number |
| MB | Mach number constants box |
| MIN | The minute the data were taken, min. |
| MFR2 | Engine-face mass flow ratio |
| MFR100 | Engine-face mass flow ratio corrected to 100% recovery |
| MODE | Mode code |
| M2 | Engine-face Mach number based on engine-face static to total pressure ratio |
| M2S | Engine-face Mach number based on weight flow |
| M6 | Flow meter configuration |
| NCN | Nozzle contour number |
| NSP | Normal shock parameter |
| N30-1 | Nacelle configuration |

| Parameter | Description |
|---|---|
| P | Tunnel static pressure, psfa |
| Part | Part number |
| PCA-1 | Primary plenum pressure, psfa |
| PCB-2 | Back-up plenum pressure, psfa |
| PD | Back-up prediction of peak instantaneous fan stall margin ratio |
| PDP | Primary prediction of peak instantaneous fan stall margin ratio |
| PLX | Model measured pressure ratioed to free-stream total pressure where L refers to outboard (L=1) and inboard (L=2) and X refers to the pressure designation (X=020, 030, 035, etc.) |
| PMIN | The minimum engine-face total pressure ratioed to free-stream total pressure |
| PMAX | The maximum engine-face total pressure ratioed to free-stream total pressure |
| PTI | Tunnel compressor inlet total pressure, psfa |
| PTA-1 | Primary tunnel total pressure, psfa |
| PTB-2 | Back-up tunnel total pressure, psfa |
| PSTCE1 | Exit control pressure for shock tube number one, psia |
| PSTCE2 | Exit control pressure for shock tube number two, psia |
| PSTCE3 | Exit control pressure for shock tube number three, psia |
| PSTCD1 | Driver control pressure for shock tube number one, psia |
| PSTCD2 | Driver control pressure for shock tube number two, psia |
| PSTCD3 | Driver control pressure for shock tube number three, psia |
| PSTCI1 | Interstage control pressure for shock tube number one, psia |

| Parameter | Description |
|---|---|
| PSTCI2 | Interstage control pressure for shock tube number two, psia |
| PSTCI3 | Interstage control pressure for shock tube number three, psia |
| PSTRD1 | Driver pressure for shock tube one, psia |
| PSTRD2 | Driver pressure for shock tube two, psia |
| PSTRD3 | Driver pressure for shock tube three, psia |
| PSTRI1 | Interstage pressure for shock tube one, psia |
| PSTRI2 | Interstage pressure for shock tube two, psia |
| PSTRI3 | Interstage pressure for shock tube three, psia |
| P1700 | MA total pressure ratioed to free-stream total pressure |
| P1701 | MA static pressure ratioed to free-stream total pressure |
| Q | Free-stream dynamic pressure |
| R2 | Engine-face total pressure recovery |
| RB$\phi$-I | Outboard and inboard second ramp angle, deg |
| RC$\phi$-I | Outboard and inboard third ramp angle, deg |
| REX10$^{-6}$ | Free-stream unit Reynolds number times ten to the minus six, ft$^{-1}$ |
| SCHED | Tunnel parameter |
| Sec | The second the data were taken, sec |
| SHOCK TUBE SELECT | Shock tube select code with the last two digits referring to the volumetric size, cu.ft. |
| S19 | Sideplate configuration |
| TAVG | Engine-face tip average static pressure ratioed to free-stream total pressure |
| Test | Test number |
| TI2 | Average engine-face turbulence factor |

| Parameter | Description |
|-----------|-------------|
| TPR | Tunnel pressure ratio |
| TT | Free-stream total temperature, °R |
| TTA-1 | Primary tunnel total temperature, °R |
| TTB-2 | Back-up tunnel total temperature, °R |
| U | Bypass door position |
| U1 | Bypass configuration |
| VANEI | Inboard flow throttling vane angle, deg |
| VANE$\phi$ | Outboard flow throttling vane angle, deg |
| WAE | East wall angle, deg |
| WAW | West wall angle, deg |
| WA/WT | Mass flow ratio of tunnel make-up air |
| W8-1 | Wing configuration |
| Wind-off | Part and point number of current wind-off |
| W2 | Engine-face weight flow, lb/sec |
| W2R | Engine-face weight flow corrected to standard conditions, lb/sec |
| W2R-FS | Full scale engine-face weight flow corrected to standard conditions, lb/sec |

*** STEADY STATE ***

PART POINT PROJECT TEST    DATE    DAY HR MIN SEC      ERCODE MODE    SETIDATE  WIND-OFF    AEDC PROPULSION WIND TUNNEL
512   3 P411-D2A  TF419  9/25/79  2691 11 391 59         0    0   J110/27/76 502/  -1            TRANSONIC 16T

M      PT   P      Q    REX10-6  TI  PTA-1  PTB-2  PCA-1  PCB-2  IIA-1  IIB-0  PTI.NCN  WAE  WAH  TPR  WA/WT  MB  SCHED
0.700 1465.7 1056.6 362.5  2.478  570 1465.7 1466.3 1066.1 1066.4  110  118 1166.6  0-0.00 0.00 1.256 0.0098 0.700  1

ALPHA  BETA  VANEO  VANEI  SHOCK TUBE SELECT     14C S19 L7 J27 E10 U1 M6 G34-2 W8-1 H16-1 N30-1 B5-1 C3
1.0  0.001  13.01  15.58        5015           RBG=1E7,RCG=1E2,1,AB1G=1.5,AB2G=180,HLG=2.733,HLI=2.226,C80-UES

      Q2    VFR2   MFR100  MFR2-FS   W2R    W2R-FS    T12    IDT    IDR    IDC    PD    PDP    IDA
OUTBOARD  0.9789 0.7498  0.7660  3.513  351.26  0.0077 0.0080 0.0393 0.0331 1.0007 1.2611 0.0748
INBOARD   0.9782 0.7341  0.75D5  3.441  344.15  0.0053 0.0901 0.0430 0.0238 1.0001 1.2613 0.0668

      M2S    M2    MA    NSP    TAVG    W2   CP1SS  CP2SS  CP3SS
OUTBOARD  0.497 0.510  0.596  0.8100  0.8195  2.273  0.736  0.768  0.737
INBOARD   0.475 0.486  0.000  0.8349  0.8321  2.225

*** RAMP PRESSURES ***                                          *** BLC PLENUM ***
         PL415  PL450  PL470  PL480  PL490                PL541  PL523
OUTBOARD 0.7785 0.8479 0.7738 0.8357 0.8408                0.7775 0.6050
INBOARD  0.8595 0.6407 0.7812 0.8526 0.8568                0.7753 0.8139

*** FLOWMETER PRESSURE ***                    *** COWL INTERNAL PRESSURES ***
         PL680  PL681  PL682  PL683          PL620  PL630  PL035  PL045
OUTBOARD 0.5677 0.5887 0.5868 0.5884         0.7893 0.7815 0.8153 0.6613
INBOARD  0.5846 0.5843 0.5841 0.5846         0.8111 0.7915 0.8330 0.8728

         PL690  PL691  PL692  PL693          PL702  PL703  PL704  PL700  PL701
OUTBOARD 0.5584 0.4671 0.4620 0.4677         0.9860 0.7987 0.7761 1.0010 0.7873
INBOARD  0.5846 0.4596 0.4670 0.4699         0.9646 0.8053 0.7913

*** CONTROL PARAMETERS ***

*** OUTBOARD PT2/PTO ***                                    *** INBOARD PT2/PTO ***
RING  22.5DEG  67.5  112.5  157.5  202.5  247.5  292.5  337.5   67.5  112.5  157.5  202.5  247.5  292.5  337.5
1     1.000   1.000  1.001  1.001  1.001  1.000  1.000  1.000  1.000  1.001  1.001  1.000  1.000  1.000
2     0.996   0.996  1.001  1.002  0.998  0.975  1.001  1.001  1.000  0.994  1.000  0.997  0.991  1.001
3     0.995   0.973  0.992  1.000  0.998  0.970  0.999  1.000  0.994  1.000  0.987  0.969  0.994
4     0.921   0.952  0.975  0.990  0.989  0.948  0.961  0.942  0.958  0.990  0.976  0.945  0.956
5     0.907   0.929  0.948  0.970  0.944  0.936  0.906  0.923  0.941  0.946  0.953  0.963  0.927  0.924

*** OUTBOARD RMS2 ***                                       *** INBOARD RMS2 ***
RING  22.5DEG  67.5  112.5  157.5  202.5  247.5  292.5  337.5   67.5  112.5  157.5  202.5  247.5  292.5  337.5
1     0.004   0.004  0.003  0.003  0.003  0.003  0.003  0.003  0.003  1.000 -1.000  0.003  0.003  0.003  1.000
3     0.009   0.012  0.007  0.004  0.005  0.015  0.009  0.005  0.000 -0.001  0.001  0.006  0.014  0.009
5     0.004   0.012  0.013  0.013  0.011  0.009  0.011  0.004  0.000  0.001  0.000  0.009  0.010  0.004

DATA SET:  IDT    IDA    IDC    IDL    IDR    IDC    IDL    IDR    TI2    PD    PDP    PD    R2    IDC12  IDC45  PMIN  PMAX
OUTBOARD  0.0080 0.0748 0.0331 0.5079 0.0393 0.0331 0.5079 0.0393 0.0077 1.0007 1.2611 1.0007 0.9789 0.0022 0.0331 0.9057 1.0016
INBOARD   0.0901 0.0668 0.0238 0.5203 0.0430 0.0238 0.5203 0.0430 0.0053 1.0001 1.2613 1.0001 0.9782 0.0045 0.0238 0.9129 1.0010

DATA SET 2
OUTBOARD  0.0981 0.0748 0.0967 0.8452 0.0393  0.0967  1.2402 0.9789  0.0486 0.9789 0.0331 0.9057 1.0016
INBOARD   0.0901 0.0668 0.0888 0.8193 0.0430  0.0888  1.2428 0.9782  0.0385 0.9129 0.0238 0.9129 1.0010

PSTCE1 PSTCE2 PSTCE3 PSTCD1 PSTCD2 PSTCD3 PSTCI1 PSTCI2 PSTCI3 PSTRD1 PSTRD2 PSTRD3 PSTRI1 PSTRI2 PSTRI3
7.82   7.31   20.95  0.00   0.00   0.00   0.00   0.00   0.00   15.02  15.05  14.40  14.40  32.80  14.55

187

*** STEADY STATE ***

| PART POINT | PROJECT | TEST | DATE | DAY HR MIN SEC | ERCODE | MODE | SET:DATE | WIND-OFF | AEDC PROPULSION WIND TUNNEL |
|---|---|---|---|---|---|---|---|---|---|
| 511 | 2 | P41-D2A | IF419 | 9/25/76 | 2691 11 58 15 | 0 | 0 | 3110/22/76 502/ -1 | TRANSONIC 16T |

| M | BI | B | D | REX10-6 | TT | PT | PTA-1 | PTB-2 | PCA-1 | PCB-2 | TIA-1 | ITB-Q | PTI | NCN | WAE | WAH | TPR | WA/WI | MB | SCHED |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 0.700 | 1471.1 | 1060.5 | 363.8 | 2.490 | 569 | 1471.1 | 1471.6 | 1070.1 | 1070.4 | 1C9 | 118 | 1171.9 | 0-0.0D | 0.00 | 1.255 | 0.0062 | 0.700 | 1 |

ALPHA BETA VANEO VANEI SHOCK TUBE SELECT
1.0 0.000 19.00 15.58 5017

14C S19 L7 J27 E1O U1 M6 G34-2 W8-1 M16-1 N30-1 B5-1 C3
RB5-1=7,BCC-1=21,AB1O=1=.5,AB2O-1=0,HLO=2.733,HL1=2.726,CEO.UWS

| | 42 | WFR2 | WFR100 | W2R | W2R-FS | T12 | IDT | IDR | IDC | IDL | PD | PDP | IDA |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.7787 | 0.7494 | 0.7657 | 3.511 | 351.10 | 0.0076 | 0.0973 | 0.0390 | 0.0330 | 0.5045 | 1.0006 | 1.2613 | 0.0744 |
| INBOARD | 0.7781 | 0.7334 | 0.7498 | 3.438 | 343.82 | 0.0053 | 0.0901 | 0.0430 | 0.0236 | 0.5204 | 1.0001 | 1.2613 | 0.067 |

| | M2S | M2 | MA | NSP | TAVG | W2 | CP1SS | CP2SS | CP3SS | |
|---|---|---|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.486 | 0.511 | 0.596 | 0.8102 | 0.6189 | 2.280 | 0.736 | 0.768 | 0.737 | |
| INBOARD | 0.474 | 0.487 | 0.000 | 0.8349 | 0.8318 | 2.232 | | | | |

*** RAMP PRESSURES ***                              *** BLC PLENUM ***

| | PL435 | PL450 | PL470 | PL480 | PL490 | PL020 | PL030 | PL035 | PL045 | PL543 | PL573 |
|---|---|---|---|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.7091 | 0.8478 | 0.7737 | 0.8361 | 0.8405 | 0.7889 | 0.7812 | 0.8149 | 0.6610 | 0.7773 | 0.8039 |
| INBOARD | 0.5098 | 0.8403 | 0.7806 | 0.8522 | 0.8566 | 0.8102 | 0.7908 | 0.8331 | 0.8729 | 0.7751 | 0.8156 |

*** FLOWMETER PRESSURE ***                           *** CONTROL PARAMETERS ***

| | PL680 | PL681 | PL682 | PL683 | PL690 | PL691 | PL692 | PL693 | PL702 | PL703 | PL704 | PL700 | PL701 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.5859 | 0.5853 | 0.5843 | 0.5856 | 0.4643 | 0.4619 | 0.4586 | 0.4643 | 0.9854 | 0.7983 | 0.7759 | 1.0006 | 0.7870 |
| INBOARD | 0.5819 | 0.5810 | 0.5812 | 0.5816 | 0.4656 | 0.4625 | 0.4634 | 0.4664 | 0.9640 | 0.6048 | 0.6048 | 0.7908 | |

*** OUTBOARD PT2/PTO ***                              *** INBOARD PT2/PTO ***

| RING | 22.5DEG | 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 | 22.5 | 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 1.000 | 1.000 | 1.001 | 1.001 | 1.001 | 1.001 | 1.000 | 1.000 | 1.001 | 1.000 | 1.001 | 1.001 | 1.000 | 1.000 | 1.000 | 1.000 |
| 2 | 1.000 | 0.995 | 1.000 | 1.001 | 1.000 | 0.996 | 1.000 | 1.001 | 1.000 | 1.000 | 1.001 | 1.001 | 1.000 | 0.997 | 0.990 | 1.001 |
| 3 | 0.995 | 0.973 | 0.991 | 1.000 | 1.000 | 0.969 | 0.975 | 1.000 | 0.992 | 0.979 | 0.994 | 1.000 | 1.000 | 0.987 | 0.969 | 0.994 |
| 4 | 0.991 | 0.952 | 0.974 | 0.991 | 0.989 | 0.969 | 0.936 | 0.992 | 0.961 | 0.942 | 0.958 | 0.991 | 0.988 | 0.977 | 0.946 | 0.994 |
| 5 | 0.967 | 0.929 | 0.948 | 0.971 | 0.944 | 0.936 | 0.906 | 0.923 | 0.913 | 0.941 | 0.946 | 0.952 | 0.962 | 0.928 | 0.924 |

*** OUTBOARD RMS2 ***                                 *** INBOARD RMS2 ***

| RING | 22.5DEG | 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 | 22.5 | 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 0.004 | 0.004 | 0.003 | 0.003 | 0.003 | 0.003 | 0.003 | 0.003 | 0.003 | 0.000 | 0.000 | 0.001 | 0.000 | 0.003 | 0.003 | 0.001 |
| 2 | 0.009 | 0.012 | 0.007 | 0.004 | 0.005 | 0.009 | 0.009 | 0.003 | 0.006 | 0.011 | -1.000 | 0.001 | 0.000 | 0.008 | 0.005 | 0.008 |
| 3 | 0.004 | 0.012 | 0.013 | 0.013 | 0.011 | 0.009 | 0.011 | 0.004 | 0.010 | 0.004 | 0.004 | 0.009 | 0.011 | 0.010 | 0.010 | 0.004 |

| DATA SET 1 | IDT | IDA | IDC | IDR | IDL | IDT | T12 | PD | PDP | T12 | PD | PMIN | PMAX |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.0973 | 0.0744 | 0.0330 | 0.0390 | 0.5045 | 0.0076 | 1.0006 | 1.2613 | IDC45 | IDC12 | R2 | PMIN | PMAX |
| INBOARD | 0.0901 | 0.0667 | 0.0236 | 0.0430 | 0.5204 | 0.0053 | 1.0001 | 1.2613 | 0.0330 | 0.0022 | 0.9787 | 0.9058 | 1.0010 |

DATA SET 2

| | | | | IDC | IDR | | IDL | | | IDC45 | IDC12 | R2 | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.0973 | 0.0744 | 0.0960 | 0.0390 | 0.8393 | 1.0128 | 1.2406 | 0.0236 | 0.0047 | 0.9781 | 0.9129 | 1.0010 |
| INBOARD | 0.0901 | 0.0667 | 0.0887 | 0.0430 | 0.6188 | 1.0110 | 1.2428 | 0.0960 | 0.0485 | 0.9787 | 0.9058 | 1.0010 |
| | | | | | | | | | 0.0887 | 0.0384 | 0.9781 | 0.9129 | 1.0010 |

| PSTCE1 | PSTCE2 | PSTCE3 | PSTCD1 | PSTCD2 | PSTCD3 | PSTC11 | PSTC12 | PSTC13 | PD | PDP | PSTRD1 | PSTRD2 | PSTRD3 | PSTR11 | PSTR12 | PSTR13 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 7.05 | 7.39 | 7.31 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.20 | 15.00 | 7.55 | 69.70 | 14.40 | 7.50 | 39.60 |

188

*** STEADY STATE ***

| PART | POINT | PROJECT | TEST | DATE | DAY HR MIN SEC | ERCODE | MODE | SETIDATE | WIND-OFF | AEDC PROPULSION WIND TUNNEL |
|---|---|---|---|---|---|---|---|---|---|---|
| 517 | 2 | 841902A | TF419 | 9/25/26 | 269 41 39 34 | 0 | 0 | 3110/22/76 516/ | -1 | TRANSONIC 16T |

| M | PT | P | Q | REX10-4 | TI | PTA-1 | PTB-2 | PCA-1 | PCB-2 | TTA-1 | ITB-2 | PTI,NCN | WAE | WAN | YPB | WA/WT | MB | SCHED |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 0.700 | 1467.4 | 1058.4 | 362.5 | 2.484 | 569 | 1467.4 | 1467.8 | 1067.9 | 1068.2 | 109 | 116 | 1170.1 | 0=0.00 | 0.00 | 1.254 | 0.0022 | 0.700 | 1 |

| ALPHA | BETA | VANEO | VANEI | SHOCK | TUBE | SELECT | 146 S19 L7 J27 E10 U1 M6 G34-2 W8-1 H16-1 N30-1 B5-1 C3 |
|---|---|---|---|---|---|---|---|
| 1.0 | 0.001 | 19.01 | 15.55 | | 5015 | | R82-187,RC0-182,1AB10-185,AB20-180,HLQR2,733,HLR2,726,CE0,uR5 |

| | R2 | WFR2 | MFR100 | W2R | W2R-FS | TI2 | IDT | IDR | IDC | PD | PDP | IDA |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.5792 | 0.7449 | 0.7608 | 3.487 | 346.72 | 0.0076 | 0.0053 | 0.0382 | 0.0323 | 1.0002 | 1.2620 | 0.0729 |
| INBOARD | 0.9278 | 0.7337 | 0.7503 | 3.459 | 343.93 | 0.0070 | 0.0905 | 0.0432 | 0.0240 | 1.0010 | 1.2604 | 0.0622 |

| | W2S | M2 | MA | NSP | TAVG | W2 | CP1SS | CP2SS | CP3SS |
|---|---|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.432 | 0.505 | 0.000 | 0.8116 | 0.8229 | 2.261 | 0.736 | 0.768 | 0.737 |
| INBOARD | 0.474 | 0.467 | 0.000 | 0.8340 | 0.8312 | 2.227 | | | |

*** RAMP PRESSURES ***

| | PL435 | PL450 | PL470 | PL480 | PL490 |
|---|---|---|---|---|---|
| OUTBOARD | 0.8015 | 0.8495 | 0.7774 | 0.8359 | 0.3430 |
| INBOARD | 0.8106 | 0.8408 | 0.7793 | 0.8511 | 0.8558 |

*** COWL INTERNAL PRESSURES ***

| | PL020 | PL030 | PL035 | PL045 |
|---|---|---|---|---|
| OUTBOARD | 0.7928 | 0.7871 | 0.8186 | 0.8624 |
| INBOARD | 0.8096 | 0.7896 | 0.8323 | 0.8723 |

*** BLC PLENUM ***

| PL541 | PL543 | PL523 |
|---|---|---|
| | 0.7772 | 0.8096 |
| | 0.7750 | 0.8128 |

*** FLOWMETER PRESSURE ***

| | PL680 | PL681 | PL682 | PL683 | PL690 | PL691 | PL692 | PL693 |
|---|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.5620 | 0.5627 | 0.5619 | 0.5623 | 0.4320 | 0.4338 | 0.4288 | 0.4300 |
| INBOARD | 0.5589 | 0.5596 | 0.5592 | 0.5592 | 0.4331 | 0.4313 | 0.4325 | 0.4345 |

*** CONTROL PARAMETERS ***

| | PL702 | PL703 | PL704 | PL700 | PL701 |
|---|---|---|---|---|---|
| | 0.9893 | 0.8030 | 0.7602 | 1.0001 | 0.7877 |
| | 0.9642 | 0.8041 | 0.7899 | | |

*** OUTBOARD PT2/PT5 ***

| RING | 22,5DEG | 67,5 | 112,5 | 157,5 | 202,5 | 247,5 | 292,5 | 337,5 |
|---|---|---|---|---|---|---|---|---|
| 1 | 1.000 | 1.001 | 1.000 | 1.001 | 1.001 | 1.000 | 1.000 | 1.000 |
| 2 | 0.999 | 0.995 | 0.999 | 1.000 | 0.995 | 0.996 | 0.999 | 1.000 |
| 3 | 0.976 | 0.976 | 0.993 | 0.999 | 1.000 | 0.994 | 0.986 | 0.994 |
| 4 | 0.955 | 0.922 | 0.955 | 0.988 | 0.989 | 0.977 | 0.968 | 0.957 |
| 5 | 0.932 | 0.058 | 0.932 | 0.969 | 0.945 | 0.937 | 0.962 | 0.923 |

*** INBOARD PT2/PT5 ***

| | 22,5 | 67,5 | 112,5 | 157,5 | 202,5 | 247,5 | 292,5 | 337,5 |
|---|---|---|---|---|---|---|---|---|
| | 1.001 | 1.000 | 1.000 | 1.001 | 1.000 | 1.000 | 1.000 | 1.000 |
| | 1.000 | 1.000 | 1.000 | 1.001 | 1.001 | 0.996 | 0.990 | 1.000 |
| | 0.999 | 0.979 | 0.994 | 1.000 | 1.000 | 0.986 | 0.968 | 0.994 |
| | 0.961 | 0.941 | 0.957 | 0.991 | 0.987 | 0.977 | 0.945 | 0.957 |
| | 0.923 | 0.912 | 0.940 | 0.946 | 0.951 | 0.962 | 0.927 | 0.923 |

*** OUTBOARD RMS2 ***

| RING | 22,5DEG | 67,5 | 112,5 | 157,5 | 202,5 | 247,5 | 292,5 | 337,5 |
|---|---|---|---|---|---|---|---|---|
| 1 | 0.004 | 0.003 | 0.003 | 0.003 | 0.003 | 0.003 | 0.003 | 0.003 |
| 2 | 0.009 | 0.012 | 0.007 | 0.004 | 0.003 | -1.000 | 0.008 | 0.003 |
| 3 | 0.024 | 0.012 | 0.012 | 0.015 | 0.005 | 0.011 | 0.001 | 0.015 |
| 4 | | | | 0.011 | 0.014 | 0.010 | 0.011 | 0.010 |

*** INBOARD RMS2 ***

| | 22,5 | 67,5 | 112,5 | 157,5 | 202,5 | 247,5 | 292,5 | 337,5 |
|---|---|---|---|---|---|---|---|---|
| | 0.008 | 0.006 | 0.000 | 0.000 | 0.003 | 0.003 | 0.003 | 0.003 |
| | 0.009 | 0.011 | 0.011 | 0.001 | 0.001 | 0.008 | 0.015 | 0.003 |
| | 0.012 | 0.010 | 0.012 | 0.009 | 0.012 | 0.011 | 0.010 | 0.012 |

| DATA SET 1 | IDT | IDA | IDC | IDR | IDA | IDL | TI2 | PDP | PD | R2 | IDC12 | IDC45 | PMIN | PMAX |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.0053 | 0.0729 | 0.0323 | 0.0382 | 0.0382 | 0.4939 | 0.0076 | 1.2620 | 1.0002 | 0.9792 | 0.0017 | 0.0323 | 0.9078 | 1.0011 |
| INBOARD | 0.0905 | 0.0672 | 0.0240 | 0.0432 | 0.0432 | 0.5229 | 0.0070 | 1.2604 | 1.0010 | 0.9778 | 0.0047 | 0.0240 | 0.9121 | 1.0006 |

| DATA SET 2 | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.0953 | 0.0729 | 0.0936 | 0.0936 | 0.0382 | 0.8194 | | 1.0121 | 1.2418 | 0.9792 | 0.0936 | 0.0476 | 0.9078 | 1.0011 |
| INBOARD | 0.0905 | 0.0672 | 0.0893 | 0.0893 | 0.0432 | 0.8236 | | 1.0120 | 1.2418 | 0.9778 | 0.0893 | 0.0388 | 0.9121 | 1.0006 |

| PSTCE1 | PSTCE2 | PSTCE3 | PSTCD1 | PSTCD2 | PSTCD3 | PSTCI1 | PSTCI2 | PSTCI3 | PSTRD1 | PSTRD2 | PSTRD3 | PSTRI1 | PSTRI2 | PSTRI3 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 7.87 | 7.52 | 7.20 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 14.25 | 85.05 | 14.50 | 14.15 | 47.50 | 14.15 |

189

END
DATE
FILMED

END
DATE
FILMED

4-79    4-79
DDC      DDC

*** STEADY STATE ***

PART POINT PROJECT TEST    DATE    DAY HR MIN SEC    ERCODE MODE    SET-DATE    WIND-OFF    AEDC PROPULSION WIND TUNNEL
51R    2 P411-D2A TF419 9/25/76 2691 51 41 14    0    0    3110/22/76 516/ -1              TRANSONIC 16T

M      PT     P      Q      REX10-6  TI  PTA-1  PTB-2  PCA-1  PCB-2 ITA-1 ITB-0 PTI NCN  WAH  HAH  TPR  HA/HT  MB  SCHED
0.700 1468.1 1758.3 363.1  2.484  569 1468.1 1468.5 1067.9 1068.2  110  117 1167.7  0-0.00  0.00 1.257 0.0062 0.700  1

ALPHA  BETA  VANEO VANEI SHOCK TUBE SELECT    14C S19 L7 J27 E:0 U1 M6 G34-2 W8-1 H16-1 N30-1 B5-1 C3
3.0  -0.000 19.01 15.55       5017             RBC-1=7.BCC-1=2.1.AB10=1-5.AB20=1s0.HL0=2.733.HL1=2.726.CE0.UHS

       R2     WFR2   MFR100   W2R    W2R-FS    TI2     IDT    IDC    IDR    IDL    PD     PDP     IDA
OUTBARD 0.9795 0.7430 0.7586  3.47R  347.83  0.0076  0.0962 0.0323 0.0387 0.4983 1.0004 1.2617 0.0732
INBOARD 0.9780 0.7318 0.7483  3.431  343.11  0.0067  0.0904 0.0238 0.0432 0.5225 1.0008 1.2606 0.0670

       M2S    M2     MA     NSP    TAVG    H2   CP1SS CP2SS CP3SS
OUTBARD 0.471 0.506  0.594  0.6115 0.8226  2.256 0.736 0.768 0.737
INBOARD 0.473 0.488  0.000  0.8346 0.8312  2.222

       *** RAMP PRESSURES ***                           *** COWL INTERNAL PRESSURES ***          *** BLC PLENUM ***

        PL435  PL450  PL470  PL480  PL490                 PL020  PL030  PL035  PL045              PL543  PL573
OUTBARD 0.8615 0.8495 0.7786 0.8389 0.8432               0.7929 0.7873 0.8185 0.8635            0.7771 0.8096
INBOARD 0.8695 0.8407 0.7795 0.6511 0.8560               0.8096 0.7898 0.8325 0.8723            0.7748 0.8127

       *** FLOWMETER PRESSURE ***                        *** CONTROL PARAMETERS ***

        PL680  PL681  PL682  PL683  PL690  PL691  PL692  PL693  PL702  PL703  PL704  PL700  PL701
OUTBARD 0.5533 0.5533 0.5532 0.5542 0.4198 0.4209 0.4167 0.4177 0.9896 0.8030 0.7802 1.0000 0.7870
INBOARD 0.5511 0.5560 0.5506 0.5504 0.4217 0.4192 0.4205 0.4228 0.9640 0.8045 0.7899

       *** OUTBOARD PT2/PT0 ***                          *** INBOARD PT2/PT0 ***

RING 22.5DEG  67.5  112.5  157.5  202.5  247.5  292.5  337.5   22.5   67.5  112.5  157.5  202.5  247.5  292.5  337.5
1    1.000   1.000 1.002  1.001  1.000  1.000  1.001  1.001   1.001  1.001  1.001  1.000  1.001  1.001  1.000  1.001
2    1.001   0.997 1.001  1.001  0.997  1.000  1.001  1.000   1.001  1.000  1.000  1.000  1.000  0.996  0.990  1.000
3    0.996   0.977 0.993  1.000  0.969  0.976  1.001  0.999   1.000  0.979  0.994  0.994  1.000  0.987  0.969  0.994
4    0.992   0.955 0.977  0.987  0.989  0.938  0.950  0.961   0.991  0.957  0.977  0.987  0.977  0.945  0.957
5    0.963   0.932 0.950  0.963  0.945  0.937  0.90R  0.924   0.912  0.941  0.946  0.951  0.962  0.927  0.924

       *** OUTBOARD RMS2 ***                             *** INBOARD RMS2 ***

RING 22.5DEG  67.5  112.5  157.5  202.5  247.5  292.5  337.5   22.5   67.5  112.5  157.5  202.5  247.5  292.5  337.5
1    0.004   0.003 0.003  0.000  0.003  0.004  9.999  0.003   0.003  0.000 -1.000  0.001  0.003  0.003  0.003  337.5
2    0.004   0.003 0.004  0.000  0.003  0.004  0.003  0.003   0.008  0.000  0.000  0.001  0.000  0.003  0.003  0.003
4    0.011   0.012 0.007  0.004  0.014  0.009  0.011  0.008   0.011  0.000  0.011  0.001  0.008  0.015  0.009
5    0.004   0.012 0.012  0.014  0.011  0.009  0.013  0.010  -1.000  0.010  0.009  0.012  0.011  0.010  0.012

DATA SET 1  IDT    IDA    IDC    IDR    IDL    TI2    PD     PDP    R2     IDC12  IDC45  PMIN   PMAX
OUTB-ARD 0.0962 0.0732 0.0323 0.0387 0.4983 0.0076 1.0004 1.2617 0.9795 0.0019 0.0323 0.9078 1.0021
INB2APD  0.0904 0.0670 0.0238 0.0432 0.5225 0.0067 1.0008 1.2606 0.9780 0.0044 0.0238 0.9125 1.0009

DATA SET 2
OUTB-ARD 0.0962 0.0732 0.0945 0.0387 0.8222         1.0124 1.2413 0.9795 0.0475 0.9078 1.0021
INBOARD  0.0934 0.0670 0.0892 0.0432 0.8226         1.0118 1.2420 0.9780 0.0385 0.9125 1.0009

PSTCE1 PSTCE2 PSTCE3 PSTCD1 PSTCD2 PSTCD3 PSTCI1 PSTCI2 PSTCI3 PSTRD1 PSTRD2 PSTRD3 PSTRI1 PSTRI2 PSTRI3
7.87   7.54   7.23   0.00   0.00   0.00   0.00   0.00   0.00   14.20  7.50  101.55 11.10  7.50   34.90

190

*** STEADY STATE ***

| PART POINT PROJECT TEST | DATE | DAY HR MIN SEC | ERCODE MODE | SET/DATE | WIND-OFF | AEDC PROPULSION WIND TUNNEL |
| 519  2  P41T-02A  TF419 | 9/25/76 | 269 | 51 | 51 | 33 | 0 | 0 | 3110/27/76 | 516/ -1 | TRANSONIC 16T |

| M | PT | P | Q | REX10-6 | TT | PTA-1 | PTB-2 | PCA-1 | PCR-2 | TTA-1 | TTB-0 | PTL | NCN | WAE | WAW | TPR | WA/WT | MB SCHED |
| 3.699 | 1448.1 | 1059.2 | 362.5 | 2.482 | 569 | 1468.2 | 1468.8 | 1048.7 | 1069.0 | 110 | 117 | 1170.3 | 0-0.00 | 0.00 | 1.254 | 0.0089 | 0.700 | 1 |

| ALPHA | BETA | VANEO | VANEI | SHOCK TUBE | SELECT | 140 S19 L7 J27 E10 U1 M6 G34-2 W8-1 H16-1 N30-1 B5-1 C3 |
| 1.0 | -5.200 | 19.21 | 15.55 | 5021 | | RB=-1z7,RCO=1#2,1,AB10=1z,2,AB20=50,HLG=2,733,HLI=2,726,G=0,UPS |

| | R2 | WFR2 | MFR100 | W2R | W2R-FS | IDT | II2 | IDR | IDI | IDC | IDL | PD | PDP | IDA |
| OUTBOARD | 0.9790 | 0.7444 | 0.7604 | 3.484 | 348.45 | 0.0076 | 0.0952 | 0.0363 | 0.0325 | 0.4955 | 1.0003 | 1.2619 | 0.0732 |
| INBOARD | 0.9778 | 0.7339 | 0.7505 | 3.440 | 343.95 | 0.0067 | 0.0909 | 0.0431 | 0.0241 | 0.5227 | 1.0008 | 1.2606 | 0.0921 |

| | M2S | M2 | MA | NSP | IAVG | W2 | CP1SS | CP2SS | CPSSS |
| OUTBOARD | 0.492 | 0.505 | 0.593 | 0.8118 | 0.8227 | 2.259 | 0.736 | 0.768 | 0.737 |
| INBOARD | 0.474 | 0.486 | 0.000 | 0.8349 | 0.8317 | 2.227 | | | |

*** RAMP PRESSURES.***

| | PL495 | PL452 | PL470 | PL480 | PL490 |
| OUTBOARD | 0.8011 | 0.8493 | 0.7771 | 0.8383 | 0.8430 |
| INBOARD | 0.6078 | 0.8405 | 0.7796 | 0.8514 | 0.8559 |

*** COWL INTERNAL PRESSURES ***

| | PL020 | PL030 | PL035 | PL045 |
| OUTBOARD | 0.7927 | 0.7871 | 0.8181 | 0.8637 |
| INBOARD | 0.8100 | 0.7897 | 0.8518 | 0.8718 |

*** BLC PLENUM ***

| | PL543 | PL521 |
| | 0.7774 | 0.8095 |
| | 0.7750 | 0.8522 |

*** FLOWMETER PRESSURE ***

| | PL681 | PL682 | PL683 | PL690 | PL691 |
| OUTBOARD | 0.5472 | 0.5468 | 0.5474 | 0.4096 | 0.4104 |
| INBOARD | 0.5448 | 0.5443 | 0.5440 | 0.4104 | 0.4085 |

*** CONTROL PARAMETERS ***

| | PL692 | PL693 | PL702 | PL703 | PL704 | PL700 | PL701 |
| OUTBOARD | 0.4057 | 0.4069 | 0.9890 | 0.8028 | 0.7603 | 1.0000 | 0.7883 |
| INBOARD | 0.4097 | 0.4119 | 0.9635 | 0.8045 | 0.7902 | | |

*** OUTBOARD PT2/PTO ***

| RING | 22.5DEG | 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 |
| 1 | 1.000 | 1.000 | 1.000 | 1.000 | 1.000 | 1.000 | 1.000 | 1.000 |
| 2 | 1.000 | 0.998 | 0.999 | 1.000 | 1.000 | 1.000 | 0.989 | 1.000 |
| 3 | 0.012 | 0.976 | 0.993 | 1.000 | 1.000 | 0.996 | 0.986 | 0.994 |
| 4 | 0.925 | 0.954 | 0.977 | 0.988 | 0.949 | 0.970 | 0.968 | 0.957 |
| 5 | 0.968 | 0.932 | 0.950 | 0.977 | 0.945 | 0.937 | 0.977 | 0.923 |

*** INBOARD PT2/PTO ***

| RING | 22.5 | 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 |
| 1 | 1.000 | 1.000 | 1.000 | 1.001 | 1.001 | 1.000 | 1.000 | 1.000 |
| 2 | 1.000 | 1.000 | 1.000 | 1.000 | 1.001 | 0.996 | 0.989 | 1.000 |
| 3 | 1.000 | 0.999 | 0.994 | 1.000 | 1.000 | 1.000 | 0.968 | 0.994 |
| 4 | 0.999 | 0.962 | 0.957 | 0.991 | 0.987 | 0.977 | 0.945 | 0.957 |
| 5 | 0.924 | 0.923 | 0.941 | 0.946 | 0.952 | 0.962 | 0.927 | 0.923 |

*** OUTBOARD RMS2 ***

| RING | 22.5DEG | 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 |
| 1 | 0.003 | 0.003 | 0.003 | 0.000 | 1.000 | 1.000 | 0.003 | 0.003 |
| 2 | 0.007 | 0.007 | 0.004 | 0.004 | 0.003 | 9.999 | 0.003 | 0.003 |
| 3 | 0.012 | 0.012 | 0.007 | 0.000 | 0.014 | 0.011 | 0.005 | 0.008 |
| 4 | 0.014 | 0.012 | 0.012 | 0.014 | 0.009 | 0.012 | 0.010 | 0.009 |

*** INBOARD RMS2 ***

| | 22.5 | 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 |
| | 0.003 | 0.003 | 0.000 | -1.000 | 0.003 | 0.003 | 0.003 | 0.003 |
| | 0.009 | 0.011 | 0.000 | 0.001 | 0.002 | 0.008 | 0.015 | 0.009 |
| | 0.013 | 0.012 | 0.010 | 0.009 | 0.012 | 0.011 | 0.010 | 0.012 |

| DATA SET 1 | IDT | IDL | IDR | IDC | IDA | II2 | IDL | PD | PDP | R2 | IDC12 | IDC45 | PMIN | PMAX |
| OUTBOARD | 0.0952 | 0.0732 | 0.0363 | 0.0325 | 0.0732 | 0.0076 | 0.4955 | 0.8223 | 1.0003 | 1.2619 | 0.9790 | 0.0016 | 0.0325 | 0.9074 | 1.0006 |
| INBOARD | 0.0909 | 0.0671 | 0.0431 | 0.0241 | 0.0671 | 0.0067 | 0.5227 | 0.6230 | 1.0008 | 1.2606 | 0.9778 | 0.0048 | 0.0241 | 0.9122 | 1.0010 |

| DATA SET 2 | | | | | | | | |
| OUTBOARD | 0.0952 | 0.0732 | 0.0363 | 0.0383 | 0.0940 | 1.0122 | 1.2416 | 0.9790 | 0.0428 | 0.9074 | 1.0006 |
| INBOARD | 0.0909 | 0.0671 | 0.0431 | 0.0892 | 1.0118 | 1.2420 | 0.9778 | 0.0388 | 0.9122 | 1.0010 |

| PSTCE1 | PSTCE2 | PSTCE3 | PSTCD1 | PSTCD2 | PSTCD3 | PSTC11 | PSTC12 | PSTC13 | PSTRD1 | PSTRD2 | PSTRD3 | PSTRI1 | PSTRI2 | PSTRI3 |
| 7.89 | 7.54 | 7.16 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 102.70 | 7.50 | 6.80 | 56.10 | 7.55 | 6.20 |

191

*** STEADY STATE ***

PART POINT PROJECT TEST DATE DAY HR MIN SEC   ERCODE MODE   SET DATE WIND-OFF   AEDC PROPULSION WIND TUNNEL
525   2 P41T-02A IF410 9/25/76 2591 61 591 32     0   0   310/27/76 524/   -1        TRANSONIC 16T

μ    PJ      P       Q    REV10-6  TI   PTA-1   PTR-2  PCA-1  PCB-2  IIA-1 IIB-0  PTI  NCN  NAE  NAH   IPR   WA/WT   MB  SCHED
0.701 1456.1 1057.8 363.5 2.407 569 1468.1 1468.7 1057.4 1067.7 109 114 1165.8 0-0.00 0.00 1.259 0.0100 0.700 1

ALPHA  BETA  VANEO  VANEI  SHOCK TUBE SELECT   14C S19 L7 J27 E10 U1 M6 G34-2 W8-1 M16-1 N30-1 B5-1 C3
3.0 0.000 19.31 15.53     5115     R85=187,BCC=1x2,1,AB10=1x.5,AB20=1x0,HLD=2,733,HL1x2,726,CEO,U15

|          | R2 | MFR2 | MFR100 | MFR2-FS | T12 | NDT | IDR | IDC | IDL | PD | PDP | IDA |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.9799 | 0.7443 | 0.7596 | 3.484 | 348.41 | 0.0075 | 0.0961 | 0.0389 | 0.0320 | 0.4994 | 1.0004 | 1.2617 | 0.0731 |
| INBOARD | 0.9781 | 0.7343 | 0.7292 | 3.443 | 344.39 | 0.0069 | 0.0907 | 0.0433 | 0.0239 | 0.5242 | 1.0010 | 1.2604 | 0.0671 |

|          | W2S | M2 | MA | NSP | TAVG | M2 | CP1SS | CP2SS | CP3SS |
|---|---|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.482 | 0.502 | 0.594 | 0.8111 | 0.8248 | 2.261 | 0.736 | 0.768 | 0.737 |
| INBOARD | 0.475 | 0.487 | 0.000 | 0.6335 | 0.6314 | 2.231 | | | |

*** RAMP PRESSURES ***

|          | PL435 | PL450 | PL470 | PL480 | PL490 |
|---|---|---|---|---|---|
| OUTBOARD | 0.8017 | 0.8501 | 0.7759 | 0.8398 | 0.8436 |
| INBOARD | 0.8096 | 0.8439 | 0.7797 | 0.8515 | 0.8562 |

*** COWL INTERNAL PRESSURES ***

| PL020 | PL030 | PL035 | PL045 |
|---|---|---|---|
| 0.7927 | 0.7874 | 0.8186 | 0.8637 |
| 0.8096 | 0.7899 | 0.8323 | 0.8727 |

*** BLC PLENUM ***

| PL543 | PL573 |
|---|---|
| 0.7772 | 0.8080 |
| 0.7746 | 0.8136 |

*** FLOWMETER PRESSURE ***

|          | PL681 | PL682 | PL683 | PL690 | PL691 | PL692 | PL693 |
|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.5614 | 0.5607 | 0.5607 | 0.4307 | 0.4310 | 0.4271 | 0.4277 |
| INBOARD | 0.5593 | 0.5539 | 0.5583 | 0.4318 | 0.4309 | 0.4332 |

*** CONTROL PARAMETERS ***

|          | PL702 | PL703 | PL704 | PL700 | PL701 |
|---|---|---|---|---|---|
| OUTBOARD | 0.9900 | 0.8030 | 0.7805 | 0.9997 | 0.7877 |
| INBOARD | 0.9648 | 0.8042 | 0.7899 | | |

*** OUTBOARD PT2/PTO ***

| RING | 22.5DEG | 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 |
|---|---|---|---|---|---|---|---|---|
| 1 | 1.001 | 1.001 | 1.001 | 1.000 | 1.001 | 1.001 | 1.001 | 1.001 |
| 2 | 1.002 | 0.998 | 1.002 | 1.002 | 0.998 | 1.001 | 1.001 | 1.001 |
| 3 | 0.996 | 0.977 | 0.994 | 0.999 | 0.970 | 0.993 | 0.999 | 0.989 |
| 4 | 0.992 | 0.955 | 0.978 | 0.987 | 0.949 | 0.980 | 0.962 | 0.987 |
| 5 | 0.989 | 0.933 | 0.951 | 0.966 | 0.938 | 0.945 | 0.923 | 0.952 |

*** INBOARD PT2/PTO ***

| RING | 22.5DEG | 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 |
|---|---|---|---|---|---|---|---|---|
| 1 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 |
| 2 | 1.002 | 0.999 | 0.999 | 1.002 | 1.000 | 1.001 | 1.002 | 1.001 |
| 3 | 0.996 | 0.977 | 0.994 | 0.999 | 0.979 | 0.993 | 0.999 | 0.989 |
| 4 | 0.992 | 0.957 | 0.991 | 0.987 | 0.962 | 0.977 | 0.941 | 0.952 |
| 5 | 0.989 | 0.941 | 0.946 | 0.952 | 0.923 | 0.924 | 0.908 | 0.923 |

*** OUTBOARD RMS2 ***

| RING | 22.5DEG | 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 |
|---|---|---|---|---|---|---|---|---|
| 1 | 0.001 | 0.003 | 0.003 | 0.000 | 0.003 | 0.003 | 0.003 | 0.003 |
| 2 | 0.004 | 0.003 | 0.003 | 0.000 | 0.003 | 0.003 | 0.003 | 0.003 |
| 3 | 0.009 | 0.012 | 0.007 | 0.004 | 0.005 | 0.014 | 0.018 | 0.008 |
| 4 | 0.024 | 0.012 | 0.012 | 0.015 | 0.011 | 0.009 | 0.012 | 0.010 |

*** INBOARD RMS2 ***

| RING | 22.5DEG | 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 |
|---|---|---|---|---|---|---|---|---|
| 1 | 0.001 | 0.003 | 0.003 | 0.001 | 0.003 | 0.003 | 0.003 | 0.003 |
| 2 | 0.004 | 0.003 | 0.003 | 0.000 | 0.001 | 0.003 | 0.003 | 0.003 |
| 3 | 0.012 | 0.007 | 0.004 | 0.005 | 0.011 | 0.009 | 0.015 | 0.009 |
| 4 | 0.012 | 0.012 | 0.015 | 0.011 | 0.012 | 0.009 | 0.010 | 0.012 |

DATA SET 1

|          | IDT | IDA | IDC | IDR | IDL | T12 | PD | PDP | R2 | IDC12 | IDC45 | PMIN | PMAX |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.0961 | 0.0731 | 0.0320 | 0.0389 | 0.4994 | 0.0075 | 1.0004 | 1.2617 | 0.9799 | 0.0016 | 0.0320 | 0.9082 | 1.0024 |
| INBOARD | 0.0907 | 0.0671 | 0.0239 | 0.0433 | 0.5242 | 0.0069 | 1.0010 | 1.2604 | 0.9781 | 0.0050 | 0.0239 | 0.9125 | 1.0012 |

DATA SET 2

|          | IDT | IDA | IDC | IDR | IDL | T12 | PD | PDP | R2 | IDC12 | IDC45 | PMIN | PMAX |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.0961 | 0.0731 | 0.0320 | 0.0389 | 0.8203 | 0.0075 | 1.0124 | 1.2412 | 0.9799 | 0.0946 | 0.0423 | 0.9282 | 1.0024 |
| INBOARD | 0.0907 | 0.0671 | 0.0239 | 0.0433 | 0.6244 | 0.0069 | 1.0120 | 1.2418 | 0.9781 | 0.0893 | 0.0387 | 0.9125 | 1.0012 |

| PSTCE1 | PSTCE2 | PSTCE3 | PSTCD1 | PSTCD2 | PSTCD3 | PSTC11 | PSTC12 | PSTC13 | PSTRD1 | PSTRD2 | PSTRD3 | PSTR11 | PSTR12 | PSTR13 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 7.87 | 7.84 | 7.12 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 14.25 | 13.20 | 14.15 | 14.15 | 60.25 | 14.15 |

192

*** STEADY STATE ***

PART POINT PROJECT TEST    DATE    DAY HR MIN SEC    ERCODE MODE    SET:DATE WIND-OFF    AEDC PROPULSION WIND TUNNEL
526   2 P41I-D2A IF419 9/25/76 269171 71 37      0    0  3110/27/76 524/ -1         TRANSONIC 16T

M      PI      P      Q    REX10-6   TT   PTA-1  PYB-2  PCA-1  PCB-2  IIA-1  IIB-0  PTI NCN  WAE MAN  TPR  MA/WT MB SCHED
0.730 1469.4 1350.2 363.4   2.499  569 1469.4 1470.0 1048.8 1069.1  109   114  1170.2  0-0.00 0.00 1.256 0.0078 0.700  1
       7.36

ALPHA  BETA  VANE0 VANEI SHOCK TUBE SELECT  140 S19 L7 J27 E10 U1 M6 G34-2 W8-1 M16-1 N3U-1 B5-1 C3
1.0   0.002  18.99 15.53         5217        RB0=1s7,RC0=1s2,1,AB10=1s5,AB20=1s0,HL0=2,733,HI=2,726,C80=0.UHS

              R2    MFR2   MFR100   M2R    M2R-FS    TI2    IDT    IDR    IDC    IDR    PD     PDP    IDA
OUTBOARD   0.9791 0.7444  0.7602   3.486  348.61  0.0076 0.0942 0.0382 0.0318 0.4923 1.0001 1.2621 0.0723
INBOARD    0.9778 0.7342  0.7508   3.443  344.28  0.0065 0.0907 0.0432 0.0241 0.5234 1.0008 1.2606 0.0673

              M2S    M2     MA     NSP    TAVG    W2    CP2SS  CP3SS
OUTBOARD   0.492  0.502  0.593  0.8113 0.8241  2.263  0.736  0.768 0.737
INBOARD    0.475  0.467  0.000  0.8352 0.8315  2.232

              *** RAMP PRESSURES ***                                     *** BLC PLENUM ***
              PL435  PL457  PL470  PL480  PL490                          PL543  PL573
OUTBOARD   0.8012 0.8434 0.7754 0.8392 0.8434                          0.7772 0.8078
INBOARD    0.8582 0.8436 0.7793 0.8510 0.8556                          0.7758 0.8122

              *** COWL INTERNAL PRESSURES ***                  *** CONTROL PARAMETERS ***
              PL023  PL030  PL035  PL045
OUTBOARD   0.7926 0.7071 0.8182 0.8632
INBOARD    0.8094 0.7893 0.8322 0.8723

              *** FLOWMETER PRESSURE ***
              PL690  PL691  PL692  PL693   PL702  PL703  PL704  PL700  PL701
OUTBOARD   0.4275 0.4282 0.4238 0.4250   0.8893 0.8026 0.8026 0.7800 0.9993 0.7875
INBOARD    0.4287 0.4266 0.4279 0.4303   0.9633 0.8045 0.8045 0.7896

              *** OUTBOARD PT2/PT0 ***                        *** INBOARD PT2/PT0 ***
RING 22.5DEG  67.5  112.5 157.5 202.5 247.5 292.5 337.5  22.5  67.5 112.5 157.5 202.5 247.5 292.5 337.5
1    1.000   1.000 1.000 1.000 1.000 1.000 1.000 1.001  1.000 1.000 1.000 1.000 1.000 1.000 1.000
2    0.999   0.999 0.999 0.999 0.995 0.999 1.001 1.000  1.000 1.001 1.001 0.996 0.989 1.000
3    0.997   0.994 0.999 0.999 1.001 0.969 0.977 0.999  0.992 0.994 1.001 1.001 1.000 0.986 0.968 0.994
4    0.992   0.977 0.988 0.989 0.949 0.938 0.962 0.950  0.957 0.941 0.987 0.972 0.945 0.957
5    0.968   0.950 0.966 0.944 0.937 0.908 0.924 0.922  0.940 0.912 0.991 0.947 0.952 0.962 0.927 0.922

              *** OUTBOARD RMS2 ***                           *** INBOARD RMS2 ***
RING 22.5DEG  67.5  112.5 157.5 202.5 247.5 292.5 337.5  22.5  67.5 112.5 157.5 202.5 247.5 292.5 337.5
1    0.003   0.003 0.000 0.000 0.003 9.999 1.000  0.003 0.000 0.000 0.003 0.003 0.003
2    0.003   0.007 0.004 0.004 0.003 0.009 0.011  0.008 0.000 0.001 0.000 0.008 0.015 0.003
3    0.012   0.012 0.014 0.011 0.012 0.012  0.012 0.010 0.009 0.004 0.010 0.012

DATA SET 1   IDT    IDA    IDC    IDR    IDL    PDP    TI2    IDT    R2    IDC12 IDC45 PMIN  PMAX
OUTBOARD   0.0942 0.0723 0.0318 0.0382 0.4923 1.2621 0.0076 0.0942 0.9791 0.0017 0.0318 0.9084 1.0006
INBOARD    0.0907 0.0673 0.0241 0.0432 0.5234 1.2606 0.0065 0.0907 0.9778 0.0049 0.0241 0.9120 1.0007

DATA SET 2
OUTBOARD   0.0942 0.0723 0.0930 0.0382 0.8154 1.2421 1.0119 0.9291 0.0930 0.9084 1.0006
INBOARD    0.0907 0.0673 0.0894 0.0432 0.8243 1.2419 1.0118 0.9778 0.0894 0.9120 1.0007

PSTCE1 PSTCE2 PSTCE3 PSTCD1 PSTCD2 PSTCD3 PSTC11 PSTC12 PSTC13 PSTRD1 PSTRD2 PSTRD3 PSTR11 PSTR12 PSTR13
7.90   7.64   7.14   0.00   0.00   0.00   0.00   0.00   0.00   14.20  7.55  132.70  14.00  7.40  70.75

193

*** STEADY STATE ***

PART POINT PROJECT TEST      DATE    DAY HR MIN SEC     ERCODE MODE    SETIDATE WIND-OFF    AEDC PROPULSION WIND TUNNEL
527  2 8417-02A  TE419  9/25/76  269 1 71 141 34      0    0  3110/27/76 524/  -1         TRANSONIC 16T

M       PI       P      Q    REX10=6  TT  PTA-1  PTB-2  PCA-1  PCB-2  ITA-1 ITB-0  PTI NCN  WAE  WAW  TPR  WA/WI  MB SCHED
0.700 1445.1 1056.7 362.0 2.480 559 1465.1 1465.1 1466.9 1066.2 1066.4 109  114 1167.6 0=0.00 0.00 1.255 0.0078 0.700  1

ALPHA  BETA  VANEO  VANEI  SHOCK TUBE SELECT   140 S19 L7 J27 E10 U1 M6 G34-2 W8-1 H16-1 N30-1 B5-1 C3
3.0 -0.000 19.00 15.53      5020              BBC-187,RGC-182,1,AB10-15,AB20-1=0,HLG=2,733,HLI=2,726,G=0,UBS

              R2     MFR2   MFR100   M2R    M2R-FS    T12    IDT    IDR    IDC    IDL    PD    PDP    IDA
OUTBOARD  0.9793 0.7443 0.7603  3.485  348.52  0.0075 0.0950 0.0384 0.0322 0.4949 1.0002 1.2619 0.0728
INBOARD   0.9727 0.7341 0.7508  3.442  344.16  0.0068 0.0907 0.0432 0.0239 0.5231 1.0009 1.2605 0.0672

          M2S    M2     MA     NSP    TAVG     M2    CP1SS  CP2SS  CP3SS
OUTBOARD 0.452 0.502 0.593 0.8112 0.0240  2.255  0.737  0.768  0.737
INBOARD  0.475 0.467 0.000 0.8342 0.8612  2.224

              *** RAMP PRESSURES ***                              *** COWL INTERNAL PRESSURES ***              *** BLC PLENUM ***

           PL635  PL450  PL470  PL490  PL490          PL620  PL630  PL635  PLD45                PL543  PL573
OUTBOARD  0.6612 0.8497 0.7751 0.8389 0.8435         0.7925 0.7867 0.8178 0.8632              0.7773 0.8076
INBOARD   0.8594 0.8407 0.7796 0.8514 0.8561         0.8099 0.7897 0.8321 0.8730              0.7754 0.8125

              *** FLOWMETER PRESSURE ***                          *** CONTROL PARAMETERS ***

           PL680  PL681  PL682  PL683  PL690  PL691  PL692  PL693    PL702  PL703  PL704  PL700  PL701
OUTBOARD  0.5588 0.5583 0.5561 0.5560 0.4273 0.4280 0.4234 0.4246  0.9893 0.8025 0.7798 0.9999 0.7863
INBOARD   0.5569 0.5564 0.5561 0.5560 0.4286 0.4267 0.4280 0.4299  0.9639 0.8041 0.7898

              *** OUTBOARD PT2/PT0 ***                            *** INBOARD PT2/PT0 ***

RING 22.5DEG  67.5  112.5  157.5  202.5  247.5  292.5  337.5   22.5   67.5  112.5  157.5  202.5  247.5  292.5  337.5
  1  1.001  1.000  1.000  1.000  1.001  1.000  1.001  1.001  1.000  1.000  1.001  1.000  1.000  1.000  1.000
  2  1.999  0.995  0.999  1.000  1.000  0.995  0.999  1.000  1.000  1.000  1.000  1.000  1.000  0.996  0.988  1.000
  3  0.996  0.976  0.993  1.000  0.969  0.976  0.992  0.999  0.999  0.994  0.991  0.994  0.986  0.966  0.994
  4  0.972  0.954  0.988  0.989  0.949  0.938  0.950  0.941  0.962  0.941  0.957  0.991  0.987  0.977  0.945  0.957
  5  0.968  0.931  0.950  0.968  0.937  0.908  0.924  0.912  0.922  0.946  0.951  0.962  0.927  0.923

              *** OUTBOARD RMS2 ***                              *** INBOARD RMS2 ***

RING 22.5DEG  67.5  112.5  157.5  202.5  247.5  292.5  337.5   22.5   67.5  112.5  157.5  202.5  247.5  292.5  337.5
  1  0.004  0.003  0.003  0.003  0.003  0.599  0.003  0.003  0.008  0.003  0.000  0.003  0.003  0.003  0.003
  2  0.009  0.012  0.007  0.004  0.014  0.009  0.011  0.005  0.011  0.000  0.001  0.003  0.008  0.015  0.009
  3  0.004  0.013  0.013  0.014  0.011  0.009  0.013  0.012  0.011  0.009  0.010  0.004  0.011  0.010  0.012

DATA SET 1  IDT    IDA    IDC    IDR    IDC    IDL    T12    IDL    PD    PDP    R2    IDC12  IDC45  PMIN   PMAX
OUTBOARD  0.0950 0.0728 0.0322 0.0239 0.0384 0.4949 0.0075 0.0384 1.0002 1.2519 0.9790 0.0018 0.0322 0.9077 1.0007
INBOARD   0.0907 0.0672 0.0239 0.0432 0.0432 0.5231 0.0068 1.2605 1.0009 1.2605 0.9777 0.0052 0.0239 0.9120 1.0007

DATA SET 2
OUTBOARD  0.0950 0.0728 0.0937 0.0892  1.0121 1.2418 1.9790 0.0937 0.0475 0.9077 1.0007
INBOARD   0.0907 0.0672 0.0892 0.0892  1.0118 1.2419 0.9777 0.0892 0.0388 0.9120 1.0007

PSTCE1 PSTCE2 PSTCE3  IDT    IDA    IDC    IDC  PSTCD1 PSTCD2 PSTCD3 PSTCI1 PSTCI2 PSTCI3 PSTRD1 PSTRD2 PSTRD3 PSTRI1 PSTRI2 PSTRI3
2.08  7.40  7.18  0.00  0.00  0.00  0.00  0.00  0.00  0.00  0.00  0.00  0.00 135.25  7.55  4.80 73.00  7.40  4.60

194

*** STEADY STATE ***

| PART PO:NT PROJECT TEST | DATE | DAY HR MIN SEC | ERCODE MODE | SET?DATE WIND-OFF | AEDC PROPULSION WIND TUNNEL |
|---|---|---|---|---|---|
| 544 1 P41I-02A TF419 | 9/27/76 | 271121 291 55 | 0 0 | 3110/22/76 5327 -2 | TRANSONIC 16T |

| M | ET | P | Q | REX10-6 | TT | P7A-1 | PTR-2 | PCA-1 | PCB-2 | TTA-1 | TTB-0 | PTI NCN | MAE | MAN | TPR | MA/MT | MB | SCHED |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 0.847 | 1693.6 | 1059.3 | 53.9 | 3.169 | 569 | 1693.6 | 1694.4 | 1072.5 | 1072.7 | 110 | 1343.1 | 0-0.00 | 1.261 | 0.0261 | 0.850 | 1 |

ALPHA BETA VANES VANEI SHOCK TUBE SELECT 140 S19 L7 J27 E10 U1 M6 G34-2 M8-1 M16-1 N30-1 B5-1 C3
3.0 -0.032 18.19 -6.33 5015 RBC=1=7,RCC=1=2,1.AB1C=1=5.AB2C=1=0.ML0=2.733.M1=2.726.C=0.uM5

| | R2 | MFR2 | MFR100 | W2R | W2R-FS | T12 | N2 | CP1SS | CP2SS | CP3SS |
|---|---|---|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.9796 | 0.6929 | 0.7062 | 3.469 | 346.90 | 0.0080 | 2.596 | 0.650 | 0.698 | 0.650 |
| INBOARD | 0.9805 | 0.6919 | 0.7057 | 3.466 | 346.62 | 0.0022 | 2.596 | | | |

| | M2S | M2 | MA | NSP | IAVG | N2 |
|---|---|---|---|---|---|---|
| OUTBOARD | 0.479 | 0.516 | 0.688 | 0.7965 | 0.8170 | 2.596 |
| INBOARD | 0.479 | 0.507 | 0.600 | 0.8018 | 0.8225 | 2.596 |

*** RAMP PRESSURES ***

| | PL435 | PL450 | PL470 | PL480 | PL490 |
|---|---|---|---|---|---|
| OUTBOARD | 0.7813 | 0.8361 | 0.7687 | 0.8336 | 0.8373 |
| INBOARD | 0.7867 | 0.6280 | 0.7654 | 0.8419 | 0.8484 |

*** FLOWMETER PRESSURE ***

| | PL681 | PL682 | PL683 | PL690 | PL691 | PL692 | PL693 |
|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.4955 | 0.4968 | 0.4973 | 0.3079 | 0.3094 | 0.2947 | 0.2969 |
| INBOARD | 0.4985 | 0.4959 | 0.4959 | 0.3517 | 0.3500 | 0.3028 | 0.3521 |

*** COWL INTERNAL PRESSURES ***

| | PL022 | PL070 | PL035 | PL045 | PL513 | PL523 |
|---|---|---|---|---|---|---|
| OUTBOARD | 0.7815 | 0.7788 | 0.8134 | 0.8614 | 0.7433 | 0.7965 |
| INBOARD | 0.7922 | 0.7759 | 0.8210 | 0.8669 | 0.7348 | 0.7991 |

*** BLC PLENUM ***

*** CONTROL PARAMETERS ***

| | PL702 | PL703 | PL704 | PL700 | PL701 |
|---|---|---|---|---|---|
| OUTBOARD | 0.6983 | 0.7951 | 0.7714 | 0.9996 | 0.7284 |
| INBOARD | 0.9914 | 0.7949 | 0.7764 | | |

| | IDT | IDC | IDR | IDL | PD | PDP | IDA |
|---|---|---|---|---|---|---|---|
| | 0.1003 | 0.0375 | 0.0377 | 0.5121 | 1.0010 | 1.2607 | 0.0773 |
| | 0.0951 | 0.0313 | 0.0436 | 0.5470 | 0.9996 | 1.2614 | 0.0743 |

*** OUTBOARD PT2/PTC ***

| RING 22.5 DEG | 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 | 22.5 | 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 |
| 2 | 1.000 | 1.000 | 1.002 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 0.986 | 0.999 |
| 3 | 0.990 | 0.990 | 0.992 | 1.001 | 0.663 | 0.994 | 0.977 | 0.995 | 1.001 | 1.001 | 1.000 | 0.996 | 0.957 | 0.961 |
| 4 | 0.995 | 1.000 | 0.985 | 0.944 | 0.933 | 0.946 | 0.937 | 0.957 | 0.996 | 0.997 | 0.959 | 0.974 | 0.935 | 0.928 |
| 5 | 0.975 | 0.969 | 0.941 | 0.936 | 0.904 | 0.923 | 0.908 | 0.939 | 0.940 | | | | | |

*** INBOARD PT2/PTC ***

*** OUTBOARD RMS2 ***

| RING 22.5 DEG | 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 | 22.5 | 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 0.004 | 0.003 | 0.003 | 0.003 | 0.004 | 0.001 | 0.001 | 0.001 | 0.001 | 0.001 | 0.001 | 0.001 | 0.001 | 0.001 |
| 2 | 0.006 | 0.011 | 0.004 | 0.005 | 0.010 | 0.004 | 0.003 | 0.001 | 0.001 | 0.002 | 0.001 | 0.001 | 0.004 | 0.001 |
| 3 | 0.006 | 0.012 | 0.012 | 0.011 | 0.009 | 0.011 | 0.004 | 0.003 | 0.003 | 0.003 | 0.003 | 0.003 | 0.004 | 0.004 |

*** INBOARD RMS2 ***

| DATA SET 1 | IDT | IDA | IDC | IDR | IDL | TI2 | PD | PDP | R2 | IDC12 | IDC45 | PMIN | PMAX |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.1003 | 0.0773 | 0.0375 | 0.0377 | 0.5121 | 0.0080 | 1.0010 | 1.2607 | 0.9796 | 0.0030 | 0.0375 | 0.9039 | 1.0022 |
| INBOARD | 0.095 | 0.0743 | 0.0313 | 0.0436 | 0.5470 | 0.0022 | 0.9996 | 1.2614 | 0.9805 | 0.0003 | 0.0313 | 0.9027 | 1.0009 |

| DATA SET 2 | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.1001 | 0.0773 | 0.0984 | 0.0327 | 0.5121 | 0.0080 | 1.0143 | 1.2382 | 0.9796 | 0.0984 | 0.0521 | 0.9039 | 1.0022 |
| INBOARD | 0.0951 | 0.0743 | 0.0948 | 0.0436 | 0.5470 | 0.0022 | 1.0120 | 1.2405 | 0.9805 | 0.0948 | 0.0465 | 0.9077 | 1.0009 |

| PSTCE1 | PSTCE2 | PSTCE3 | PSTCD1 | PSTCD2 | PSTCD3 | PSTC11 | PSTC12 | PSTC13 | PSTRD1 | PSTRD2 | PSTRD3 | PSTRI1 | PSTRI2 | PSTRI3 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 7.61 | 7.24 | 22.44 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 15.05 | 93.65 | 14.30 | 14.60 | 52.65 | 14.15 |

195

*** STEADY STATE ***

| PART POINT | PROJECT | TEST | DATE | DAY | HR | MIN | SEC | ENCODE | MODE | SETIDATE | WIND-OFF | AEDC PROPULSION WIND TUNNEL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 545 | 2 | P441-02A | YF419 | 9/22/76 | 271 | 21 | 41 | 26 | 0 | 0 | 3110/22/76 542/ -2 | TRANSONIC 16T |

| M | BT | B | Q | REX10-6 | IT | PIA-1 | PTB-2 | PCA-1 | PCB-2 | TIA-1 | TIB-0 | PTI-NCN | WAE | WAN | TPR | WA/HT | WB | SCHED |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 0.847 | 1664.4 | 1059.5 | 532.4 | 3.170 | 569 | 1694.4 | 1694.7 | 1072.7 | 1072.9 | 110 | 110 | 1343.0 | 0-0.00 | 0.00 | 1.262 | 0.0266 | 0.850 | 1 |

ALPHA BETA VANE0 VANE1 SHOCK TUBE SELECT 140 S19 L7 J27 E10 U1 M6 G34-2 W8-1 H16-1 N30-1 B5-1 C3
1.0 -0.004 18.49 14.30 5017 RBC-127,RCG-1s2,1,AB10-1s,5,AB20-1s0,HL0s2,733,HL1s2,726,C80,unS

| | M | MFR2 | MFR100 | W2R | W2R-FS | T12 | IDT | IDR | IDC | IDL | PD | PDP | IDA |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.0795 | 0.6920 | 0.7064 | 3.470 | 347.00 | 0.0079 | 0.1002 | 0.0379 | 0.0373 | 0.5131 | 1.0010 | 1.2607 | 0.0772 |
| INBOARD | 0.9865 | 0.6926 | 0.7064 | 3.470 | 346.99 | 0.0021 | 0.0953 | 0.0435 | 0.0314 | 0.5471 | 0.9996 | 1.2615 | 0.0742 |

| | R2 | MFR2 | M2S | M2 | MA | NSP | TAVG | W2 | CP2SS | CP2SS | CP3SS |
|---|---|---|---|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.479 | 0.515 | 0.667 | 0.7660 | 0.8476 | 2.598 | 2.600 | | 0.650 | 0.698 | 0.650 |
| INBOARD | 0.479 | 0.507 | 0.000 | 0.8021 | 0.8227 | 2.600 | | | | | |

*** RAMP PRESSURES ***

| | PL435 | PL450 | PL460 | PL470 | PL480 | PL490 |
|---|---|---|---|---|---|---|
| OUTBOARD | 0.7911 | 0.8343 | 0.7646 | 0.7689 | 0.8337 | 0.8374 |
| INBOARD | 0.7864 | 0.8265 | 0.7646 | 0.7646 | 0.8413 | 0.6476 |

*** CCWL INTERNAL PRESSURES ***

| | PL020 | PL030 | PL035 | PL045 |
|---|---|---|---|---|
| | 0.7812 | 0.7785 | 0.8130 | 0.6610 |
| | 0.7925 | 0.7752 | 0.8224 | 0.8671 |

*** BLC PLENUM ***

| | PL543 | PL573 |
|---|---|---|
| | 0.7428 | 0.7961 |
| | 0.7347 | 0.7983 |

*** FLOWMETER PRESSURE ***

| | PL680 | PL681 | PL682 | PL683 | PL690 | PL691 | PL692 | PL693 |
|---|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.4931 | 0.4929 | 0.4912 | 0.4939 | 0.2793 | 0.2792 | 0.2686 | 0.2747 |
| INBOARD | 0.4934 | 0.4944 | 0.4926 | 0.4925 | 0.2746 | 0.2733 | 0.2763 | 0.2792 |

*** CONTROL PARAMETERS ***

| | PL702 | PL703 | PL704 | PL700 | PL701 |
|---|---|---|---|---|---|
| | 0.9982 | 0.7946 | 0.7713 | 0.9991 | 0.7284 |
| | 0.9905 | 0.7945 | 0.7752 | | |

*** OUTBOARD PT2/PTO ***

| RING | 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 |
|---|---|---|---|---|---|---|---|
| 1 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.000 | 1.001 |
| 2 | 1.000 | 1.001 | 1.002 | 1.001 | 0.994 | 1.002 | 1.001 |
| 3 | 0.990 | 1.001 | 0.992 | 1.001 | 0.963 | 0.970 | 0.999 |
| 4 | 0.995 | 0.999 | 0.961 | 0.985 | 0.944 | 0.933 | 0.946 |
| 5 | 0.952 | 0.969 | 0.939 | 0.941 | 0.936 | 0.904 | 0.924 |

*** INBOARD PT2/PTC ***

| RING | 22.5 | 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 |
|---|---|---|---|---|---|---|---|---|
| 1 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 |
| 2 | 1.000 | 1.000 | 1.001 | 1.001 | 1.001 | 1.001 | 0.988 | 0.999 |
| 3 | 0.997 | 0.977 | 0.995 | 0.995 | 0.977 | 0.988 | 0.999 | |
| 4 | 0.933 | 0.937 | 0.958 | 0.986 | 0.998 | 0.996 | 0.957 | 0.961 |
| 5 | 0.904 | 0.908 | 0.940 | 0.940 | 0.959 | 0.974 | 0.935 | 0.928 |

*** OUTBOARD RMS2 ***

| RING | 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 |
|---|---|---|---|---|---|---|---|
| 1 | 0.004 | 0.004 | 0.004 | 0.003 | 0.004 | 0.004 | 0.004 |
| 2 | 0.004 | 0.004 | 0.009 | 0.005 | 0.015 | 0.004 | 0.001 |
| 3 | 0.000 | 0.011 | 0.009 | 0.013 | 0.010 | 0.001 | 0.001 |
| 4 | 0.004 | 0.012 | 0.013 | 0.011 | 0.009 | 0.011 | 0.004 |

*** INBOARD RMS2 ***

| RING | 22.5 | 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 |
|---|---|---|---|---|---|---|---|---|
| 1 | 0.004 | 0.001 | 0.001 | 0.001 | 0.001 | 0.001 | 0.001 | 0.001 |
| 2 | 0.004 | 0.004 | 0.001 | 0.002 | 0.001 | 0.004 | 0.004 | 0.001 |
| 3 | -0.000 | 0.013 | -0.001 | 0.002 | 0.002 | 0.004 | 0.004 | 0.001 |
| 4 | 0.004 | 0.011 | 0.013 | 0.003 | 0.003 | 0.003 | 0.004 | 0.004 |

DATA SET 1

| | IDT | IDA | IDT | IDC | IDR | IDL | T12 | IDL | PDP | PD | R2 | IDC45 | IDC12 | PMIN | PMAX |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.1002 | 0.0772 | 0.0373 | 0.0373 | 0.0379 | 0.5131 | 0.0079 | 0.5131 | 1.2607 | 1.0010 | 0.9796 | 0.0373 | 0.0030 | 0.9040 | 1.0022 |
| INBOARD | 0.0953 | 0.0742 | 0.0953 | 0.0314 | 0.0435 | 0.5471 | 0.0021 | 0.5471 | 1.2615 | 0.9998 | 0.9805 | 0.0314 | 0.0002 | 0.9022 | 1.0011 |

DATA SET 2

| | | | | | | | | | | | | IDC45 | IDC12 | PMIN | PMAX |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.1002 | 0.0772 | 0.0983 | 0.0329 | 0.0379 | 0.6755 | 0.0079 | | 1.2607 | 1.0010 | 0.9796 | 0.0983 | 0.0520 | 0.9040 | 1.0022 |
| INBOARD | 0.0953 | 0.0742 | 0.0947 | 0.0435 | 0.0435 | 0.8838 | 0.0021 | | 1.2615 | 1.0019 | 0.9805 | 0.0947 | 0.0464 | 0.9077 | 1.0011 |

| PSTCE1 | PSTCE2 | PSTCE3 | PSTCD1 | PSTCD2 | PSTCD3 | PSTCI1 | PSTCI2 | PSTCI3 | PSTRD1 | PSTRD2 | PSTRD3 | PSTRI1 | PSTRI2 | PSTRI3 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 7.82 | 7.38 | 7.37 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 14.55 | 7.55 | 14.55 | 113.35 | 7.70 | 61.30 |

196

*** STEADY STATE ***

PART POINT PROJECT TEST    DATE   DAY HR MIN SEC      ERCODE MODE      SET DATE WIND-OFF    AEDC PROPULSION WIND TUNNEL
50A   3 P41T-02A  TF419  9/27/76  271 21  50 52        0       0      3 10/27/76  542/  -2         TRANSONIC  16T

M    PT    P    Q   REX10-6  TT  PTA-1  PTB-2  PCA-1  PCB-2  TTA-1  TTB-2  PTI NCN  MAE  MAH  TPR  MA/WT  M8 SCHED
0.847 1093.7 1059.5 531.9  3.168  569 1693.7 1694.0 1072.7 1072.8  110   110 1343.1  0-0.00  1.261 0.0262 0.650  1

ALPHA  BETA  VANEO  VANEI  SHOCK TUBE SELECT     14C S19 L7 J27 E10 U1 M6 G34-2 W8-1 M16-1 N30-1 B5-1 C3
3.0  -0.002  18.39 14.29         5320                 RBQ-1=7,BCC-1=2,1,AB10-1=5,AB20-1=9,HLG-2,733,HL1=2,726,C10-UES

         R2     MFR2    MFR100   W2R    W2R-FS   T12    IDT    IDC    IDR    IDL    PDP     IDA
OUTBOARD 0.0795 0.5936  0.7081  3.476  347.81  0.0080 0.0089 0.0378 0.0954 0.5131 1.2606  0.0773
INBOARD  0.9935 0.5933  0.7971  3.473  347.31  0.0021 0.0954 0.0315 0.0437 0.5488 1.2614  0.0745

         M2S    M2      MA     MSP    TAVG    W2   CP1SS  CP2SS  CP3SS
OUTBOARD 0.481  0.515  0.687  0.7974 0.8172  2.603 0.650  0.698  0.650
INBOARD  0.460  0.509  0.000  0.8020 0.8218  2.602

         *** RAMP PRESSURES ***          *** COWL INTERNAL PRESSURES ***          *** BLC PLENUM ***
         PL435   PL452  PL470   PL480  PL490     PL02Q  PL03Q  PL035  PL045         PL543   PL573
OUTBOARD 0.7P13 0.8380 0.7693  0.8342 0.8378    0.7814 0.7784 0.8128 0.8610        0.7426  0.7963
INBOARD  0.7865 0.8280 0.7647  0.8415 0.8477    0.7914 0.7748 0.8226 0.8670        0.7345  0.7972

                    *** FLOWMETER PRESSURE ***               *** CONTROL PARAMETERS ***
         PL680   PL681  PL682   PL683  PL690  PL691  PL692  PL693    PL702   PL703  PL704  PL1700  PL1701
OUTBOARD 0.4941 0.4937 0.4936  0.4945 0.2810 0.2810 0.2723 0.2766   0.9967  0.7948 0.7711 0.9991  0.7289
INBOARD  0.4645 0.4952 0.4927  0.4928 0.2772 0.2760 0.2780 0.2814   0.9907  0.7945 0.7752

         *** OUTBOARD PT2/PTQ ***                             *** INBOARD PT2/PTQ ***
RING 22.5DEG  67.5  112.5  157.5  202.5  247.5  292.5  337.5    22.5  67.5  112.5  157.5  202.5  247.5  292.5  337.5
1    1.001   1.001  1.001  1.001  1.001  1.001  1.001  1.001   1.001 1.001 1.001  1.001  1.001  1.001  1.001  1.001
2    1.000   1.000  1.001  1.001  0.994  1.001  1.000  1.001   1.001 1.001 1.001  1.001  1.001  1.001  1.001  1.000
3    0.999   0.991  1.001  1.001  0.992  1.000  0.998  0.995   0.998 0.977 1.001  1.001  1.001  1.000  0.988  1.000
4    0.995   0.973  0.999  0.962  0.965  0.944  0.957  0.937   0.957 0.937 0.957  0.987  0.998  0.996  0.957  0.962
5    0.975   0.952  0.969  0.939  0.941  0.936  0.904  0.919   0.919 0.907 0.940  0.959  0.974  0.935  0.928

         *** OUTBOARD RMS2 ***                                *** INBOARD RMS2 ***
RING 22.5DEG  67.5  112.5  157.5  202.5  247.5  292.5  337.5    22.5  67.5  112.5  157.5  202.5  247.5  292.5  337.5
1    0.004   0.304  0.003  0.003  0.003  0.004  0.004  0.004   0.001 0.001 0.001  0.001  0.001  0.001  0.001  0.001
2   -1.000   0.011  0.004  0.009  0.005  0.015  0.010  0.004   0.010 0.001 0.002  0.001  0.001  0.001  0.004  0.001
3    0.004   0.012  0.013  0.013  0.009  0.011  0.013  0.004   0.003 0.004 0.003  0.003  0.003  0.003  0.004  0.004

DATA SET 1  IDT    IDA    IDC    IDR    IDL    TI2    PD     PDP    R2      IDC12  IDC45  PMIN   PMAX
OUTBOARD 0.0069 0.0773 0.0374 0.0378 0.5131 0.0080 1.0010 1.2606 0.9795  0.0030 0.0374 0.9038 1.0008
INBOARD  0.0954 0.0745 0.0315 0.0437 0.5488 0.0021 0.9996 1.2614 0.9805  0.0001 0.0315 0.9075 1.0010
DATA SET 2
OUTBOARD 0.0989 0.0773 0.0983 0.0378 0.8749          1.0143 1.2382 0.9783 0.0983 0.0521 0.9038 1.0008
INBOARD  0.0954 0.0745 0.0951 0.0437 0.8869          1.0120 1.2404 0.9805 0.0951 0.0467 0.9075 1.0010

PSTCE1 PSTCE2 PSTCE3 PSTCD1 PSTCD2 PSTCD3 PSTC11 PSTC12 PSTC13 PSTRD1 PSTRD2 PSTRD3 PSTRI1 PSTRI2 PSTRI3
7.34   7.39   7.37   0.00   0.00   0.00   0.00   0.00   0.00   120.60  7.85   0.00   63.90  7.75   6.40

197

*** STEADY STATE ***

| PART | POINT | PROJECT | TEST | DATE | DAY HR MIN SEC | ERCODE | MODE | SETIDATE | WIND-OFF | AEDC PROPULSION WIND TUNNEL |
|---|---|---|---|---|---|---|---|---|---|---|
| 550 | 2 | 641-H2A | IF419 | 9/27/76 | 271:231:11 24 | 0 | 0 | 3110/27/76 548/ | -1 | TRANSONIC 16T |

| M | BT | B | Q | REX10-6 | TT | PT4-1 | PTB-2 | PCA-1 | PCB-2 | TT/=1 | TT8-0 | PT1 NCN | NAE NAH | TPR | NA/HT | MB | SCHED |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 0.899 | 1786.6 | 1058.7 | 598.9 | 3.429 | 569 | 1788.6 | 1789.4 | 1073.2 | 1073.4 | 110 | 810 | 1445.1 | 0=0.00 0.00 | 1.238 | 0.0391 | 0.900 | 1 |

| ALPHA | SETA | VANE0 | VANE1 | SHOCK TUBE SELECT | 140 S19 L7 J27 E10 U1 M6 G34-2 H8-1 H16-1 N30-1 B5-1 C3 |
|---|---|---|---|---|---|
| 1.0 | 0.0018 | 17.00 | 12.99 | 5015 | RB2=1B7,RCG=1B2.1,AB10=1B5,AB20=1B0,HL0=2.733,HL1=2.726,C50=uBS |

|  | R2 | MFR2 | MFR100 | W2R | W2R-FS | IDT | IDR | IDC | IDL | PD | PDP | IDA |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.9809 | 0.6686 | 0.7021 | 3.491 | 349.14 | 0.0078 | 0.0956 | 0.0371 | 0.4857 | 1.0000 | 1.2624 | 0.0742 |
| INBOARD | 0.9822 | 0.5990 | 0.7117 | 3.539 | 353.92 | 0.0023 | 0.0929 | 0.0333 | 0.5315 | 0.9991 | 1.2622 | 0.0736 |

|  | M25 | M2 | MA | NSP | IAVG | W2 | CP1SS | CP2SS | CP3SS |
|---|---|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.463 | 0.498 | 0.711 | 0.6067 | 0.6277 | 2.762 | 0.620 | 0.676 | 0.621 |
| INBOARD | 0.491 | 0.502 | 0.500 | 0.5006 | 0.6269 | 2.804 | | | |

*** RAMP PRESSURES ***

|  | PL435 | PL452 | PL470 | PL482 | PL492 |
|---|---|---|---|---|---|
| OUTBOARD | 0.7239 | 0.8420 | 0.7807 | 0.8419 | 0.8443 |
| INBOARD | 0.7262 | 0.8359 | 0.7701 | 0.8448 | 0.8512 |

*** COWL INTERNAL PRESSURES ***

|  | PL020 | PL030 | PL035 | PL045 |
|---|---|---|---|---|
| OUTBOARD | 0.7941 | 0.7900 | 0.6211 | 0.8751 |
| INBOARD | 0.7952 | 0.7804 | 0.8268 | 0.8715 |

*** BLC PLENUM ***

|  | PL543 | PL573 |
|---|---|---|
| OUTBOARD | 0.7384 | 0.8017 |
| INBOARD | 0.7266 | 0.7999 |

*** FLOWMETER PRESSURE ***

|  | PL680 | PL681 | PL682 | PL683 | PL690 | PL691 | PL692 | PL693 |
|---|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.7847 | 0.7844 | 0.7837 | 0.7847 | 0.7070 | 0.7077 | 0.7062 | 0.7074 |
| INBOARD | 0.7862 | 0.7856 | 0.7856 | 0.7862 | 0.7073 | 0.7056 | 0.7052 | 0.7064 |

*** CONTROL PARAMETERS ***

|  | PL702 | PL703 | PL704 | PL702 | PL701 |
|---|---|---|---|---|---|
| OUTBOARD | 0.9983 | 0.8053 | 0.7624 | 0.9987 | 0.7128 |
| INBOARD | 0.9989 | 0.7996 | 0.7804 | | |

*** OUTBOARD PT2/PTO ***

| RING | 22.5DEG | 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 |
|---|---|---|---|---|---|---|---|---|
| 1 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 |
| 2 | 1.000 | 1.000 | 1.001 | 1.001 | 1.000 | 1.001 | 0.999 | 1.001 |
| 3 | 0.995 | 0.995 | 1.001 | 0.988 | 0.994 | 0.964 | 0.969 | 1.001 |
| 4 | 0.996 | 0.981 | 1.000 | 0.984 | 0.961 | 0.946 | 0.935 | 0.959 |
| 5 | 0.977 | 0.958 | 0.972 | 0.948 | 0.943 | 0.939 | 0.908 | 0.926 |

*** INBOARD PT2/PTO ***

| RING | 22.5 | 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 |
|---|---|---|---|---|---|---|---|---|
| 1 | 1.001 | 1.000 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 |
| 2 | 1.001 | 1.001 | 1.001 | 1.001 | 1.000 | 1.000 | 0.999 | 1.000 |
| 3 | 0.994 | 0.977 | 0.996 | 0.977 | 0.986 | 1.001 | 1.001 | 0.992 |
| 4 | 0.984 | 0.939 | 0.985 | 0.959 | 0.948 | 0.999 | 0.969 | 0.973 |
| 5 | 0.961 | 0.910 | 0.942 | 0.940 | 0.926 | 0.980 | 0.948 | 0.930 |

*** OUTBOARD RMS2 ***

| RING | 22.5DEG | 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 |
|---|---|---|---|---|---|---|---|---|
| 1 | 0.003 | 0.003 | 0.004 | 0.004 | 0.004 | 0.004 | 0.001 | 0.001 |
| 2 | 0.006 | 0.006 | 0.003 | 0.005 | 0.004 | 0.008 | 0.001 | 0.001 |
| 3 | 0.011 | 0.011 | 0.004 | 0.010 | 0.015 | 0.013 | 0.001 | 0.001 |
| 5 | 0.005 | 0.011 | 0.012 | 0.209 | 0.011 | 0.012 | -1.000 | 0.003 |

*** INBOARD RMS2 ***

| RING | 22.5 | 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 |
|---|---|---|---|---|---|---|---|---|
| 1 | 0.004 | 0.001 | 0.001 | 0.001 | 0.001 | 0.001 | 0.004 | 0.001 |
| 2 | 0.003 | 0.000 | 0.002 | 0.001 | 0.001 | 0.001 | 0.004 | 0.001 |
| 3 | -1.000 | 0.001 | 0.003 | 0.003 | 0.001 | 0.003 | 0.003 | 0.004 |

DATA SET 1

|  | IDT | IDA | IDR | IDC | IDL | IDP | TI2 | PD | PDP | R2 | IDC12 | IDC45 | PMIN | PMAX |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.0356 | 0.0742 | 0.0350 | 0.0371 | 0.4857 | 0.0078 | 0.0078 | 1.0000 | 1.2624 | 0.9808 | 0.0034 | 0.0371 | 0.9060 | 1.0018 |
| INBOARD | 0.0329 | 0.0735 | 0.0329 | 0.0333 | 0.5315 | 0.0023 | 0.0023 | 0.9991 | 1.2622 | 0.9822 | 0.0004 | 0.0333 | 0.9099 | 1.0011 |

DATA SET 2

|  | IDT | IDA | IDR | IDC | IDL | IDP | TI2 | PD | PDP | R2 | IDC12 | IDC45 | PMIN | PMAX |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.0356 | 0.0742 | 0.0350 | 0.0350 | 0.0350 | 0.8304 | 1.0126 | 1.2410 | 0.9808 | 0.0940 | 0.0506 | 0.9080 | 1.0018 | |
| INBOARD | 0.0329 | 0.0736 | 0.0329 | 0.0414 | 0.0414 | 0.8563 | 1.0110 | 1.2421 | 0.9822 | 0.0925 | 0.0480 | 0.9099 | 1.0011 | |

| PSTCE1 | PSTCE2 | PSTCE3 | PSTCD1 | PSTCD2 | PSTCD3 | PSTC11 | PSTC12 | PSTC13 | PSTRD1 | PSTRD2 | PSTRD3 | PSTR11 | PSTR12 | PSTR13 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1023/75 | 7.34 | 7.50 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 14.15 | 85.75 | 14.25 | 14.05 | 45.50 | 14.05 |

*** STEADY STATE ***

| ERCODE MODE | SETIDATE | WIND-OFF | AEDC PROPULSION WIND TUNNEL |
| --- | --- | --- | --- |
| 0      0 | 3110/27/76 548/  -1 | | TRANSONIC 16T |

PART POINT PROJECT TEST DATE DAY HR MIN SEC
551   7 261T=22A  TF419  9/27/76  271:21 221 32

| M | DT | P | O | REX10-6 | TT | PTA-1 | PTB-2 | PCA-1 | PCB-2 | TTA-1 | TTB-0 | PTI.NCN | WAE | WW | TPR | WA/WT | WB | SCHED |
| --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- |
| 0.900 | 1787.4 | 1057.3 | 598.9 | 3.426 | 570 | 1787.4 | 1768.5 | 1071.8 | 1072.3 | 110 | 110 | 1445.7 | 0=0.00 | 0.00 | 1.236 | 0.0386 | 0.900 | 1 |

ALPHA BETA VANEO VANEI SHOCK TUBE SELECT   140 S19 L7 J27 E10 U1 M6 G34=2 W8=1 H16=1 N30=1 B5=1 C3
1.0  10.036  17.00  12.97       5017       RB2=187,RC0=1a2,,A810=1a5,A820=1a0,HL0a2.733,HL1a2.724,G=0.uE5

| | W2 | WFR2 | MFR100 | W2R | W2R=FS | T12 | IDT | IDR | IDT | IDC | IDL | PD | PDP | IDA |
| --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- |
| OUTBOARD | 0.9808 | 0.6855 | 0.7021 | 3.492 | 349.17 | 0.0078 | 0.0954 | 0.0350 | 0.0370 | 0.4858 | 1.0000 | 1.2624 | 0.0741 |
| INBOARD | 0.9921 | 0.6994 | 0.7121 | 3.542 | 354.16 | 0.0023 | 0.0927 | 0.0413 | 0.0334 | 0.5307 | 0.9991 | 1.2623 | 0.0736 |

| | M2S | M2 | MA | NSP | TAVG | N2 | CP1SS | CP2SS | CP3SS | | |
| --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- |
| OUTBOARD | 3.443 | 0.499 | 0.712 | 0.8044 | 0.8274 | 2.760 | 0.620 | 0.677 | 0.620 | | |
| INBOARD | 0.492 | 0.502 | 0.000 | 0.8905 | 0.8267 | 2.803 | | | | | |

*** RAMP PRESSURES ***                              *** BLC PLENUM ***

| | PL435 | PL45] | PL470 | PL480 | PL490 | PL020 | PL030 | PL035 | PL045 | PL543 | PL523 |
| --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- |
| OUTBOARD | 0.7827 | 0.6425 | 0.7809 | 0.8422 | 0.8448 | 0.7942 | 0.7900 | 0.8213 | 0.8753 | 0.7383 | 0.8018 |
| INBOARD | 0.7862 | 0.6312 | 0.7700 | 0.8448 | 0.8514 | 0.7953 | 0.7803 | 0.8268 | 0.8713 | 6.7264 | 0.6004 |

*** FLOWMETER PRESSURE ***                          *** COWL INTERNAL PRESSURES ***                     *** CONTROL PARAMETERS ***

| | PL680 | PL685 | PL682 | PL683 | PL690 | PL691 | PL692 | PL693 | PL702 | PL703 | PL704 | PL700 | PL701 |
| --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- |
| OUTBOARD | 0.7444 | 0.7847 | 0.7847 | 0.7844 | 0.7070 | 0.7073 | 0.7055 | 0.7071 | 0.9992 | 0.8038 | 0.7826 | 0.9992 | 0.7123 |
| INBOARD | 0.7959 | 0.7855 | 0.7854 | 0.7859 | 0.7067 | 0.7053 | 0.7048 | 0.7060 | 0.9989 | 0.7996 | 0.7803 | | |

*** OUTBOARD PT2/PTC ***                            *** INBOARD PT2/PTC ***

| RING | 22.5DEG | 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 | 22.5 | 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 |
| --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- |
| 1 | 1.001 | 1.001 | 1.001 | 1.001 | 1.000 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 |
| 2 | 1.000 | 1.001 | 1.001 | 1.001 | 1.000 | 0.994 | 1.001 | 1.001 | 1.000 | 1.000 | 1.001 | 1.000 | 1.000 | 1.001 | 1.001 | 1.000 |
| 3 | 1.000 | 0.995 | 1.001 | 1.002 | 0.988 | 0.964 | 0.985 | 1.001 | 0.998 | 0.995 | 0.995 | 0.997 | 0.987 | 1.001 | 0.992 | 1.001 |
| 4 | 0.996 | 0.984 | 1.000 | 0.960 | 0.984 | 0.946 | 0.935 | 0.908 | 0.959 | 0.940 | 0.959 | 0.948 | 0.957 | 0.985 | 0.999 | 0.973 |
| 5 | 0.977 | 0.957 | 0.973 | 0.948 | 0.943 | 0.939 | 0.908 | 0.902 | 0.942 | 0.910 | 0.942 | 0.940 | 0.926 | 0.921 | 0.980 | 0.930 |

*** OUTBOARD RMS2 ***                               *** INBOARD RMS2 ***

| RING | 22.5DEG | 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 | 22.5 | 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 |
| --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- |
| 1 | 0.004 | 0.003 | 0.003 | 0.004 | 0.004 | 0.004 | 0.004 | 0.003 | 0.001 | 0.001 | 0.001 | 0.001 | 0.001 | 0.001 | 0.001 | 0.001 |
| 2 | 0.000 | 0.004 | 0.004 | 0.005 | 0.005 | 0.015 | 0.006 | 0.004 | 0.003 | 0.003 | 0.001 | 0.001 | 0.002 | 0.003 | 0.001 | 0.001 |
| 3 | 0.005 | 0.011 | 0.012 | 0.012 | 0.011 | 0.009 | 0.010 | 0.013 | 0.004 | 0.003 | 0.003 | 0.003 | -1.000 | 0.003 | 0.003 | 0.004 |

| DATA SET 1 | IDT | IDA | IDC | IDL | IDR | IDT | IDL | T12 | IDL | IDR | IDC | PDP | R2 | IDC12 | IDC45 | PMIN | PMAX |
| --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- |
| OUTBOARD | 0.0954 | 0.0741 | 0.0741 | 0.0350 | 0.0370 | 0.0350 | 0.4858 | 0.0078 | 0.4858 | 0.0350 | 0.0370 | 1.0000 | 0.9808 | 0.0033 | 0.0370 | 0.9080 | 1.0016 |
| INBOARD | 0.0927 | 0.0736 | 0.0736 | 0.0413 | 0.0334 | 0.0413 | 0.5307 | 0.0023 | 0.5307 | 0.0413 | 0.0334 | 0.9991 | 0.9821 | 0.0014 | 0.0334 | 0.9098 | 1.0008 |

| DATA SET 2 | | | | | | | | | | | | | | | | | |
| --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- |
| OUTBOARD | 0.0954 | 0.0741 | 0.0741 | 0.0940 | 0.0350 | 0.0940 | 0.8305 | 0.0078 | 1.0126 | 1.2410 | 0.0505 | 1.2624 | 0.9808 | 0.0940 | 0.0505 | 0.9080 | 1.0016 |
| INBOARD | 0.0927 | 0.0736 | 0.0736 | 0.0923 | 0.0413 | 0.0923 | 0.8544 | 0.0023 | 1.0109 | 1.2422 | 0.0461 | 1.2623 | 0.9821 | 0.0923 | 0.0461 | 0.9098 | 1.0008 |

| PSTCE1 | PSTCE2 | PSTCE3 | PSTCD1 | PSTCD2 | PSTCD3 | PSTCI1 | PSTCI2 | PSTCI3 | PSTRD1 | PSTRD2 | PSTRD3 | PSTRI1 | PSTRI2 | PSTRI3 |
| --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- | --- |
| 1.023/75 | 7.32 | 7.54 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 14.10 | 7.20 | 103.80 | 14.05 | 7.20 | 56.65 |

199

*** STEADY STATE ***

PART POINT PROJECT TEST    DATE   DAY HR MIN SEC    ERCODE MODE   SET DATE  WIND-OFF   AEDC PROPULSION WIND TUNNEL
551  2 P41-D2A TF419 9/27/76 271231 461 35         0      0   3110/27/76 548/   -1          TRANSONIC 16T

M        OT     P     Q   REX10-6  TT  PTA-1  PTB-2  PCA-1  PCB-2  TTA-1 JTB-0  PTI NCN  WAE  WAM  TPR  WA/WT  MB  SCHED
0.900 1788.5 1059.0 599.3 3.428  570 1786.5 1789.2 1072.5 1072.9 110  1446.4 -0.00  0.00 1.237 0.0392 0.900  1

ALPHA  BETA   VANEO  VANEI  SHOCK TUBE SELECT       14C S19 L7 J27 E10 U1 M6 G34-2 W8-1 M16-1 N30-1 B5-1 C3
1.0  0.727 18.56  14.57        5020                 R8C-167,RCC-182,1 AB19 19.5 AB20-189 ML0=2.733 ML1=2.726 CBO-Uns

        R2     MFR2   MFR100    W2R    W2R-FS    T12     IDT     IDR     IDC     IDL     PD     PDP    IDA
OUTBOARD 0.9801 0.6896 0.7036  3.499 349.93  0.0076  0.0073  0.0357  0.0377  0.4949 1.0002 1.2619 0.0754
INBOARD  0.9826 0.6835 0.7007  3.485 348.47  0.0019  0.0996  0.0104  0.0328  0.5198 0.9985 1.2632 0.0221

         W2S    M2     MA     NSP    TAVG     W2    CP1SS  CP2SS  CP3SS
OUTBOARD 0.404 0.505 0.714  0.8006 0.8235  2.766  0.619  0.676  0.620
INBOARD  0.482 0.497 0.000  0.8040 0.6298  2.761

*** RAMP PRESSURES ***                        *** COWL INTERNAL PRESSURES ***              *** BLC PLENUM ***

         PL635  PL455  PL470  PL490            PLC20  PLC3C  PLC35  PLC45                   PL543  PL573
OUTBOARD 0.7803 0.8389 0.7754 0.8381           0.7883 0.7861 0.8174 0.8727                 0.7352 0.7985
INBOARD  0.7882 0.8335 0.7745 0.8476           0.7992 0.7846 0.8295 0.8738                 0.7284 0.8035

*** FLOWMETER PRESSURE ***                     *** CONTROL PARAMETERS ***

         PL680  PL681  PL682  PL683            PL690  PL691  PL692  PL693  PL700  PL702  PL703  PL704  PL700  PL701
OUTBOARD 0.6547 0.6552 0.6533 0.6551           0.6551 0.5546 0.5521 0.5547 0.9988 0.9988 0.7997 0.7778 0.9991 0.7109
INBOARD  0.6546 0.6547 0.6546 0.6544           0.6544 0.5532 0.5543 0.5565 0.9988 0.9988 0.8030 0.7843

*** OUTBOARD PT2/PTG ***                       *** INBOARD PT2/PTG ***

RING 22.5DEG  67.5  112.5  157.5  202.5  247.5  292.5  337.5   22.5   67.5  112.5  157.5  202.5  247.5  292.5  337.5
1    1.001 1.001 1.000 1.001 1.001 1.001 1.001 1.001   1.000  1.000  1.001  1.001  1.001  1.001  1.001  1.001
2    1.001 1.001 1.000 1.000 1.000 1.000 1.000 1.000   1.000  1.000  1.001  1.001  1.000  1.000  1.000  1.000
3    1.000 0.994 1.001 1.002 0.993 0.964 0.986 0.978   0.997  0.978  0.996  1.001  0.996  0.992  0.992  1.000
4    0.996 0.986 0.958 0.984 0.945 0.933 0.947 0.940   0.958  0.940  0.960  0.985  0.998  0.999  0.971  0.976
5    0.977 0.956 0.972 0.945 0.941 0.938 0.906 0.912   0.922  0.912  0.943  0.941  0.962  0.981  0.951  0.931

*** OUTBOARD RMS2 ***                          *** INBOARD RMS2 ***

RING 22.5DEG  67.5  112.5  157.5  202.5  247.5  292.5  337.5   22.5   67.5  112.5  157.5  202.5  247.5  292.5  337.5
1   0.003 0.003 0.003 0.003 0.003 0.003 0.001 0.001   0.001  0.001  0.001  0.001  0.001  0.001  0.001  0.001
2  -0.003 0.003 0.003 0.005 0.005 0.003 0.010 0.003   0.001  0.001  0.002  0.001  0.001  0.001  0.004  0.001
3  -0.000 0.004 0.010 0.012 0.015 0.013 -0.004 0.013  -1.000  0.003  0.002  0.003  0.003  0.004  0.003  0.004
4   0.004 0.011 0.012 0.011 0.009 0.013 0.013 0.013   0.004  0.003  0.003  0.003  0.003  0.003  0.003  0.004

DATA SET 1  IDT   IDA    IDC    IDP   IDL    T12    PDP    PD     IDL    R2    IDC12  IDC45  PMIN    PMAX
OUTBOARD 0.0073 0.0754 0.0377 0.0357 0.4949 0.0076 1.0002 1.0002 0.4949 0.9801 0.0033 0.0377 0.9062 1.0015
INBOARD  0.0996 0.0721 0.0328 0.0404 0.5198 0.0019 0.9985 0.9985 0.5198 0.9826 0.0003 0.0328 0.9118 1.0008

DATA SET 2
OUTBOARD 0.0973 0.0754 0.0754 0.0957 0.0352 1.0130 1.2619 1.2402 0.9801 0.9801 0.0957 0.0513 0.9062 1.0015
INBOARD  0.0906 0.0721 0.0721 0.0903 0.0404 1.0101 1.2632 1.2436 0.9826 0.9826 0.0903 0.0473 0.9118 1.0008

PSTCE1 PSTCE2 PSTCE3 PSTCD1 PSTCD2 PSTCD3 PSTCI1 PSTCI2 PSTCI3 PSTRD1 PSTRD2 PSTRD3 PSTRI1 PSTRI2 PSTRI3
7.33   7.32   7.55   0.00   0.00   0.00   0.00   0.00   0.00   114.55  7.35   4.40  62.00  7.30   6.20

**\*\*\* STEADY STATE \*\*\***

| PART POINT | PROJECT | TEST | DATE | DAY | HR | MIN | SEC | ENCODE MODE | SET | DATE | WIND-OFF | AEDC PROPULSION WIND TUNNEL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 557 | 2 | P41L-D2A | TF49 | 9/28/76 | 2721 | 11 | 151 37 | 0 0 | 3110/27/76 | 555/ | -1 | TRANSONIC 16T |

| M | PT | P | Q | REX10-6 | TT | PTA-1 | PTB-2 | PCA-1 | PCB-2 | TTA-1 | TTB-0 | PTI | NCN | WAE | WAH | TPR | WA/WT | MB | SCHED |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 0.851 | 1697.5 | 1557.8 | 535.7 | 3.178 | 570 | 1697.5 | 1698.1 | 1071.0 | 1071.7 | 110 | 111 | 1377.3 | 0 | -0.00 | 0.00 | 1.232 | 0.030 | 0.850 | 1 |

ALPHA BETA VANEO VANEI SHOCK TUBE SELECT 140 S19 L7 J27 E10 U1 M6 G34-2 W8-1 M16-1 N30-1 B5-1 C3
1.0 25.67 21.22 5015 R8E=167,RC0=1n2,1,AB1Cs1n,5,AB20=1s0,HL0=2,733,HL1=2,726,C:0,UmS

| | W2 | MFR2 | MFR100 | W2R | W2R-FS | T12 | IDT | IDR | IDC | IDL | PD | PDP | IDA |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.9852 | 0.6001 | 0.6092 | 2.995 | 299.53 | 0.0061 | 0.0710 | 0.0281 | 0.0285 | 0.3845 | 0.9955 | 1.2694 | 0.0547 |
| INBOARD | 0.9893 | 0.5973 | 0.6038 | 2.969 | 296.89 | 0.0023 | 0.0624 | 0.0271 | 0.0248 | 0.3596 | 0.9928 | 1.2729 | 0.0506 |

| | W25 | W2 | MA | NSP | TAVG | W2 | CP2SS | CP2SS | CP3SS |
|---|---|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.400 | 0.415 | 0.671 | 0.8594 | 0.8751 | 2.258 | 0.644 | 0.699 | 0.645 |
| INBOARD | 0.396 | 0.407 | 0.000 | 0.8707 | 0.8826 | 2.248 | | | |

**\*\*\* RAMP PRESSURES \*\*\***

| | PL435 | PL450 | PL470 | PL480 | PL490 |
|---|---|---|---|---|---|
| OUTBOARD | 0.8307 | 0.8709 | 0.8441 | 0.8854 | 0.8855 |
| INBOARD | 0.8424 | 0.8777 | 0.8476 | 0.8904 | 0.8975 |

**\*\*\* COWL INTERNAL PRESSURES \*\*\***

| | PL020 | PL030 | PL035 | PL045 |
|---|---|---|---|---|
| | 0.8526 | 0.8525 | 0.8717 | 0.9041 |
| | 0.8615 | 0.8546 | 0.8816 | 0.9124 |

**\*\*\* BLC PLENUM \*\*\***

| | PL543 | PL573 |
|---|---|---|
| | 0.7871 | 0.8541 |
| | 0.7796 | 0.8605 |

**\*\*\* FLOWMETER PRESSURE \*\*\***

| | PL680 | PL661 | PL682 | PL683 | PL690 | PL691 | PL692 | PL693 |
|---|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.4721 | 0.4714 | 0.4714 | 0.4717 | 0.3520 | 0.3518 | 0.3482 | 0.3492 |
| INBOARD | 0.4705 | 0.4721 | 0.4705 | 0.4705 | 0.3500 | 0.3498 | 0.3510 | 0.3515 |

**\*\*\* CONTROL PARAMETERS \*\*\***

| | PL702 | PL703 | PL704 | PL700 | PL701 |
|---|---|---|---|---|---|
| | 0.9982 | 0.8578 | 0.8471 | 0.9989 | 0.7385 |
| | 0.9985 | 0.8694 | 0.8536 | | |

**\*\*\* OUTBOARD PT2/PT0 \*\*\***

| RING | 22.5 DEG | 67.5 | 112.5 | 157.5 | 207.5 | 247.5 | 292.5 | 337.5 |
|---|---|---|---|---|---|---|---|---|
| 1 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 |
| 2 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.000 | 1.001 |
| 3 | 0.996 | 1.000 | 1.001 | 0.999 | 0.994 | 0.984 | 0.986 | 0.994 |
| 4 | 0.984 | 0.994 | 0.984 | 0.999 | 0.961 | 0.975 | 0.959 | 0.968 |
| 5 | 0.947 | 0.974 | 0.974 | 0.979 | 0.955 | 0.974 | 0.931 | 0.943 |

**\*\*\* INBOARD PT2/PT0 \*\*\***

| RING | 22.5 DEG | 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 |
|---|---|---|---|---|---|---|---|---|
| 1 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 |
| 2 | 1.000 | 1.000 | 1.001 | 1.001 | 1.000 | 1.000 | 1.001 | 1.000 |
| 3 | 0.994 | 0.994 | 1.001 | 0.998 | 0.994 | 0.999 | 0.986 | 1.000 |
| 4 | 0.968 | 0.984 | 0.987 | 0.975 | 0.947 | 0.991 | 0.975 | 0.999 |
| 5 | 0.955 | 0.931 | 0.956 | 0.964 | 0.977 | 0.987 | 0.956 | 0.959 |

**\*\*\* OUTBOARD RMS2 \*\*\***

| RING | 22.5 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 |
|---|---|---|---|---|---|---|---|
| 1 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 |
| 2 | 0.004 | 0.003 | 0.003 | 0.004 | 0.004 | 0.001 | 0.001 |
| 3 | 0.004 | 0.004 | 0.005 | 0.011 | 0.008 | 0.001 | 0.001 |
| 5 | 0.008 | 0.008 | 0.008 | 0.007 | 0.008 | 0.002 | 0.002 |

**\*\*\* INBOARD RMS2 \*\*\***

| RING | 22.5 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 |
|---|---|---|---|---|---|---|---|
| 1 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 | 1.001 |
| 3 | 0.003 | 0.003 | 0.001 | 0.001 | 0.001 | 0.001 | 0.001 |
| 4 | 0.004 | 0.005 | 0.008 | 0.011 | 0.002 | 0.002 | 0.002 |
| 5 | 0.008 | 0.009 | 0.002 | 0.007 | 0.002 | 0.002 | -1.000 |

DATA SET 1

| | IDT | IDA | IDT | IDC | IDR | IDL | R2 | PD | PDP | TI2 |
|---|---|---|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.0710 | 0.0547 | 0.0285 | 0.0697 | 0.0281 | 0.3845 | 0.9852 | 0.9955 | 1.2694 | 0.0061 |
| INBOARD | 0.0624 | 0.0526 | 0.0248 | 0.0621 | 0.0271 | 0.3596 | 0.9893 | 0.9928 | 1.2729 | 0.0023 |

DATA SET 2

| | IDT | IDA | IDC | IDL | IDC45 | PDP | PD | IDC12 | IDC45 | PMIN | PMAX |
|---|---|---|---|---|---|---|---|---|---|---|---|
| OUTBOARD | 0.0710 | 0.0547 | 0.0281 | 0.0226 | 1.0044 | 1.2543 | 0.9852 | 0.0028 | 0.0285 | 0.9312 | 1.0011 |
| INBOARD | 0.0524 | 0.0506 | 0.0271 | 0.5709 | 1.0005 | 1.2598 | 0.9893 | 0.0004 | 0.0248 | 0.9392 | 1.0009 |

| PSTCE1 | PSTCE2 | PSTCE3 | PSTCD1 | PSTCD2 | PSTCD3 | PSTCI1 | PSTCI2 | PSTCI3 | PSTRD1 | PSTRD2 | PSTRD3 | PSTRI1 | PSTRI2 | PSTRI3 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| -0.12 | 7.62 | 7.40 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 14.15 | 54.70 | 14.20 | 14.05 | 31.80 | 14.05 |

*** STEADY STATE ***

PART POINT PROJECT TEST    DATE     DAY HR MIN SEC      ENCODE MODE    SET DATE  WIND-OFF    AEDC PROPULSION WIND TUNNEL
558   2 P41-D2A  TF419 9/28/76 2221 11 231  1             0    0  3110/27/76 555/ -1                    TRANSONIC 16T

M      PI     P      Q    REX10-6   TT   PTA-1  PTB-2  PCA-1  PTB-2  TTA-1  TTB-0  PTI NCN  WAE  WAW  TPR  WA/WT  MB  SCHED
0.850 1096.0 1057.3 534.9   3.178  569 1696.0 1696.6 1070.5 1070.9  110   111 1376.1  0 -0.00  0.00  1.232  0.0321  0.850  1

ALPHA  BETA  VANEO  VANEI  SHOCK TUBE SELECT    140 S19 L7 J27 E10 U1 M6 G34-2 W6-1 M16-1 N30-1 B5-1 C3
1.0  -0.012 25.06  21.22       5017          RBC-1=7,BCO-1=2.1,AB10-1=.5,AB20-1=0,H1-1=2.733,H1I1=2.726,C=0.U=S

         R2     MFR2   MFR100   W2R   W2R-FS   TI2    IDT    IDR    IDC    IDL    PD    PDP    IDA
OUTBOARD 0.9851 0.6000 0.6090  2.994 299.44  0.0059 0.0708 0.0281 0.0284 0.3838 0.9954 1.2695 0.0546
INBOARD  0.9893 0.5991 0.6052  2.978 297.77  0.0019 0.0629 0.0274 0.0247 0.3617 0.9927 1.2731 0.0510

         M2S    M2     MA     NSP    TAVG    W2    CP1SS  CP1SS  CP2SS  CP3SS
OUTBOARD 0.400  0.414  0.669  0.8586 0.8756 2.256 0.645  0.645  0.699  0.645
INBOARD  0.397  0.408  0.300  0.6653 0.8822 2.253

*** RAMP PRESSURES ***                          *** COWL INTERNAL PRESSURES ***                *** BLC PLENUM ***

         PL435  PL450  PL472  PL480  PL490     PL020  PL030  PL035  PL045     PL543  PL523
OUTBOARD 0.6308 0.6770 0.6441 0.8855 0.8858    0.8529 0.8525 0.8778 0.9041    0.7877 0.8546
INBOARD  0.6424 0.8780 0.8478 0.8948 0.8980    0.8618 0.8547 0.8815 0.9123    0.7798 0.8595

*** FLOWMETER PRESSURE ***                       *** CONTROL PARAMETERS ***

         PL680  PL681  PL682  PL683  PL690     PL691  PL692  PL693     PL702  PL703  PL704  PL700  PL701
OUTBOARD 0.4701 0.4696 0.4703 0.4705 0.3497    0.3496 0.3457 0.3467    0.9995 0.8581 0.8472 0.9991 0.7403
INBOARD  0.4597 0.4705 0.4701 0.4693 0.3471    0.3472 0.3490 0.3493    0.9991 0.8645 0.8541

*** OUTBOARD PT2/PTO ***                          *** INBOARD PT2/PTO ***

RING 22.5DEG  67.5  112.5  157.5  202.5  247.5  292.5  337.5   22.5   67.5  112.5  157.5  202.5  247.5  292.5  337.5
1     1.001  1.001  1.001  1.000  1.001  1.001  1.001  1.001  1.001  1.001  1.001  1.001  1.001  1.001  1.001  1.001
2     1.001  1.001  1.001  1.001  0.994  0.994  1.000  1.000  1.000  1.000  1.001  1.001  1.000  1.001  1.001  1.001
3     0.997  1.000  1.001  1.000  0.976  0.968  0.986  0.998  0.998  0.999  0.999  1.001  1.000  1.001  0.999  1.001
4     0.977  0.994  0.996  0.984  0.961  0.948  0.960  0.972  0.979  0.975  0.987  1.000  1.001  0.991  0.996
5     0.947  0.974  0.974  0.956  0.955  0.931  0.943  0.944  0.939  0.962  0.956  0.976  0.987  0.973  0.960

*** OUTBOARD RMS2 ***                            *** INBOARD RMS2 ***

RING 22.5DEG  67.5  112.5  157.5  202.5  247.5  292.5  337.5   22.5   67.5  112.5  157.5  202.5  247.5  292.5  337.5
1     0.003  0.003  0.003  0.003  0.003  0.003  0.001  0.001  0.001  0.001  0.001  0.001  0.001
2    -0.000  0.004  0.004  0.005  0.005  0.011  0.004  0.008  0.001  0.007  0.001  0.001  0.001  0.005
3    -1.000  0.004  0.004  0.008  0.009  0.007  0.008  0.010  0.000 -1.000  0.001  0.001  0.005  0.001
5     0.025  0.036  0.009  0.009  0.007  0.002 -1.000  0.002  0.002  0.002  0.002 -1.000

DATA SET 1  IDT    IDA    IDC    IDR    IDL    TI2    PDP    PD    R2     IDC12  IDC45  PMIN   PMAX
OUTBOARD 0.0708 0.0546 0.0284 0.0281 0.3838 0.0059 1.2695 0.9954 0.9851 0.0028 0.0284 0.9314 1.0011
INBOARD  0.0629 0.0510 0.0247 0.0274 0.3617 0.0019 1.2731 0.9927 0.9893 0.0003 0.0247 0.9388 1.0010

DATA SET 2
OUTBOARD 0.0708 0.0546 0.0696 0.0696 0.6266  1.0043 1.2545 1.2695 0.9851 0.0696 0.0366 0.9314 1.0011
INBOARD  0.0529 0.0510 0.0625 0.0625 0.5747  1.0005 1.2599 1.2731 0.9893 0.0351 0.9388 1.0010

PSTCE1 PSTCE2 PSTCE3 PSTCD1 PSTCD2 PSTCD3 PSTC11 PSTC12 PSTC13 PSTRD1 PSTRD2 PSTRD3 PSTRI1 PSTRI2 PSTRI3
-0.39  7.67   7.40   0.00   0.00   0.00   0.00   0.00   0.00  14.15  7.65  14.10  59.60  8.25  34.95

*** STEADY STATE ***

PART POINT PROJECT TEST    DATE    DAY HR MIN SEC    ERCODE MODE    SETIDATE WIND-OFF    AEDC PROPULSION WIND TUNNEL
559  1 P41T-D2A TE149 9/29/76 2721 1 291 41        0    0  3110/2776 5551 -1         TRANSONIC 16T

M    FL    P    Q    REX10-6  TI  PTA-1  PTR-2  PCA-1  PCB-2  ITA-1  TTB-0  PTI.NCN  WAE  WAH  YPP  WA/WT  MB  SCHED
0.850 1695.7 1057.2 534.8  3.177  569 1695.7 1696.2 1070.4 1070.7  110   111 1375.6  0-0.00 0.00 1.233 0.0328 0.850  1

ALPHA  BETA  VANE0  VANEI  SHOCK TUBE SELECT    140 S19 L7 J27 E10 U1 M6 G34-2 W6-1 H16-1 N30-1 B5-1 C3
1.0 -0.013 25.06 21.21         5020          RBC-1E7,RGO-1e2,1,AB10=1,5,AB20-1s0,HLG=2.733,HLI=2.226,CEO-U8S

        R2     WFR2   WFR100  WFR2   W2R    W2R-FS   TI2    IDT    IDR    IDC    IDL    PD     PDP    IDA
OUTBOARD 0.9350 0.6000 0.6091  2.995 299.45  299.67 0.0060 0.0703 0.0280 0.0281 0.3822 0.9954 1.2696 0.0543
INBOARD  0.7592 0.5992 0.6055  2.977 297.67  297.67 0.0017 0.0634 0.0274 0.0248 0.3620 0.9926 1.2732 0.0512

        M2S    M2     MA     NSP    TAVG   W2    CP1SS  CP1SS  CP2SS  CP3SS
OUTBOARD 0.440 0.671 0.6588 0.0758 2.256 0.645 0.645 0.699 0.645
INBOARD  0.397 0.408 0.000 0.9950 0.8821 2.252

*** RAMP PRESSURES ***                    *** COWL INTERNAL PRESSURES ***              ***BLC PLENUM.***

        PL435  PL450  PL470  PL480  PL490        PL020  PL030  PL035  PL045              PL543  PL523
OUTBOARD 0.8715 0.8776 0.8449 0.8861 0.8861      0.8528 0.8522 0.8714 0.9040            0.7873 0.8543
INBOARD  0.8424 0.8775 0.8477 0.8945 0.8977      0.8615 0.8547 0.8619 0.9131            0.7798 0.8600

*** FLOWMETER PRESSURE ***                                  *** CONTROL PARAMETERS ***

        PL630  PL681  PL682  PL683  PL690  PL691  PL692  PL693      PL702  PL703  PL704  PL700  PL1701
OUTBOARD 0.4495 0.4692 0.4695 0.4693 0.3481 0.3479 0.3449 0.3459    0.9986 0.8576 0.8466 0.9992 0.7389
INBOARD  0.4496 0.4697 0.4696 0.4687 0.3465 0.3465 0.3485 0.3465    0.9992 0.8644 0.8538

*** OUTBOARD PT2/PTO ***                                    *** INBOARD PT2/PTO ***

RING 22.5 DEG  67.5  112.5  157.5  202.5  247.5  292.5  337.5   22.5   67.5  112.5  157.5  202.5  247.5  292.5  337.5
1   1.001  1.001  1.001  1.001  1.001  1.001  1.000  1.000   1.001  1.001  1.001  1.001  1.001  1.001  1.001  1.001
2   1.001  1.000  1.001  1.000  1.000  1.001  1.000  1.000   1.001  1.000  1.000  1.000  1.000  1.000  1.001  1.001
3   0.997  1.000  1.000  0.994  0.975  0.969  0.998  0.986   0.985  0.999  1.000  0.999  1.000  0.999  1.000  1.001
4   0.977  0.994  0.999  0.996  0.984  0.961  0.972  0.960   0.959  0.975  1.000  0.986  1.000  0.991  0.996
5   0.947  0.974  0.974  0.979  0.955  0.955  0.932  0.944   0.939  0.962  0.944  0.956  0.976  0.987  0.973  0.959

*** OUTBOARD RMS2 ***                                       *** INBOARD RMS2 ***

RING 22.5 DEG  67.5  112.5  157.5  202.5  247.5  292.5  337.5   22.5   67.5  112.5  157.5  202.5  247.5  292.5  337.5
1   0.001  0.001  0.001  0.001  0.003  0.004  0.004  0.003   0.003  0.001  0.001  0.001  0.001  0.001  0.001  0.001
2   0.004  0.003  0.003  0.003  0.004  0.004  0.004  0.003   0.001  0.001  0.001  0.001  0.001  0.001  0.001  0.001
3  -1.000  0.004  0.004  0.005  0.011  0.008  0.010  0.005  -1.000  0.001  0.001  0.001  0.001  0.001  0.002  0.001
4   1.005  0.008  0.008  0.009  0.007  0.007  0.002 -1.000   0.002  0.002  0.002  0.002  0.002  0.002  0.002 -1.000

DATA SET 1  IDT    IDA    IDC    IDR    IDL    TI2    PD     PDP    R2     IDC12  IDC45  PMIN   PMAX
OUTBOARD 0.0703 0.0543 0.0281 0.0280 0.3822 0.0060 0.9954 1.2696 0.9650 0.0026 0.0281 0.9315 1.0008
INBOARD  0.0634 0.0512 0.0248 0.0274 0.3620 0.0017 0.9926 1.2732 0.9892 0.0005 0.0248 0.9385 1.0013

DATA SET 2
OUTBOARD 0.0703 0.0543 0.0281 0.0280 0.8237 1.0042 1.2546 0.9650 0.0364 0.0692 0.9315 1.0008
INBOARD  0.0634 0.0512 0.0627 0.0274 0.5765 1.0005 1.2599 0.9892 0.0354 0.0627 0.9385 1.0013

PSTCE1 PSTCE2 PSTCE3 PSTCD1 PSTCD2 PSTCD3 PSTCI1 PSTCI2 PSTCI3 PSTRD1 PSTRD2 PSTRD3 PSTRI1 PSTRI2 PSTRI3
7.67   7.66   7.41   0.00   0.00   0.00   0.00   0.00   0.00   61.45  7.80   0.00   33.90  7.75   6.30

*** STEADY STATE ***

PART POINT PROJECT TEST    DATE    DAY HR MIN SEC    ERCODE MODE    SETIDATE WIND-OFF    AEDC PROPULSION WIND TUNNEL
568   2 P43 2D2A  TF419  9/28/76  2721 51 431 40        0      0   3110/27/76 5671  -1              TRANSONIC 16T

M        DI      P      Q    PEX10-6    TT  PTA-1  PTB-2  PCA-1  PCB-2  JTA-1  JTB-0  PTI NCN  WAE  WAH  TPR  WA/WT  MB SCHED
0.700 1469.0 1059.4 362.9  2,482  570 1469.0 1469.7 1069.7 1069.4  110  110 1167.7  0-0.00  0.00 1.258 0.0001 0.700  1

ALPHA  BETA  VANEI  VANEI  SHOCK TUBE SELECT    141 S19 L7 J27 E10 U1 M6 G34-2 N8-1 H16-1 N30-1 B5-1 C3
3.0   5.023 18.87 14.08         5015              RB5-1E2,8C5-1B24,AB10-15,AB20-190,ML8s2.733,HL1s2.726,CR0.UR5

         R2      MFR2    MFR1D0   W2R    W2R-FS   TI2     IDT    IDR    IDC    IDL    PD     PDP     IDA
OUTBOARD 0.9758 0.7455 0.7640  3.502 350.19  0.0076 0.0913 0.0390 0.0316 0.4990 1.0004 1.2617 0.0651
INBOARD  0.9749 0.7416 0.7607  3.487 348.71  0.0030 0.1101 0.0420 0.0420 0.5671 1.0008 1.2596 0.0831

         W25     M2     MA      NSP    IAVG      M2    CP1SS  CP2SS  CP3SS
OUTBOARD 0.495 0.505 0.508  0.5489  0.0200  2.263  0.752  0.765  0.719
INBOARD  0.492 0.501 0.501  0.000  0.8264  2.252

         *** RAMP PRESSURES ***                            *** COWL INTERNAL PRESSURES ***              *** BLC PLENUM ***

         PL435   PL455   PL460   PL470   PL480   PL490       PL020   PL030   PL035   PL045           PL543   PL523
OUTBOARD 0.755  0.6506  0.7728  0.8355  0.8402               0.7937  0.7826  0.8161  0.8609          0.7828  0.8053
INBOARD  0.7927 0.6256  0.7667  0.8366  0.8447               0.7934  0.7768  0.8205  0.8625          0.7598  0.7999

         *** FLOWMETER PRESSURE ***                          *** CONTROL PARAMETERS ***

         PL680   PL681   PL682   PL683   PL690   PL691   PL692   PL693   PL702   PL703   PL704   PL700   PL1701
OUTBOARD 0.5563 0.5457  0.5449  0.5439  0.4057  0.4070  0.4422  0.4032  0.9324  0.7915  0.7751  0.9991  0.8376
INBOARD  0.5449 0.5461  0.5430  0.5439  0.4057  0.4036  0.4047  0.4076  0.9890  0.7975  0.7773

         *** OUTBOARD PT2/PTC ***                                            *** INBOARD PT2/PTC ***

RING 22.5 DEG 67.5   112.5   157.5   202.5   247.5   292.5   337.5   22.5   67.5   112.5   157.5   202.5   247.5   292.5   337.5
1    0.996  0.999  1.000  1.000  1.001  1.001  1.001  1.001  1.001  1.001  1.001  1.001  1.000  1.001  1.001
2    0.923  0.974  0.967  1.001  1.001  0.995  0.996  0.992  1.000  0.992  1.001  1.001  0.995  1.000  1.001
3    0.951  0.952  0.978  1.001  0.995  0.957  0.959  0.952  1.001  1.000  1.001  1.000  0.983  0.997
4    0.980  0.937  0.972  0.992  0.892  0.957  0.928  0.917  0.992  0.943  1.000  0.942  0.955  0.957
5    0.958  0.919  0.954  0.953  0.944  0.936  0.912  0.931  0.980  0.934  0.943  0.944  0.934  0.913

         *** OUTBOARD RMS2 ***                                               *** INBOARD RMS2 ***

RING 22.5 DEG 67.5   112.5   157.5   202.5   247.5   292.5   337.5   22.5   67.5   112.5   157.5   202.5   247.5   292.5   337.5
1    0.006  0.004  0.003  0.003  0.003  0.003  0.003  0.008  0.001  0.003  0.001  0.003  0.001  0.002
2    0.000  0.013  0.011  0.005  0.005  0.007  0.008  0.000  -1.000  1.000  0.001  0.001  8.888  0.002
3    0.006  0.012  0.014  0.001  0.009  0.011  0.013  -1.000  1.000  0.003  0.000  0.004  0.003  0.011

         *** DATA SET 1 ***

         IDT     IDA     IDC     IDR     IDL     TI2     IDL     PDP     PD     R2     IDC12  IDC45   PMIN   PMAX
OUTBOARD 0.0013 0.0651  0.0316  0.0390  0.0390  0.0076  0.4990  1.0004  1.2617  0.9758  0.0117  0.0316  0.9124  1.0015
INBOARD  0.0101 0.0831  0.0420  0.0420  0.0420  0.0030  0.5671  1.0008  1.2596  0.9749  0.0034  0.0420  0.6938  1.0012

         *** DATA SET 2 ***

OUTBOARD 0.0913 0.0651  0.0869  0.7817  1.0107 1.2441  0.9728  0.9728  0.0869  0.0398  0.9124  1.0015
INBOARD  0.0101 0.0831  0.1086  0.9369  1.0113 1.2367  0.9749  0.9749  0.1086  0.0538  0.8938  1.0012

         PSTCE1  PSTCE2  PSTCE3  PSTCD1  PSTCD2  PSTCD3  PSTCI1  PSTCI2  PSTCI3  PSTRD1  PSTRD2  PSTRD3  PSTRI1  PSTRI2  PSTRI3
         6.10    7.85    6.95    0.00    0.00    0.00    0.00    0.00    0.00   14.00  132.45  14.10   14.00   71.75  14.00

204

*** STEADY STATE ***

PART POINT PROJECT TEST    DATE   DAY HR MIN SEC      ERCODE MODE    SET:DATE   WIND-OFF    AEDC PROPULSION WIND TUNNEL
549   2  P41-D2A  TF419 9/28/26 272 15 51 571 16       0    0    310/27/76 567/  -1              TRANSONIC 16T

M      PI      B      Q    REX10-6   II   PTA-1  PTB-2   PCA-1  TIB-0  PTI NCN  WAE  MAN  TPR  MA/WT  MB  SCHED
0.703 1458.9 1955.7 365.7  2.493  569 1468.9 1460.5 1065.3  110  110 1170.6  0-0.00 0.00 1.255 0.0063 0.700  1

ALP=4   BETA  VANEO VANEI  SHOCK TUBE SELECT     14F S19 L7 J27 E10 U1 M6 G34-2 H8-1 M16-1 N30-1 B5-1 C3
1.0  -5  C0:  18.67  14.66         5717            BB=-1&7,RG0=1&2,1,AB10=1&5,AB20=1&0,H0=2,733,H1=2,726,C=0,U&S

        R2     MFR2   MFR100    M2R    M2R-FS     TI2    IDT     IDR    IDC    IDD    PD    PDP    IDA
OUTBOARD  0.9430 0.7361 0.7644  3.513  351.28  0.0111 0.1050 0.0364 0.0298 0.4674 1.0008 1.2623 0.0659
INBOARD   0.7737 0.7401 0.7601  3.493  349.33  0.0031 0.0978 0.0431 0.0225 0.5296 0.9994 1.2619 0.0699

        M2S    M2     MA     NSP    TAVG     N2    CP1SS  CP2SS  CP3SS
OUTBOARD  0.447 0.503 0.726 0.7865 0.8102  2.241  0.720  0.761  0.751
INBOARD   0.493 0.500 0.000 0.8650 0.8210  2.254

*** RAMP PRESSURES ***                              *** COWL INTERNAL PRESSURES ***           *** BLC PLENUM ***

        PL415   PL455   PL470   PL480   PL490      PL020   PL030   PL035   PL045      PL543   PL573
OUTBOARD 0.7415 0.8149 0.7648 0.8232 0.6292      0.7786 0.7736 0.8071 0.8492      0.7591 0.7014
INBOARD  0.5252 0.8280 0.7639 0.8399 0.6490      0.7869 0.7771 0.8210 0.8629      0.7704 0.7982

            *** FLOWMETER PRESSURE ***                    *** CONTROL PARAMETERS ***

        PL680   PL681   PL682   PL683   PL690   PL691   PL692   PL693     PL702   PL703   PL704   PL700   PL701
OUTBOARD 0.5441 0.5436 0.5441 0.5435 0.4082 0.4088 0.4042 0.4054     0.9989 0.7857 0.7664 0.9289 0.6541
INBOARD  0.5441 0.5455 0.5451 0.5445 0.4056 0.4039 0.4056 0.4075     0.8932 0.7726 0.7754

            *** OUTBOARD PT2/PTB ***                              *** INBOARD PT2/PTB ***

RING  22.5DEG  67.5  112.5  157.5  202.5  247.5  292.5  337.5     22.5   67.5  112.5  157.5  202.5  247.5  292.5  337.5
1    1.004  1.301  1.000  1.003  1.000  0.989  0.967  0.999     1.001  1.001  1.001  1.000  1.001  0.993  0.987  0.998
2    0.981  0.990  0.964  0.925  1.000  1.000  0.960  0.996     1.000  1.000  1.001  1.001  1.001  0.984  0.964  0.998
3    0.954  0.952  1.000  1.000  0.943  0.937  0.980  0.975     0.997  0.993  1.001  1.001  0.983  0.948  0.981
4    0.931  0.926  0.936  1.000  0.994  0.922  0.944  0.935     0.955  0.954  0.991  0.978  0.933  0.949
5    0.905  0.912  0.968  0.968  0.948  0.908  0.900  0.914     0.917  0.906  0.942  0.949  0.961  0.920  0.922

            *** OUTBOARD RMS2 ***                              *** INBOARD RMS2 ***

RING  22.5DEG  67.5  112.5  157.5  202.5  247.5  292.5  337.5     22.5   67.5  112.5  157.5  202.5  247.5  292.5  337.5
1    0.005  0.005  0.005  0.005  0.005  0.013  0.013  0.033     0.009  0.001  0.001  0.001  0.001  0.993  0.987  8.000
2    0.000  0.016  0.018  0.004  0.018  0.018  0.033  0.017     7.777  0.004  0.002  0.001  0.888  8.888  8.888
3    0.008  0.015  0.015  0.012  0.013  0.012  0.014  0.015    -1.000  0.004  0.003  0.000  0.005  0.005  0.005

DATA SET 1   IDT    IDA    IDC     IDR     IDL    TI2     PDP     PD     R2     IDC12   IDC45  PMIN   PMAX
OUTBOARD 0.1150 0.0656 0.0298 0.0364 0.4674 0.0111 1.2623 1.0008 0.9630 0.0171 0.0298 0.8995 1.0006
INBOARD  0.0978 0.0699 0.0275 0.0431 0.5296 0.0031 1.2619 0.9994 0.9737 0.0207 0.0275 0.9056 1.0009

DATA SET 2
OUTBOARD 0.1050 0.0659 0.0935 0.0364 0.8083  1.0133 1.2412 0.9630 0.0935 0.8995 1.0006
INBOARD  0.0978 0.0699 0.0924 0.0431 0.6418  1.0108 1.2425 0.9737 0.0417 0.9056 1.0009

PSTCE1 PSTCE2 PSTCE3 PSTCD1 PSTCD2 PSTCD3 PSTC11 PSTC12 PSTC13 PSTRD1 PSTRD2 PSTRD3 PSTR11 PSTR12 PSTR13
6.12  7.57  6.99  0.00  0.00  0.00  0.00  0.00  0.00  14.13  7.55  12.75  14.00  7.45  76.85

*** STEADY STATE ***

| PART | POINT | PROJECT | TEST | DATE | DAY HR MIN SEC | ERCODE MODE | SET/DATE | WIND-OFF | AEDC PROPULSION WIND TUNNEL |
|---|---|---|---|---|---|---|---|---|---|
| 52C | 1 | R41T-D2A | TF419 | 9/28/76 | 2221 61 111 37 | 0 0 | 3110/22/76 567/ | -1 | TRANSONIC 16T |

| M | PT | P | Q | REX10-6 | TT | PTA-1 | PTB-2 | PGA-1 | PCB-2 | TTA-1 | TTB-0 | PTI | NCN | NAE | NAM | TPR | NA/WT | MB | SCHED |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 0.599 | 1471.1 | 1061.1 | 363.3 | 2.489 | 569 | 1471.1 | 1471.9 | 1070.7 | 1070.9 | 109 | 110 | 1169.7 | 0-0.00 | 0.00 | 1.258 | 0.0063 | 0.700 | 1 | |

ALPHA BETA VANEO VANEI SHOCK TUBE SELECT   140 S19 L7 J27 E10 U1 M6 G34-2 W8-1 H16-1 N30-1 B5-1 C3
1.0   4.993  19.85  14.85   5820   R8=-1S/ARG9=1R2.1.AB10=1R.5.AB20=1S0.HLG2.733.HI12.726.CB0.UBS

| | P2 | WFR2 | MFR100 | W2R | W2R-FS | TI2 | IDT | IDR | IDC | IDL | PD | PDP | IDA |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| OUTBRD | 0.9256 | 0.7453 | 0.7649 | 3.506 | 350.59 | 0.0576 | 0.0907 | 0.0388 | 0.0315 | 0.4966 | 1.0005 | 1.2618 | 0.0647 |
| INBRD | 0.9747 | 0.7433 | 0.7626 | 3.495 | 349.54 | 0.0024 | 0.1100 | 0.0422 | 0.0419 | 0.5691 | 1.0005 | 1.2599 | 0.0631 |

| | M2S | M2 | MA | NSP | TAVG | N2 | CP1SS | CP2SS | CP3SS |
|---|---|---|---|---|---|---|---|---|---|
| OUTBRD | 0.445 | 0.504 | 0.508 | 0.8483 | 0.8201 | 2.270 | 0.752 | 0.765 | 0.719 |
| INBRD | 0.494 | 0.502 | 0.000 | 0.8060 | 0.8208 | 2.261 | | | |

*** RAMP PRESSURES ***                                    *** BLC PLENUM ***

| | PL435 | PL450 | PL470 | PL480 | PL490 | | | |
|---|---|---|---|---|---|---|---|---|
| OUTBRD | 0.8061 | 0.8512 | 0.7733 | 0.8362 | 0.8407 | | | |
| INBRD | 0.7722 | 0.8256 | 0.7664 | 0.8385 | 0.8447 | | | |

*** COWL INTERNAL PRESSURES ***

| | PL020 | PL030 | PL035 | PL045 | | PL543 | PL573 |
|---|---|---|---|---|---|---|---|
| OUTBRD | 0.7940 | 0.7832 | 0.6156 | 0.8598 | | 0.7833 | 0.8052 |
| INBRD | 0.7930 | 0.7761 | 0.8208 | 0.8629 | | 0.7800 | 0.8008 |

*** FLOWMETER PRESSURE ***                          *** CONTROL PARAMETERS ***

| | PL681 | PL682 | PL683 | PL690 | PL691 | PL692 | PL693 | | PL702 | PL703 | PL704 | PL700 | PL701 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| OUTBRD | 0.5406 | 0.5406 | 0.5387 | 0.3970 | 0.3683 | 0.3929 | 0.3925 | | 0.9340 | 0.7923 | 0.7780 | 0.9996 | 0.8379 |
| INBRD | 0.5399 | 0.5396 | 0.5394 | 0.3964 | 0.3939 | 0.3960 | 0.3985 | | 0.9886 | 0.7976 | 0.7773 | | |

*** OUTBOARD PT2/PTC ***                            *** INBOARD PT2/PTC ***

| RING | 22.5 DEG | 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 | 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 1.000 | 0.993 | 0.998 | 1.000 | 1.000 | 1.001 | 1.001 | 1.000 | 1.001 | 1.001 | 1.001 | 1.000 | 1.001 | 1.001 | 1.001 |
| 2 | 0.972 | 0.973 | 0.986 | 1.001 | 1.001 | 0.994 | 1.000 | 1.000 | 0.993 | 1.000 | 1.001 | 1.000 | 0.994 | 0.999 | 1.000 |
| 3 | 0.981 | 0.952 | 0.977 | 1.001 | 0.995 | 0.957 | 0.997 | 1.000 | 0.995 | 0.952 | 1.000 | 1.000 | 0.950 | 0.982 | 0.997 |
| 4 | 0.980 | 0.937 | 0.972 | 0.991 | 0.957 | 0.928 | 0.959 | 0.999 | 0.943 | 0.917 | 1.000 | 0.992 | 0.941 | 0.954 | 0.958 |
| 5 | 0.958 | 0.918 | 0.954 | 0.953 | 0.936 | 0.913 | 0.926 | 0.979 | 0.934 | 0.894 | 0.943 | 0.979 | 0.943 | 0.933 | 0.912 |

*** OUTBOARD RMS2 ***                               *** INBOARD RMS2 ***

| RING | 22.5 DEG | 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 | 67.5 | 112.5 | 157.5 | 202.5 | 247.5 | 292.5 | 337.5 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 0.005 | 0.006 | 0.004 | 0.003 | 0.003 | 0.003 | 0.003 | 0.003 | 0.001 | 0.001 | 0.001 | 0.001 | 0.001 | 0.000 | 0.001 |
| 2 | 0.000 | 0.013 | 0.011 | 0.003 | 0.005 | 0.007 | 0.009 | 0.006 | 0.004 | 0.003 | 0.001 | 0.001 | 8.888 | 0.004 | 0.002 |
| 3 | 0.006 | 0.012 | 0.014 | 0.012 | 0.011 | 0.009 | 0.012 | 0.013 | 0.005 | 0.003 | 0.000 | 0.002 | 0.004 | 0.003 | 0.004 |

| DATA SET 1 | IDT | IDA | IDC | IDR | IDL | TI2 | PD | PDP | R2 | IDC12 | IDC45 | PMIN | PMAX |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| OUTBRD | 0.0907 | 0.0647 | 0.0315 | 0.0388 | 0.4966 | 0.0576 | 1.0003 | 1.2618 | 0.9756 | 0.0116 | 0.0315 | 0.9125 | 1.0011 |
| INBRD | 0.1100 | 0.0831 | 0.0419 | 0.0422 | 0.5691 | 0.0024 | 1.0005 | 1.2599 | 0.9747 | 0.0031 | 0.0419 | 0.8936 | 1.0009 |

| DATA SET 2 | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| OUTBRD | 0.0907 | 0.0647 | 0.0863 | 0.0388 | 0.7720 | 0.0076 | 1.0106 | 1.2444 | 0.9756 | 0.0863 | 0.0395 | 0.9125 | 1.0011 |
| INBRD | 0.1100 | 0.0831 | 0.1087 | 0.0422 | 0.9385 | 0.0024 | 1.0140 | 1.2370 | 0.9747 | 0.1087 | 0.0537 | 0.8936 | 1.0009 |

| PSTCE1 | PSTCE2 | PSTCE3 | PSTCD1 | PSTCD2 | PSTCD3 | PSTCI1 | PSTCI2 | PSTCI3 | PSTRD1 | PSTRD2 | PSTRD3 | PSTRI1 | PSTRI2 | PSTRI3 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 7.59 | 7.58 | 6.95 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 144.15 | 7.85 | 7.00 | 26.90 | 7.50 | 6.40 |

*** STEADY STATE ***

PART POINT PROJECT TEST      DATE      DAY HR MIN SEC      ERCODE MODE      SET:DATE  WIND-OFF      AEDC PROPULSION WIND TUNNEL
521  1  B4:T:D2A  TF419  9/28/26  2721.71.191.28           0    0  3110/22/76.5727  -1             TRANSONIC 16T

M     PT     P     Q     REX10-6   TT   PTA-1  PTR-2  PCA-1  PCB-2  PTA-1  TTB-0  PTI  NCN  WAE  WAM  IPR  WA/WT  WB  SCHED
0.701 1470.3 1050.0 364.3 2.492  569 1470.3 1471.2 1048.6 1089.0  110 1173.4  0-0.00 0.00 1.253 0.0063 0.700  1

ALPHA  BETA  VANFO  VANEI  SHOCK TUBE SELECT      140 S19 L7 J27 E10 U1 M6 G34-2 W8-1 M16-1 N30-1 B5-1 C3
1.0  -0.004 24.62 26.88       5215                RBC-1E2.RC0-1s2.1.AB10-1s.5.AB20-1s0.HL0s2.733.HI1s2.726.C=0.UHS

       P2     WFR2    WFR100   W2R     W2R-FS   T12     IDT     IDR     IDC     IDL     PD     PDP     IDA
OUTBOARD 0.9965 0.6524 0.6613  3.034  303.42  0.0261  0.0701  0.0266  0.0268  0.3601  0.9946 1.2709  0.0541
INBOARD  0.9982 0.6597 0.6585  3.022  302.15  0.0030  0.0049  0.0294  0.0234  0.3750  0.9937 1.2215  0.0516

       M2S    M2     MA     NSP     IAVG    W2     CP1SS  CP2SS  CP3SS
OUTBOARD 0.407 0.418 0.579 0.8595 0.6747  1.986  0.734  0.769  0.735
INBOARD  0.435 0.412 0.000 0.8626 0.8790  1.981

*** RAMP PRESSURES ***                              *** COWL INTERNAL PRESSURES ***                    *** BLC PLENUM ***

       PL435  PL450   PL470   PL480   PL490          PL020  PL030  PL035  PL045                       PL541  PL523
OUTBOARD 0.6449 0.8571 0.8437 0.8647 0.8860          0.8534 0.8505 0.8708 0.9028                      0.6129 0.8592
INBOARD  0.8515 0.8898 0.8436 0.8915 0.8950          0.8597 0.8595 0.8788 0.9090                      0.8073 0.8627

       *** FLOWMETER PRESSURE ***                   *** CONTROL PARAMETERS ***

       PL680  PL681   PL682   PL683   PL690   PL691  PL692  PL693    PL722  PL703  PL704  PL700  PL701
OUTBOARD 0.5199 0.5232 0.5201 0.5205 0.5189 0.4180 0.4146 0.4165   0.9986 0.8583 0.8467 0.9992 0.7701
INBOARD  0.5204 0.5223 0.5196 0.5199 0.4186 0.4186 0.4170 0.4190   0.9995 0.8621 0.8506       0.7963

*** OUTBOARD PT2/PT5 ***                                           *** INBOARD PT2/PT0 ***

RING   22.5DEG  67.5   112.5  157.5  202.5  247.5  292.5  337.5    22.5   67.5  112.5 157.5  202.5  247.5  292.5  337.5
  1    1.001   1.000  1.000  1.002  1.001  1.300  1.001  1.001    1.000  1.000 1.001 1.001  1.001  1.000  1.001  1.000
  2    1.001   1.001  1.001  1.002  1.001  0.996  0.999  1.000    1.001  1.000 1.001 1.001  1.001  1.001  1.001  1.001
  3    1.000   0.998  0.993  0.905  1.000  0.974  0.978  0.994    1.000  0.985 0.998 1.001  1.000  1.000  0.995  1.001
  4    0.922   0.985  0.985  1.000  0.989  0.963  0.953  0.963    0.974  0.959 0.973 0.989  0.999  1.000  0.982  0.989
  5    0.974   0.969  0.966  0.979  0.959  0.956  0.933  0.943    0.943  0.937 0.959 0.972  0.986  0.967  0.953

*** OUTBOARD RMS2 ***                                              *** INBOARD RMS2 ***

RING   22.5DEG  67.5   112.5  157.5  202.5  247.5  292.5  337.5    22.5   67.5  112.5 157.5  202.5  247.5  292.5  337.5
  1    0.003   0.003  1.000  0.003  0.003  0.003  0.003  0.003    0.003  0.001 0.001 0.001  0.001  0.003  0.001  0.000
  2    0.005   0.006  0.003  0.007  0.006  0.011  0.008  0.003    0.008 -1.000 0.001 0.001  0.001  0.003  0.003  0.001
  5    0.006   0.003  0.009  0.009  0.009  0.007  0.009  0.009    0.008  0.009 0.007 0.000  0.000  0.002  0.002  0.010

DATA SET 1  IDT     IDA     IDC     IDR     IDL     T12     IDT     IDR     IDC     IDL     PDP     PD     PMIN    PMAX
OUTBOARD    0.0701  0.0541  0.0268  0.0266  0.3601  0.0061  0.0266  0.0268  0.3601  0.9946 1.2709  0.9332 1.0024
INBOARD     0.0649  0.0516  0.0234  0.0294  0.3750  0.0030  0.0294  0.0234  0.3750  0.9937 1.2215  0.9372 1.0013

DATA SET 2
OUTBOARD    0.0701  0.0541  0.0681  0.0266  0.5888         1.0029 1.2567 0.9865  0.0268  IDC12  IDC45  0.9332 1.0024
INBOARD     0.0649  0.0516  0.0642  0.0294  0.5816         1.0013 1.2587 0.9882  0.0642  0.0681 0.0370 0.9332 1.0024
                                                                                                    0.0343 0.9372 1.0013

       PSTCE1  PSTCE2  PSTCE3  PSTCD1  PSTCD2  PSTCD3  PSTC11  PSTC12  PSTC13  PSTRD1  PSTRD2  PSTRD3  PSTRI1  PSTRI2  PSTRI3
        7.59    6.94    0.00    0.00    0.00    0.00    0.00   14.15   12.30  112.25   14.15   59.15   14.15

*** STEADY STATE ***

PART PCINT PROJECT TEST     DATE   DAY HR MIN SEC     ERCODE MODE   SETIDATE  WIND-OFF     AEDC PROPULSION WIND TUNNEL
574  2 P411-02A TF519 9/28/26 2721 71 281 38        0    0   3110/27/76 522/  -1              TRANSONIC 16T

M      PT      P      Q   REX10-6  TT  PTA-1  PTB-2  PCA-1  PCB-2  TTA-1 ITB-0  PTI NCN  MAE  MAM  TPR  WA/WT  WB SCHED
0.731 1467.6 1057.2 303.5  2.487  569 1467.6 1468.2 1046.8 1067.0  110  1171.7  0-0.00 0.00 1.253 0.0063 0.700  1

ALPHA  BETA VANED VANEI SHOCK TUBE SELECT    140 S19 L7 J27 E10 U1 M6 G34-2 W8-1 H16-1 N30-1 B5-1 C3
1.0 -0.052 24.75 21.09      3317               RB2=1e7,AC0=1e2,1,AB1C=1e5,AB2O=1e0,HL0=2.733,HL1=2.726,C=0.uES

*** RAMP PRESSURES ***                          *** COWL INTERNAL PRESSURES ***              *** BLC PLENUM ***

*** FLOWMETER PRESSURE ***

*** OUTBOARD PT2/PTD ***                         *** INBOARD PT2/PTD ***

*** CONTROL PARAMETERS ***

*** OUTBOARD RMS2 ***                            *** INBOARD RMS2 ***

*** STEADY STATE ***

AEDC PROPULSION WIND TUNNEL

RUN POINT PROJECT TEST     DATE    DAY HR MIN SEC     SET-DATE  WIND-OFF     ERCODE MODE

*** FAMP PRESSURES ***

*** DUCT INTERNAL PRESSURES ***

*** SEC PLENUM ***

*** FLOWMETER PRESSURE ***

*** CONTROL PARAMETERS ***

*** OUTBOARD RMS2 ***

*** INBOARD RMS2 ***

DATA SET 2

*** STEADY STATE ***

AEDC PROPULSION WIND TUNNEL
TRANSONIC 16T

PART PCINT PROJECT TEST    DATE    DAY HR MIN SEC    ERCODE MODE    SET:DATE    WIND-OFF

*** COWL INTERNAL PRESSURES ***

*** RAMP PRESSURES ***

*** FLOWMETER PRESSURE ***

*** CONTROL PARAMETERS ***

*** BLC PLENUM ***

*** OUTBOARD PT2/PTO ***

*** INBOARD PT2/PTO ***

*** OUTBOARD RMS2 ***

*** INBOARD RMS2 ***

*** STEADY STATE ***

AEDC PROPULSION WIND TUNNEL

| EAST PCINT | PROJECT | TEST | DATE | DAY | HR | MIN | SEC | ERCODE | MODE | SET:DATE | WIND-OFF |
|---|---|---|---|---|---|---|---|---|---|---|---|

*** RAMP PRESSURES ***

*** FLOWMETER PRESSURE ***

*** CONL INTERNAL PRESSURES ***

*** BLC PLENUM ***

*** CONTROL PARAMETERS ***

*** OUTBOARD PT2/PTO ***

*** INBOARD PT2/PTO ***

*** OUTBOARD RMS2 ***

*** INBOARD RMS2 ***

211

*** STEADY STATE ***

EAST POINT PROJECT TEST    DATE    DAY HR MIN SEC    ERCODE MODE    SET+DATE WIND-OFF    AETC PROPULSION WIND TUNNEL
                                                                                        TRANSONIC  1PT

ALPHA  BETA  VANEO  VANEI  SHOCK TURF SELECT

*** COWL INTERNAL PRESSURES ***

*** OLG PLENUM ***

*** RAMP PRESSURES ***

*** FLOWMETER PRESSURE ***

*** CONTROL PARAMETERS ***

*** OUTBOARD PT2/PT0 ***

*** INBOARD PT2/PT0 ***

*** OUTBOARD RMS2 ***

*** INBOARD RMS2 ***

DATA SET 4

DATA SET 5

*** STEADY STATE ***

PART POINT PROJECT TEST     DATE   DAY HR MIN SEC    ERCODE MODE    SET DATE  WIND-OFF    AEDC PROPULSION WIND TUNNEL
    AEDC-TR-76-107

|   | B1 | B | B | REYN=6 | TT | PTA-1 | PTB-2 | PCA=1 | PCB=0 | TTA=0 | TTA=1 | TTB=1 | PT1 | NR | ... | WEFMT | WB | SCHED |
|---|----|---|---|--------|-----|-------|-------|-------|-------|-------|-------|-----|-----|-----|-------|------|-------|

ALPHA   BETA   VANE1   VANE1   SHOCK TUBE SELECT

| | RP | MFB2 | MFB100 | MBB | MBB-FS | TT2 | TPT | IDR | IDC | IPL | PT | PNP | IDA |
|---|----|------|--------|-----|--------|------|------|-----|-----|-----|-----|-----|-----|
| OUTBOARD | 0.949 | 0.8522 | 0.9797 | 1.514 | 351.45 | 0.0085 | 0.0999 | 0.0404 | 0.0293 | 0.5007 | 1.0008 | 1.2612 | 0.0667 |
| INBOARD | 0.9441 | 0.8444 | 0.8714 | 1.491 | 348.13 | 0.0030 | 0.1068 | 0.0435 | 0.0108 | 0.5326 | 1.0001 | 1.2600 | 0.0743 |

*** RAMP PRESSURES ***

*** PLC PLENUM ***

*** CONTROL PARAMETERS ***

*** INTERNAL PRESSURES ***

*** FLOWMETER PRESSURE ***

*** OUTBOARD RMS2 ***

*** INBOARD RMS2 ***

DATA SET 1

DATA SET 2

*** STEADY STATE ***

EAST POINT PROJECT TEST    DATE    DAY HR MIN SEC    ERCODE MODE    SET:DATE WIND-OFF    AEDC PROPULSION WIND TUNNEL

*** RAMP PRESSURES ***

*** FLOWMETER PRESSURE ***

*** OUTBOARD PT2/PTD ***

*** OUTBOARD RMS2 ***

*** CORE INTERNAL PRESSURE ***

*** QLC PLENUM ***

*** CONTROL PARAMETERS ***

*** INBOARD PT2/PTD ***

*** INBOARD RMS3 ***

DATA SET 1

DATA SET 2

214

*** STEADY STATE ***

TEST POINT PROJECT TEST    DATE    DAY HR MIN SEC    SET DATE    WIND-OFF    AEDC PROPULSION WIND TUNNEL

*** AXD PRESSURES ***

*** COWL INTERNAL PRESSURES ***

*** FLOWMETER PRESSURE ***

*** CONTROL PARAMETERS ***

*** OUTBOARD PI2/PIO ***

*** PLC-PLENUM ***

*** INBOARD PI2/PIO ***

*** OUTBOARD RMS2 ***

*** INBOARD RMS2 ***

215

*** STEADY STATE ***

PART POINT PROJECT TEST    DATE    DAY HR MIN SEC    ERCODE MODE    SET:DATE WIND-OFF    AEDC PROPULSION WIND TUNNEL

ALPHA  BETA  VANFO  VANEI  SHOCK TUBE SELECT

*** RAMP PRESSURES ***

*** FLOWMETER PRESSURE ***

*** OUTBOARD PIP/PIO ***

*** COWL INTERNAL PRESSURES ***

*** INBOARD PIP/PIO ***

*** CONTROL PARAMETERS ***

*** BLC PLENUM ***

*** OUTBOARD RMS2 ***

*** INBOARD RMS2 ***

*** STEADY STATE ***

| BEST POINT | PROJECT | TEST | DATE | DAY | HR | MIN | SEC | ERCODE | MODE | SETIDATE | WIND-OFF | AEDC PROPULSION WIND TUNNEL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|

ALP=4   BETA   VANEO   VANEI   SHOCK   TURF   SELECT

*** RAMP PRESSURES ***

*** COWL INTERNAL PRESSURES ***

*** PLC PLENUM ***

*** FLOWMETER PRESSURE ***

*** CONTROL PARAMETERS ***

*** OUTBOARD PT2/PTO ***

*** INBOARD PT2/PTO ***

*** OUTBOARD RMS2 ***

*** INBOARD RMS2 ***

217

*** STEADY STATE ***

| PRDT POINT PROJECT TEST | DATE | DAY HR MIN SEC | ERCODE MODE | SET/DATE | WIND-OFF | AEDC PROPULSION WIND TUNNEL |
|---|---|---|---|---|---|---|

*** RAMP PRESSURES ***

*** COWL INTERNAL PRESSURES ***

*** FLOWMETER PRESSURE ***

*** CONTROL PARAMETERS ***

*** BLC PLENUM ***

*** OUTBOARD R12/PTO ***

*** INBOARD R12/PTO ***

*** OUTBOARD RMS2 ***

*** INBOARD RMS2 ***

DATA SET 1

DATA SET 2

218

*** STEADY STATE ***

PART POINT PROJECT TEST      DATE   DAY HR MIN SEC      ERCODE MODE     SET:DATE WIND-OFF     AEDC PROPULSION WIND TUNNEL

*** RAMP PRESSURES ***

*** COWL INTERNAL PRESSURE ***

*** BLC-PLENUM ***

*** FLOWMETER PRESSURE ***

*** CONTROL PARAMETERS ***

*** OUTBOARD PI2/PIO ***

*** INBOARD PI2/PIO ***

*** OUTBOARD RMS2 ***

*** INBOARD RMS2 ***

*** STEADY STATE ***

AEDC PROPULSION WIND TUNNEL

PART POINT PROJECT TEST     DATE   DAY HR MIN SEC      ERCODE MODE   SETIDATE WIND-OFF
Transonic 1CT

*** FWD PRESSURES ***

*** COWL INTERNAL PRESSURE ***

*** PLC PLENUM ***

*** FLOWMETER PRESSURE ***

*** CONTROL PARAMETERS ***

*** OUTBOARD PI2/PIO ***

*** INBOARD PI3/PIO ***

*** OUTBOARD RMS2 ***

*** INBOARD RMS2 ***

220

*** STEADY STATE ***

PART POINT PROJECT TEST    DATE    DAY HR MIN SEC    ERCODE MODE    SET:DATE  WIND-OFF    AEDC PROPULSION WIND TUNNEL

RE*10-6  TT   PTA-1  PTB-2  PCA-2  PCB-2  TTA-1  TTB-0  PTI-NON  NAF  YAW  TDB  WZ/HT  MB  SCWEN

ALPHA  BETA  VANE0  VANE1  SHOCK TUBE SELECT

|  |  R2 | MFR2 | MFK100 | W2R | W2R-FS | TI2 | IDT | IDC | IDA | PT | POP | IDA |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| CUT2CARD |  |  |  |  |  |  |  |  |  |  |  |  |
| TABCARD |  |  |  |  |  |  |  |  |  |  |  |  |

|  | M2E | M2 | M4 | W5P | TAVG | W2 | CP:SS | CP:SS |
|---|---|---|---|---|---|---|---|---|
| CUT2CARD |  |  |  |  |  |  |  |  |
| TABCARD |  |  |  |  |  |  |  |  |

*** RAMP PRESSURES ***

*** COWL INTERNAL PRESSURES ***

*** DPC PLENUM ***

*** FLOWMETER PRESSURE ***

*** CONTROL PARAMETERS ***

*** OUTBOARD PT2/PT0 ***

*** INBOARD PT2/PT0 ***

*** OUTBOARD RMS2 ***

*** INBOARD RMS2 ***

DATA SET 1

DATA SET 2

PSTCE1  PSTCE2  PSTCE3  PSTCD1  PSTCD2  PSTCD3  PSTCI1  PSTCI2  PSTCI3  PSTRD1  PSTRD2  PSTRI2  PSTRI3

*** STEADY STATE ***

PAST POINT PROJECT TEST   DATE   DAY HR MIN SEC        ERCODE MODE    SET:DATE WIND-OFF    AEDC PROPULSION WIND TUNNEL

ALPHA   BETA   VANEO  VANEI   SHOCK TUBE SELECT

*** BLT PLENUM ***

*** COWL INTERNAL PRESSURES ***

*** RAMP PRESSURES ***

*** FLOWMETER PRESSURE ***

*** CONTROL PARAMETERS ***

*** OUTBOARD BT2/BTO ***

*** INBOARD BT2/BTO ***

*** OUTBOARD RMS2 ***

*** INBOARD RMS2 ***

DATA SET 1

DATA SET 2

*** STEADY STATE ***

PART PCINT PROJECT TEST     DATE   DAY HR MIN SEC     ERCODE MODE     SETIDATE  WIND-OFF    AEDC PROPULSION WIND TUNNEL
                                   9/29/76 273? 6:26:15           0      21022/76 8757  7          TRANSONIC TET

P1      P2      R       REYNC/A  TT  PTA-1  PTA-2  PCA-1  PCA-2  TT1-1  TTRP1  PT1  VCN   WA4  KW  TPP  KWMT  PB  SCHED
0.95° 1601.0 1055.4 534.0   3.174  560 1603.9 1694.8 1069.6 1069.5 110  111 1727.6  0.00.00 1.276 0.247 0.450  1

ALPHA  BETA  VANEO  VANE1  SHOCK TUBE SELECT   140 S19 L7 J27 E19 L3 M6 G34-2 W8-J W14-1 A30-1 P5-1 C3
3.0                                      5070

         P3     MFP2   MFP10R         M3R    M3R-FS     T12      IDT      IDA      IDC       IPL       PT      PNP     TDA
OUTBCARD  0.9840 0.6013 0.6105       7.001  300.14    0.0064  0.0705   0.0274   0.0277   0.3921   0.9055  1.2494  0.0541
INBCARD   0.9041 0.6014 0.6060       2.989  299.90    0.0040  0.0436   0.0040   0.0256   0.3454   0.0934  1.2714  0.0555

          M3S    M3     M3            NSP    TAVG      M2      CP155    CP255    CP355
OUTBCARD  0.601  0.413  0.671       0.8502 0.8758    2.259   0.646    0.700    0.646
INBCARD   0.399         0.616       0.8677 0.8608    2.259

*** RAMP PRESSURES ***                        *** COWL INTERNAL PRESSURES ***           *** BLC PLENUM ***

          PL655  PL660  PL650         PL480  PL490  PL400      PL620    PL630    PL640    PL645              PL5?3  PL5?5
OUTBCARD  0.8512 0.8771 0.8060       0.857  0.8934 0.8964     0.8833  0.8526  0.8723  0.9040            0.7846 0.8551
INBCARD   0.8014 0.8764 0.8450       0.8950                   0.8604  0.8534  0.8402  0.9123            0.7707 0.8594

*** FLOWMETER PRESSURE ***                    *** CONTROL PARAMETERS ***

          PL650  PL662  PL663         PL600  PL601  PL602      PL603                                     PL707  PL708  PL709
OUTBCARD  0.4754 0.475R 0.4754       0.4754 0.4754 0.3576     0.3541  0.3548                 0.9904 0.8587 0.8475 1.0006 0.7397
INBCARD   0.4762 0.4753 0.4756       0.4746 0.3548 0.3544     0.3563  0.3559                 0.9997 0.8635 0.8577

*** OUTBOARD PT2/PTO ***                      *** OUTBOARD-PT2/PTO ***                    *** INBOARD-PT2/PTO ***

RING 22.5DEG  47.5  112.5  157.5    202.5  247.5  292.5  337.5    22.5  67.5  112.5  157.5  202.5  247.5  292.5  337.5
  1   1.001  1.001  1.001  1.001    1.001  1.001  1.001  1.001   1.001  1.001  1.001  1.001  1.001  1.001  1.001  1.001
  2   1.008  1.001  1.001  1.001    1.003  1.000  1.000  1.041   1.001  1.000  1.000  1.001  1.001  1.001  1.001  1.041
  3   0.997  1.001  1.001  0.999    0.974  0.962  0.987  1.001   0.994  0.998  1.001  1.001  1.001  1.001  0.099  1.001
  4   0.974  1.000  0.095  0.084    0.940  0.944  0.975  0.996   0.958  0.959  0.947  1.000  1.000  0.099  1.000  0.996
  5   0.047  0.078  0.973  0.955    0.932  0.944  0.938  0.059   0.943  0.956  0.961  0.976  0.027  0.991  0.073  0.059

*** OUTBOARD RMS2 ***                         *** INBOARD RMS2 ***

DATA SET 0  IDT    IDA     IDC       IDL     IDR     T12     IDL     T12      PD       PCP     R2      PMIN    PMAX
OUTBCARD  0.0705 0.0541  0.0274     0.0283  0.0274  0.0064  0.0064  0.0064  0.9055  1.2694  0.9949  0.9774  1.0011
INBCARD   0.0436 0.0515  0.0250     0.0277  0.0436  0.0640  0.0640  0.0931  0.9091  0.9891  0.9940  0.9742  1.0014

DATA SET 2
OUTBCARD  0.0305 0.0544  0.0401     0.0381  0.0383  0.0243  1.044  1.2544  1.0017  0.9901  0.8661  0.9814  1.0011
INBCARD   0.0436 0.0515  0.0431     0.0277  0.5409  1.0017  1.2582  0.9901  0.0354  0.0631  0.9742  1.0014

          PSTCE1  PSTCE2  PSTCE3  PSTCD1  PSTCD2  PSTCD3  PSTC11  PSTC12  PSTC13  PSTD1  PSTD2  PSTD3  PSTQ11  PSTQ12  PSTQ13
            7.40   7.24    7.44   0:00    0:00    0:00    0:00    0:00    0:00   0:00  112:15 112:15  6:25   6:05   74:45   7.70   6.45

*** STEADY STATE ***

AEDC PROPULSION WIND TUNNEL

*** LOCAL INTERNAL PRESSURES ***

*** PLC PLENUM ***

*** RAMP PRESSURES ***

*** CONTROL PARAMETERS ***

*** FLOWMETER PRESSURE ***

*** INBOARD P12/BIG ***

*** OUTBOARD P12/PIO ***

*** OUTBOARD BMS2 ***

*** INBOARD BMS3 ***

*** STEADY STATE ***

EAST POINT PROJECT TEST    DATE  DAY HR MIN SEC        ERCODE MODE    SETIDATE WIND-OFF    AEDC PROPULSION WIND TUNNEL

ALPHA  BETA  VANEO  VANEI  SHOCK TUBF SELECT

*** RAMP PRESSURES ***

*** COWL INTERNAL PRESSURES ***

*** PLC PLENUM ***

*** FLOWMETER PRESSURE ***

*** CONTROL PARAMETERS ***

*** INBOARD PT2/PTO ***

*** INBOARD RMS2 ***

*** OUTBOARD PT2/PTO ***

*** OUTBOARD RMS2 ***

225

436762

*** STEADY STATE ***

TEST  PROJECT  TEST    DATE    DAY HR MIN SEC     ERCODE MODE     SET+DATE  WIND OFF     SEC PROPULSION WIND TUNNEL
420  5 P41T-02A TF910  0/29/76 273I 61 421 52       0     0    2110/02/76 618/ -1          TRANSONIC 16T

M      DT     D      G    REX10-6  TT   PTA-1  PTA-1 PCA-1 PCR-2 TTA-1 TTP-C PTI NCN  NAF NIN TPD WE/WT  MB  SCHED

*** DAMP PRESSURES ***                          *** BLF PLENUM ***

*** COWL INTERNAL PRESSURES ***

*** CONTROL PARAMETERS ***

*** FLOWMETER PRESSURE ***

*** OUTBOARD PT2/PTO ***                         *** INBOARD PT2/PTO ***

*** OUTBOARD RMS2 ***                            *** INBOARD RMS2 ***

*** STEADY STATE ***

| TEST PNT. | PRO-SET TEST | DATE | DAY-HR-MIN-SEC | ERCODE MODE | SET-DATE | WIND-OFF | SEC. PROPULSION WIND-TUNNEL |
|---|---|---|---|---|---|---|---|
| 421 | PAIT-02A TF410 | 6/29/75 273: 6: 48: 37 | | 0 0 | 2:10/24/76 (18/ -1 | | TRANSONIC 16T |

*** BLC PLENUM ***

*** COAL INTERNAL PRESSURES ***

*** CONTROL PARAMETERS ***

*** BAND PRESSURES ***

*** FLOWMETER PRESSURE ***

*** OUTBOARD PT2/PTO ***

*** INBOARD PT2/PTO ***

*** OUTBOARD R-52 ***

*** INBOARD R-52 ***

*** STEADY STATE ***

*** STEADY STATE ***

TEST POINT PROJECT TEST        DATE   DAY HR MIN SEC       ENGINE MODE      SET DATE   WIND-OFF    AERO PROPULSION WIND TUNNEL
625   2  E41T-DDA  TF41Q  9/29/76  273: 7: 36: 46          0     0   2:10/24/76 623/   -1          TRANSONIC 16T

M     RT     P     C    REXIO-6  TT  PTA-1  PTR-2  PCA-1  PCR-2  TTA-1  TTR-0  PTI  NCN  WAF  WAM  TPP  WA/WT  WB  SCHED

ALPHA  BETA  VANEO  VANEI   SHOCK TUBE SELECT
3.0

*** RAMP PRESSURES ***

*** COWL INTERNAL PRESSURES ***

*** BLC PLENUM ***

*** FLOWMETER PRESSURE ***

*** CONTROL PARAMETERS ***

*** OUTBOARD PT2/PTO ***

*** INBOARD PT2/PTO ***

*** OUTBOARD RMS2 ***

*** INBOARD RMS2 ***

DATA SET 1

DATA SET 2

229

*** STEADY STATE ***

ARC PROPULSION WIND TUNNEL
TRANSONIC 16T

PART POINT PROJECT TEST DATE DAY HR MIN SEC FRCODE MODE SET:DATE WIND-OFF
A26 1 P4T-524 TF410 9/20/76 273: 7: 38: 54 0 0 2:10/24/76 623/ -1

*** BLC PLENUM ***

*** COAL INTERNAL PRESSURES ***

*** CONTROL PARAMETERS ***

*** RAMP PRESSURES ***

*** FLOWMETER PRESSURE ***

*** OUTBOARD PT2/PTO ***   *** INBOARD PT2/PTO ***

*** OUTBOARD RMS2 ***   *** INBOARD RMS2 ***

230

## APPENDIX C

### LIST OF COMMON SYMBOLS AND CONVENTIONS

d     shock tube diameter
IDA   average distortion index
IDC   total circumferential distortion index
IDL   stall margin allocation ratio              see Table 5.1
IDR   total radial distortion index
IDT   total distortion index
M     Mach number
PSi   overpressure at i'th claw probe (i=1,2,3)
$\Delta p$    shock overpressure at blast arrival (scaled to 1 atm. ambient pressure conditions)
p     pressure
$p_o$    pre-blast tunnel ambient pressure
$p_t$    total pressure
$p_{t_o}$   pre-blast tunnel total pressure
$p_{t_2}$   average engine face total pressure (psf)

R2I   average engine face total pressure for inboard inlet (nondimensional)
R2O   average engine face total pressure for outboard inlet (nondimensional)
r     distance from end of shock tube
SM    fan stall margin (Sec. 8.3)
TT    pre-blast tunnel total temperature ($^O$R)
W2    engine-face weight flow
W2R   engine-face weight flow corrected to standard conditions (for full scale inlet (lb/sec)
      $W2R = W2 \times (TT/519)^{1/2} / (P_{t_2}/2116)$
$\beta$    side-slip angle
$\theta$    polar angle from shock tube axis
$\Phi$    angle between shock tube axis and wind tunnel axis
$\phi$    blast intercept angle (between a normal to the blast front and the inlet longitudinal axis)

Notes:

    In most pressure plots in this report the ordinate label designates the variable measured and the vertical scale is either pressure/$p_t$ or pressure/$p_o$, the latter being designated by an asterisk after the label.

    All blast pressure values in this report designated as $\Delta p$ are scaled to a tunnel ambient pressure of one atmosphere. The actual test values can be obtained by dividing $\Delta p$ by the ambient pressure in atmospheres (obtained from P in Appendix B).

    Inlet mass flow rates in this report are always expressed in terms of full scale inlet conditions. To obtain model values divide by 100.

    A separate table of symbols is provided for Appendix B in that appendix.

231

# DISTRIBUTION LIST

DEPARTMENT OF DEFENSE

Assistant to the Secretary of Defense
Atomic Energy
    ATTN: Executive Assistant

Defense Documentation Center
12 cy ATTN: DD

Defense Nuclear Agency
    ATTN: SPAS
    ATTN: DDST
    ATTN: STSP
4 cy ATTN: TITL

Field Command
Defense Nuclear Agency
    ATTN: FCPR

Livermore Division, Fld. Command, DNA
Lawrence Livermore Laboratory
    ATTN: FCPRL

Commandant
NATO School (SHAPE)
    ATTN: U.S. Documents Officer

Under Secy. of Def. for Rsch. & Engrg.
    ATTN: Strategic & Space Systems (OS)
    ATTN: Strategic & Space Systems, M. Atkins

DEPARTMENT OF ARMY

Harry Diamond Laboratories
Department of the Army
    ATTN: DELHD-N-NP
    ATTN: DELHD-N-P, J. Gwaltney

U.S. Army Ballistic Research Labs.
    ATTN: DRXBR-BLE, W. Taylor
    ATTN: DRDAR-BLV, J. Meszaros

U.S. Army Materiel Dev. & Readiness Cmd.
    ATTN: DRCDE-D, L. Flynn

U.S. Army Nuclear & Chemical Agency
    ATTN: Library

DEPARTMENT OF THE NAVY

Naval Material Command
    ATTN: MAT 08T-22

Naval Research Laboratory
    ATTN: Code 2627, Tech. Lib.

Naval Surface Weapons Center
    ATTN: K. Caudle

Naval Weapons Evaluation Facility
    ATTN: L. Oliver

Office of Naval Research
    ATTN: Code 464

Strategic Systems Project Office
    ATTN: NSP-272

DEPARTMENT OF THE AIR FORCE

Aeronautical Systems Division, AFSC
    ATTN: ENFT, R. Bachman
4 cy ATTN: ENFTV, D. Ward

Air Force Aero-Propulsion Laboratory
    ATTN: M. Stibich

Air Force Materials Laboratory
    ATTN: MBE, G. Schmitt

Air Force Weapons Laboratory
    ATTN: DYV, A. Sharp
    ATTN: SUL
    ATTN: DYV, G. Campbell

Foreign Technology Division, AFSC
    ATTN: PDBF, Mr. Spring

Strategic Air Command/XPFS
Department of the Air Force
    ATTN: XPFS, B. Stephan

DEPARTMENT OF DEFENSE CONTRACTORS

Aerospace Corp.
    ATTN: W. Barry

Avco Research & Systems Group
    ATTN: J. Patrick
    ATTN: P. Grady

Boeing Co.
    ATTN: R. Dyrdahl
    ATTN: S. Strack
    ATTN: E. York

Boeing Wichita Co.
    ATTN: R. Syring

Calspan Corp.
    ATTN: M. Dunn

Effects Technology, Inc.
    ATTN: E. Bick
    ATTN: R. Parisse
    ATTN: R. Wengler

General Dynamics Corp.
    ATTN: R. Shemensky

General Electric Co.-TEMPO
Center for Advanced Studies
    ATTN: DASIAC

General Research Corp.
    ATTN: T. Stathacopoulos

Kaman AviDyne
Division of Kaman Sciences Corp.
    ATTN: N. Hobbs
    ATTN: R. Ruetenik
    ATTN: E. Criscione
    ATTN: R. Smiley

Kaman Sciences Corp.
    ATTN: D. Sachs

Los Alamos Technical Assoc., Inc.
    ATTN:  P. Hughes

McDonnell Douglas Corp.
    ATTN:  J. McGrew

Prototype Development Associates, Inc.
    ATTN:  C. Thacker
    ATTN:  J. McDonald

R & D Associates
    ATTN:  C. MacDonald
    ATTN:  J. Carpenter
    ATTN:  F. Field
    ATTN:  A. Kuhl

Rockwell International Corp.
    ATTN:  R. Sparling
    ATTN:  R. Moonan

Sandia Laboratories
    ATTN:  Doc. Con. for A. Lieber

Science Applications, Inc.
    ATTN:  D. Hove

Science Applications, Inc.
    ATTN:  J. Dishon

SRI International
    ATTN:  G. Abrahamson